

Rubycon

引线型铝电解电容器

RADIAL LEAD ALUMINUM ELECTROLYTIC CAPACITORS

ZLJ


ZLJ 系列
SERIES

UPGRADE

105°C 长寿命 低阻抗 高纹波电流品
105°C High Ripple Current, Long Life, Low Impedance

•105°C 6000~10000小时品。
Load Life : 105°C 6000~10000 hours.

RoHS compliance



规格表 / SPECIFICATIONS

项目 Items	特性 Characteristics																																			
工作温度范围 Category Temperature Range	-40~+105°C																																			
额定电压范围 Rated Voltage Range	6.3~100Vdc																																			
静电容量允许差 Capacitance Tolerance	±20% (20°C, 120Hz)																																			
漏电流 Leakage Current(MAX)	小于 $I=0.01CV$ 和 $3\mu A$ 中的较大值 (施加额定电压2分钟后) $I=0.01CV$ or $3\mu A$ whichever is greater. (After 2 minutes) I =漏电流(μA) Leakage Current C =静电容量(μF) Capacitance V =额定电压(Vdc) Rated Voltage																																			
损失角正切值 ($\tan \delta$) Dissipation Factor(MAX)	<table border="1"> <tr> <td>额定电压(Vdc) Rated Voltage</td> <td>6.3</td> <td>10</td> <td>16</td> <td>25</td> <td>35</td> <td>50</td> <td>63</td> <td>80</td> <td>100</td> <td>(20°C, 120Hz)</td> </tr> <tr> <td>$\tan \delta$</td> <td>0.22</td> <td>0.19</td> <td>0.16</td> <td>0.14</td> <td>0.12</td> <td>0.10</td> <td>0.09</td> <td>0.08</td> <td>0.08</td> <td></td> </tr> </table> <p>对于静电容量超过1000μF的产品, 其静电容量每增加1000μF, 则损失角正切值在上表值的基础上加上0.02。 When capacitance is over 1000μF, $\tan \delta$ shall be added 0.02 to the listed value with increase of every 1000μF.</p>		额定电压(Vdc) Rated Voltage	6.3	10	16	25	35	50	63	80	100	(20°C, 120Hz)	$\tan \delta$	0.22	0.19	0.16	0.14	0.12	0.10	0.09	0.08	0.08													
额定电压(Vdc) Rated Voltage	6.3	10	16	25	35	50	63	80	100	(20°C, 120Hz)																										
$\tan \delta$	0.22	0.19	0.16	0.14	0.12	0.10	0.09	0.08	0.08																											
耐久性 Endurance	在105°C环境中, 不超过额定电压的范围内叠加额定纹波电流, 连续加载右表时间后, 满足以下各项要求。 After applying rated voltage with rated ripple current for specified time at 105°C, the capacitors shall meet the following requirements. <table border="1"> <tr> <td rowspan="2">静电容量变化率 Capacitance Change</td> <td rowspan="2">初期值的±25%以内 (6.3Vdc, 10Vdc:±30%) Within ±25% of the initial value.(6.3Vdc, 10Vdc:±30%)</td> <td colspan="3">时间(hrs) Life Time</td> </tr> <tr> <td>6.3Vdc</td> <td>10~50Vdc</td> <td>63~100Vdc</td> </tr> <tr> <td rowspan="2">损失角正切值 Dissipation Factor</td> <td rowspan="2">规格值的200%以下 Not more than 200% of the specified value.</td> <td>$\phi D \leq 6.3$</td> <td>6000</td> <td>7000</td> <td>6000</td> </tr> <tr> <td>8×11.5</td> <td>8000</td> <td>9000</td> <td>8000</td> </tr> <tr> <td rowspan="2">漏电流 Leakage Current</td> <td rowspan="2">规格值以下 Not more than the specified value.</td> <td>10×12.5</td> <td>9000</td> <td>9000</td> <td>9000</td> </tr> <tr> <td>8×16.8×20</td> <td>9000</td> <td>10000</td> <td>9000</td> </tr> <tr> <td></td> <td></td> <td>10×16, 10×20, 10×25 $\phi D \geq 12.5$</td> <td colspan="3">10000</td> </tr> </table>		静电容量变化率 Capacitance Change	初期值的±25%以内 (6.3Vdc, 10Vdc:±30%) Within ±25% of the initial value.(6.3Vdc, 10Vdc:±30%)	时间(hrs) Life Time			6.3Vdc	10~50Vdc	63~100Vdc	损失角正切值 Dissipation Factor	规格值的200%以下 Not more than 200% of the specified value.	$\phi D \leq 6.3$	6000	7000	6000	8×11.5	8000	9000	8000	漏电流 Leakage Current	规格值以下 Not more than the specified value.	10×12.5	9000	9000	9000	8×16.8×20	9000	10000	9000			10×16, 10×20, 10×25 $\phi D \geq 12.5$	10000		
静电容量变化率 Capacitance Change	初期值的±25%以内 (6.3Vdc, 10Vdc:±30%) Within ±25% of the initial value.(6.3Vdc, 10Vdc:±30%)	时间(hrs) Life Time																																		
		6.3Vdc	10~50Vdc	63~100Vdc																																
损失角正切值 Dissipation Factor	规格值的200%以下 Not more than 200% of the specified value.	$\phi D \leq 6.3$	6000	7000	6000																															
		8×11.5	8000	9000	8000																															
漏电流 Leakage Current	规格值以下 Not more than the specified value.	10×12.5	9000	9000	9000																															
		8×16.8×20	9000	10000	9000																															
		10×16, 10×20, 10×25 $\phi D \geq 12.5$	10000																																	
低温特性 Low Temperature Stability (阻抗比) Impedance Ratio(MAX)	<table border="1"> <tr> <td>额定电压(Vdc) Rated Voltage</td> <td>6.3</td> <td>10</td> <td>16</td> <td>25</td> <td>35</td> <td>50</td> <td>63</td> <td>80</td> <td>100</td> <td>(120Hz)</td> </tr> <tr> <td>$Z(-25^\circ C)/Z(20^\circ C)$</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td></td> </tr> <tr> <td>$Z(-40^\circ C)/Z(20^\circ C)$</td> <td>3</td> <td>3</td> <td>3</td> <td>3</td> <td>3</td> <td>3</td> <td>3</td> <td>3</td> <td>3</td> <td></td> </tr> </table>		额定电压(Vdc) Rated Voltage	6.3	10	16	25	35	50	63	80	100	(120Hz)	$Z(-25^\circ C)/Z(20^\circ C)$	2	2	2	2	2	2	2	2	2		$Z(-40^\circ C)/Z(20^\circ C)$	3	3	3	3	3	3	3	3	3		
额定电压(Vdc) Rated Voltage	6.3	10	16	25	35	50	63	80	100	(120Hz)																										
$Z(-25^\circ C)/Z(20^\circ C)$	2	2	2	2	2	2	2	2	2																											
$Z(-40^\circ C)/Z(20^\circ C)$	3	3	3	3	3	3	3	3	3																											

纹波电流修正系数 / MULTIPLIER FOR RIPPLE CURRENT


频率(Hz) Frequency	120	1k	10k	100k≤
8.2~33 μF	0.42	0.70	0.90	1.00
47~270 μF	0.50	0.73	0.92	1.00
330~680 μF	0.55	0.77	0.94	1.00
820~1800 μF	0.60	0.80	0.96	1.00
2200~8200 μF	0.70	0.85	0.98	1.00

副记号 / OPTION

副记号 OPTION	记号 Code
PET套管 PET Sleeve	无 Blank

尺寸图 / DIMENSIONS

(mm)



产品型号体系 / PART NUMBER

□□□	ZLJ	□□□□□	M	□□□	□□	D×L
额定电压 Rated Voltage	系列名称 Series	静电容量 Capacitance	静电容量允许差 Capacitance Tolerance	副记号 Option	引线加工记号 Lead Forming	铝壳尺寸 Case Size



引线型铝电解电容器 RADIAL LEAD ALUMINUM ELECTROLYTIC CAPACITORS

ZLJ

◆标准品名单/STANDARD SIZE

额定电压 Rated Voltage (Vdc)	静电容量 Capacitance (μF)	外形尺寸 Size φDXL(mm)	额定纹波电流 Rated ripple current (mAr.m.s./105°C, 100kHz)	阻抗(Ω MAX) Impedance	
				20°C, 100kHz	-10°C, 100kHz
				6.3	220
	470	6.3X11	540	0.17	0.51
	820	8X11.5	945	0.075	0.23
	1000	8X16	1250	0.059	0.18
	1200	10X12.5	1330	0.053	0.16
	1500	8X20	1500	0.041	0.13
	1800	10X16	1760	0.038	0.12
	2700	10X20	1960	0.028	0.084
	3300	10X25	2250	0.024	0.072
	3900	12.5X20	2480	0.025	0.075
	4700	12.5X25	2900	0.019	0.057
	5600	12.5X30	3450	0.018	0.054
	6800	12.5X35	3570	0.016	0.048
	6800	16X20	3250	0.021	0.063
	8200	16X25	3630	0.017	0.051
	150	5X11	450	0.4	1.2
	330	6.3X11	700	0.17	0.51
	560	8X11.5	1200	0.075	0.23
	680	8X16	1600	0.059	0.18
	820	10X12.5	1700	0.053	0.16
	1000	8X20	1960	0.041	0.13
	1200	10X16	2000	0.038	0.12
	1800	10X20	2500	0.028	0.084
	2200	10X25	2900	0.024	0.072
	2700	12.5X20	2600	0.025	0.075
	3300	12.5X25	3200	0.019	0.057
	4700	12.5X30	3660	0.018	0.054
	4700	16X20	3330	0.021	0.063
	5600	12.5X35	4120	0.016	0.048
	5600	16X25	3810	0.017	0.051
	120	5X11	450	0.4	1.2
	270	6.3X11	700	0.17	0.51
	470	8X11.5	1200	0.075	0.23
	560	8X16	1600	0.059	0.18
	680	8X16	1600	0.059	0.18
	680	10X12.5	1700	0.053	0.16
	820	8X20	1960	0.041	0.13
	1000	8X20	1960	0.041	0.13
	1000	10X16	2000	0.038	0.12
	1500	10X20	2500	0.028	0.084
	1800	10X25	2900	0.024	0.072
	2200	12.5X20	2600	0.025	0.075
	2700	12.5X25	3200	0.019	0.057
	3300	12.5X30	3660	0.018	0.054
	3300	16X20	3330	0.021	0.063
	3900	12.5X35	4120	0.016	0.048
	4700	16X25	3810	0.017	0.051
	68	5X11	450	0.4	1.2
	150	6.3X11	700	0.17	0.51
	330	8X11.5	1200	0.075	0.23
	390	8X16	1600	0.059	0.18
	470	10X12.5	1700	0.053	0.16
	560	8X20	1960	0.041	0.13
	680	10X16	2000	0.038	0.12
	1000	10X20	2500	0.028	0.084
	1200	10X25	2900	0.024	0.072
	1500	12.5X20	2600	0.025	0.075
	1800	12.5X25	3200	0.019	0.057
	2200	12.5X30	3660	0.018	0.054
	2200	16X20	3330	0.021	0.063
	2700	12.5X35	4120	0.016	0.048
	3300	16X25	3810	0.017	0.051
	47	5X11	450	0.4	1.2
	100	6.3X11	700	0.17	0.51
	180	8X11.5	1200	0.075	0.23
	220	8X16	1600	0.059	0.18

额定电压 Rated Voltage (Vdc)	静电容量 Capacitance (μF)	外形尺寸 Size φDXL(mm)	额定纹波电流 Rated ripple current (mAr.m.s./105°C, 100kHz)	阻抗(Ω MAX) Impedance	
				20°C, 100kHz	-10°C, 100kHz
				35	270
	270	10X12.5	1700	0.053	0.16
	330	8X20	1960	0.041	0.13
	330	10X12.5	1700	0.053	0.16
	390	8X20	1960	0.041	0.13
	390	10X16	2000	0.038	0.12
	470	10X16	2000	0.038	0.12
	560	10X20	2500	0.028	0.084
	680	10X25	2900	0.024	0.072
	820	12.5X20	2600	0.025	0.075
	1000	12.5X25	2600	0.025	0.075
	1200	12.5X25	3200	0.019	0.057
	1500	12.5X30	3660	0.018	0.054
	1500	16X20	3330	0.021	0.063
	1800	12.5X35	4120	0.016	0.048
	1800	16X25	3810	0.017	0.051
	27	5X11	310	0.48	1.5
	56	6.3X11	500	0.22	0.66
	100	8X11.5	950	0.12	0.36
	120	8X11.5	1300	0.11	0.33
	120	8X16	1230	0.082	0.25
	150	10X12.5	1280	0.073	0.22
	180	8X16	1700	0.081	0.24
	180	8X20	1580	0.058	0.18
	220	10X12.5	1700	0.071	0.21
	220	10X16	1650	0.053	0.16
	270	8X20	2100	0.058	0.17
	330	10X16	2100	0.052	0.16
	330	10X20	2060	0.038	0.12
	390	10X25	2420	0.032	0.1
	470	10X20	2500	0.037	0.11
	470	12.5X16	2200	0.04	0.12
	470	12.5X20	2300	0.03	0.1
	560	10X25	2900	0.031	0.093
	680	12.5X20	2700	0.029	0.087
	680	12.5X25	2800	0.025	0.08
	820	12.5X30	3370	0.023	0.074
	820	16X20	3070	0.026	0.084
	1000	12.5X25	3000	0.022	0.066
	1000	12.5X30	3500	0.02	0.06
	1000	12.5X35	3810	0.021	0.067
	1000	16X25	3510	0.022	0.07
	1200	12.5X35	4000	0.017	0.051
	1200	16X20	3100	0.023	0.069
	1500	12.5X40	4500	0.019	0.057
	1500	16X25	3600	0.018	0.054
	1500	18X20	3200	0.029	0.087
	2200	16X31.5	4100	0.018	0.054
	2200	18X25	3700	0.022	0.066
	2700	16X35.5	4400	0.016	0.048
	2700	16X40	4800	0.014	0.042
	2700	18X31.5	4200	0.019	0.057
	3300	18X35.5	4600	0.016	0.048
	3900	18X40	5000	0.014	0.042
	18	5X11	240	0.71	3.2
	47	6.3X11	420	0.28	1.3
	82	8X11.5	720	0.18	0.79
	100	8X11.5	1000	0.13	0.39
	100	8X16	990	0.13	0.58
	120	8X16	1300	0.095	0.29
	120	10X12.5	990	0.11	0.44
	150	8X20	1200	0.096	0.43
	150	10X12.5	1300	0.08	0.24
	180	8X20	1600	0.069	0.21
	180	10X16	1200	0.076	0.31
	220	10X16	1700	0.058	0.17

*此技术数据如有更改，恕不另行通知。

*Specifications subject to change without notice.



引线型铝电解电容器 RADIAL LEAD ALUMINUM ELECTROLYTIC CAPACITORS

ZLJ

◆标准品名单/STANDARD SIZE

额定电压 Rated Voltage (Vdc)	静电容量 Capacitance (μF)	外形尺寸 Size φDXL(mm)	额定纹波电流 Rated ripple current (mAr.m.s./105°C, 100kHz)	阻抗(Ω MAX) Impedance	
				20°C, 100kHz	-10°C, 100kHz
				63	270
	270	12.5X16	1570	0.072	0.27
	330	10X20	2000	0.042	0.13
	330	10X25	1990	0.046	0.19
	330	12.5X16	1900	0.045	0.14
	390	10X25	2400	0.035	0.11
	390	12.5X20	1990	0.041	0.13
	470	12.5X20	2400	0.033	0.099
	470	12.5X25	2460	0.031	0.093
	560	12.5X30	2760	0.028	0.084
	560	16X20	2380	0.032	0.096
	680	12.5X25	2800	0.025	0.075
	680	12.5X35	3040	0.024	0.072
	820	12.5X30	3200	0.022	0.066
	820	16X20	2900	0.025	0.075
	820	16X25	2890	0.025	0.075
	1000	12.5X35	3500	0.018	0.054
	1000	16X25	3200	0.02	0.06
	1200	12.5X40	3800	0.021	0.063
	1200	18X20	3000	0.032	0.096
	1500	16X31.5	3500	0.02	0.06
	1500	18X25	3200	0.024	0.072
	1800	16X35.5	3800	0.017	0.051
	1800	18X31.5	3700	0.02	0.06
	2200	16X40	4100	0.015	0.045
	2200	18X35.5	3900	0.017	0.051
	2700	18X40	4300	0.015	0.045
	●12	5X11	235	0.72	3.2 NEW
	12	5X11	220	1.2	5.4
	●27	6.3X11	390	0.34	1.5 NEW
	27	6.3X11	370	0.46	2.1
	●47	8X11.5	650	0.2	0.9 NEW
	47	8X11.5	620	0.29	1.3
	56	8X16	780	0.2	0.9
	68	10X12.5	780	0.17	0.66
	82	8X16	820	0.14	0.63 NEW
	82	8X20	1040	0.16	0.66
	100	10X12.5	860	0.14	0.56 NEW
	100	10X16	1040	0.11	0.47
	120	8X20	1090	0.12	0.54 NEW
	150	10X16	1150	0.09	0.36 NEW
	150	10X20	1430	0.084	0.34
	150	12.5X16	1430	0.11	0.34
	180	10X25	1620	0.069	0.28
	220	10X20	1570	0.068	0.28 NEW
	220	12.5X16	1430	0.09	0.27 NEW
	220	12.5X20	1750	0.062	0.18
	270	10X25	1780	0.055	0.22 NEW
	270	12.5X25	2210	0.047	0.14
	330	12.5X20	1800	0.048	0.15 NEW
	330	12.5X30	2400	0.042	0.13
	330	16X20	1950	0.048	0.15
	390	12.5X25	2210	0.038	0.12 NEW
	390	12.5X35	2600	0.036	0.11
	470	12.5X30	2520	0.033	0.11 NEW
	470	12.5X40	2860	0.032	0.095
	470	16X20	2150	0.036	0.12 NEW
	470	16X25	2430	0.038	0.12
	470	18X20	2270	0.045	0.14
	560	12.5X35	2860	0.026	0.078 NEW
	560	16X31.5	2640	0.032	0.095
	680	12.5X40	3150	0.026	0.078 NEW
	680	16X25	2620	0.028	0.084 NEW
	680	18X20	2280	0.032	0.096 NEW
	680	16X35.5	2860	0.029	0.086
	680	18X25	2750	0.027	0.081 NEW
	680	18X31.5	3150	0.02	0.06 NEW
	680	18X35.5	3510	0.027	0.081
	820	16X40	3710	0.018	0.054 NEW
	820	18X35.5	3710	0.018	0.054 NEW
	820	18X40	3860	0.026	0.076
	1000	18X40	4060	0.017	0.051 NEW

额定电压 Rated Voltage (Vdc)	静电容量 Capacitance (μF)	外形尺寸 Size φDXL(mm)	额定纹波电流 Rated ripple current (mAr.m.s./105°C, 100kHz)	阻抗(Ω MAX) Impedance	
				20°C, 100kHz	-10°C, 100kHz
				80	820
	820	16X40	3510	0.027	0.081
	820	18X31.5	2860	0.03	0.09
	1000	16X35.5	3150	0.02	0.06 NEW
	1000	18X25	2750	0.027	0.081 NEW
	1000	18X35.5	3510	0.027	0.081
	1200	16X40	3710	0.018	0.054 NEW
	1200	18X31.5	3150	0.02	0.06 NEW
	1200	18X40	3860	0.026	0.076
	1500	18X35.5	3710	0.018	0.054 NEW
	1800	18X40	4060	0.017	0.051 NEW
	●8.2	5X11	235	0.72	3.2 NEW
	8.2	5X11	220	1.2	5.4
	●18	6.3X11	390	0.34	1.5 NEW
	18	6.3X11	370	0.46	2.1
	●33	8X11.5	650	0.2	0.9 NEW
	33	8X11.5	620	0.29	1.3
	●47	8X16	820	0.14	0.63 NEW
	47	8X16	780	0.2	0.9
	●56	10X12.5	860	0.14	0.56 NEW
	56	10X12.5	780	0.17	0.66
	●68	8X20	1090	0.12	0.54 NEW
	68	8X20	1040	0.16	0.66
	●82	10X16	1150	0.09	0.36 NEW
	82	10X16	1040	0.11	0.47
	100	10X20	1430	0.084	0.34
	100	12.5X16	1430	0.11	0.34
	120	10X20	1570	0.068	0.28 NEW
	120	10X25	1620	0.069	0.28
	120	12.5X16	1430	0.09	0.27 NEW
	150	10X25	1780	0.055	0.22 NEW
	150	12.5X20	1750	0.062	0.18
	180	12.5X20	1800	0.048	0.15 NEW
	●220	12.5X25	2210	0.038	0.12 NEW
	220	12.5X25	2210	0.047	0.14
	●270	12.5X30	2520	0.033	0.11 NEW
	270	12.5X30	2400	0.042	0.13
	270	16X20	1950	0.048	0.15
	330	12.5X35	2600	0.036	0.11
	330	16X20	2150	0.036	0.12 NEW
	390	12.5X35	2860	0.026	0.078 NEW
	390	12.5X40	2860	0.032	0.095
	●390	16X25	2620	0.028	0.084 NEW
	390	16X25	2430	0.038	0.12
	●390	18X20	2280	0.032	0.096 NEW
	390	18X20	2270	0.045	0.14
	470	12.5X40	3150	0.026	0.078 NEW
	470	16X31.5	2640	0.032	0.095
	470	18X25	2500	0.036	0.11
	560	16X31.5	2900	0.022	0.066 NEW
	560	16X35.5	2860	0.029	0.086
	560	18X25	2750	0.027	0.081 NEW
	560	18X31.5	2860	0.03	0.09
	680	16X35.5	3150	0.02	0.06 NEW
	680	16X40	3510	0.027	0.081
	680	18X31.5	3150	0.02	0.06 NEW
	680	18X35.5	3510	0.027	0.081
	820	16X40	3710	0.018	0.054 NEW
	820	18X35.5	3710	0.018	0.054 NEW
	820	18X40	3860	0.026	0.076
	1000	18X40	4060	0.017	0.051 NEW

● : OPTION has EFU.

*此技术数据如有更改，恕不另行通知。

*Specifications subject to change without notice.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Aluminium Electrolytic Capacitors - Radial Leaded](#) category:

Click to view products by [Rubycon](#) manufacturer:

Other Similar products are found below :

[NRELS102M35V16X16C.140LLF](#) [ESRG160ETC100MD07D](#) [227RZS050M](#) [335CKR250M](#) [476CKH100MSA](#) [477CKR100M](#)
[107CKR010M](#) [107CKH063MSA](#) [RJH-25V222MI9#](#) [RJH-35V221MG5#](#) [B43827A1106M8](#) [RJH-50V221MH6#](#) [EKYA500ELL470MF11D](#)
[B41022A5686M6](#) [ESRG250ELL101MH09D](#) [EKMA160EC3101MF07D](#) [RJB-10V471MG3#](#) [ESMG160ETD221MF11D](#)
[EKZH160ETD152MJ20S](#) [RJH-35V122MJ6#](#) [EGXF630ELL621ML20S](#) [RBD-25V100KE3#N](#) [EKMA350ELL100ME07D](#)
[ESMG160ETD101ME11D](#) [ELXY100ETD102MJ20S](#) [EGXF500ELL561ML15S](#) [EKMG350ETD471MJ16S](#) [35YXA330MEFC10X12.5](#)
[RXW471M1ESA-0815](#) [ELXZ630ELL221MJ25S](#) [ERR1HM1R0D11OT](#) [LPE681M30060FVA](#) [LPL471M22030FVA](#) [HFE221M25030FVA](#)
[LKMD1401H221MF](#) [B41888G6108M000](#) [EKMA160ETD470MF07D](#) [UHW1J102MHD6](#) [EKMG500ETD221MJC5S](#) [LKMK2502W101MF](#)
[LKMD1401H181MF](#) [LKMI2502G820MF](#) [LKMJ2001J122MF](#) [LKML2501C472MF](#) [LKMJ4002C681MF](#) [450MXH330MEFCSN25X45](#)
[450MXK330MA2RFC22X50](#) [63ZLH560MEFCG412.5X30](#) [ELH2DM331O25KT](#) [ELH2DM471P30KT](#)