CHIP ALUMINUM ELECTROLYTIC CAPACITORS



THV SERIES

Load Life: 125°C 2000~3000 hours Low ESR

•AEC-Q200.






◆SPECIFICATIONS


Items	Characteristics					
Category Temperature Range	-40~+125℃					
Rated Voltage Range	16~50Vdc					
Capacitance Tolerance	±20%(20℃,120Hz)					
Leakage Current(MAX)	I=0.01CV or 3μ A whichever is greater. (After 2 minutes application of rated voltage) I=Leakage Current(μ A) C=Capacitance(μ F) V=Rated Voltage(Vdc)					
Dissipation Factor(MAX) (tanδ)	Rated Voltage (Vdc) 16 25 35 50 (20°C,120Hz) tanδ 0.23 0.18 0.16 0.14					
	After applying rated voltage with rated ripple current for specified time at 125°C, the capacitors shall meet the following requirements.					
Endurance	Capacitance Change Within ±30% of the initial value. Case Size LifeTime (hrs)					
Dissipation Factor Not more than 300% of the specified value. ϕ D=6.3						
	Leakage Current Not more than the specified value. φD≥8 3000					
Low Temperature Stability Impedance Ratio(MAX)	Rated Voltage (Vdc) 16 25 35 50 (120Hz) (120Hz) (120Hz)					

♦DIMENSIONS

(mm)



◆MARKING



◆MULTIPLIER FOR RIPPLE CURRENT

Frequency (Hz)		120	1k	10k	100k≦
	10~33μF	0.45	0.75	0.90	1.00
	47~100μF	0.50	0.80	0.95	1.00
	220~330μF	0.60	0.85	0.95	1.00

◆STANDARD SIZE Size φD×L(mm), Rated Ripple Current (mA r.m.s./125°C, 100kHz), ESR(Ω MAX/100kHz)

Vdc	Cap (μF)	Size (φDxL)	Ripple	ESR	
				20℃	-40°C
16	33	6.3×6.1	70	1	15
	47	6.3×8	200	0.7	10
	100	6.3×8	200	0.7	10
		8×10.5	300	0.3	4.5
	220	8×10.5	300	0.3	4.5
		10×10.5	500	0.2	3
	330	10×10.5	500	0.2	3

Vdc	Cap (μF)	Size (φDxL)	Ripple	ESR	
				20℃	-40°C
25	33	6.3×6.1	70	1	15
	47	6.3×8	200	0.7	10
	100	8×10.5	300	0.3	4.5
	220	8×10.5	300	0.3	4.5
		10×10.5	500	0.2	3
	330	10×10.5	500	0.2	3

◆PART NUMBER

	THV		M		D×L
Rated Voltage	Series	Capacitance	Capacitance Tolerance	Option	Case Size

Vdc	Cap	Size	Ripple	ESR	
Vuc	(μF)	(φDxL)	nippie	20°C	-40°C
	22	6.3×8	200	0.7	10
	33	6.3×6.1	70	1	15
		6.3×8	200	0.7	10
35	47	6.3×8	200	0.7	10
33		8×10.5	300	0.3	4.5
	100	8×10.5	300	0.3	4.5
		10×10.5	500	0.2	3
	220	10×10.5	500	0.2	3
	10	6.3×6.1	70	1	15
50	22	6.3×8	150	0.9	10
		6.3×8	150	0.9	10
	33	8×10.5	250	0.36	-40°C 10 15 10 4.5 4.5 3 3 15
	47	8×10.5	250	0.36	4.5
	47	10×10.5	350	0.25	3
	100	10×10.5	350	0.25	3

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Aluminium Electrolytic Capacitors - SMD category:

Click to view products by Rubycon manufacturer:

Other Similar products are found below:

GA0402A270FXBAC31G RVB-50V330MG10UQ-R RVJ-50V101MH10U-R RVZ-35V151MH10U-R2 RC0J226M04005VR

RC0J476M05005VR RC1A227M08010VR RC1C226M05005VR RC1C476M6L005VR RC1E107M6L07KVR RC1E336M6L005VR

RC1H106M6L005VR RC1H475M05005VR RC1V227M10010VR RC1V476M6L006VR 50SEV1M4X5.5 TYEH1A336E55MTR

TYEH1H106F55MTR TYEH1V106E55MTR 35SEV47M6.3X8 35SGV220M10X10.5 VES2R2M1HTR-0405 VZH102M1ATR-1010

50SEV10M6.3X5.5 50SGV1M4X6.1 SC1C476M05005VR SC1E107M0806BVR SC1E227M08010VR SC1H106M05005VR

SC1H106M6L005VR SC1H227M10010VR SC1H335M04005VR CE4.7/50-SMD VEJ4R7M1VTR-0406 VZH331M1ETR-0810

VES101M1CTR-0605 TYEH1H475E55MTR 6.3SEV22M4X5.5 6.3SEV47M4X5.5 EEEFK1H151GP EEEFK1A681GP EEE0GA471XP

EEEFK1V151GP RC1V107M6L07KVR VZH101M1VTR-0810 VE010M1HTR-0405 GYA1V151MCQ1GS EEH-ZC1J680P EEH
ZK1V181P GYA1V271MCQ1GS