


ACCLIMATE



16 mm IP68 FIELD TERMINATION KIT

SPECIFICATIONS

For complete specifications and processing guidelines see www.samtec.com?ACPK-16

Insulator Material: Thermoplastic Terminal Material:

Brass
Contact Material:
Brass/BeCu


Operating Temp Range: -10 °C to +105 °C Housing:

Housing:
-P: Thermoplastic
-M: Zinc Alloy
RoHS Compliant:

Mates with: ACR-16, ACRK-16

LEAD PINS CCC per PIN -01	CURRENT RATING		
-02 10 2.6 A			CCC per PIN
2	-01	14	1.3 A
2 (plus 8 signal pins 11.6 A	-02	10	2.6 A
powered & 1 A)	-06	2 (plus 8 signal pins powered @ 1 A)	11.6 A

For general reference only. See www.samtec.com?ACPK-16 for complete test data or contact AccliMate@samtec.com for applications requiring higher current carrying capacity.



DUST CAPS


- DCA-ACP-16-M-X (Metal)
- DCA-ACP-16-P-X (Plastic)



 Visit sealedio.samtec.com for a complete list of sealed systems

NOTE

For complete specifications and processing guidelines see www.samtec.com?ACPK-16



Note

Some lengths, styles and options are non-standard, non-returnable.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Standard Circular Connector category:

Click to view products by Samtec manufacturer:

Other Similar products are found below:

5M2530B10P 600259N006 600273N007 6134-336-13149 6134-337-11149 6134-337-2390 6134-341-17149 6280-4SG-516 6280-7SG-3DC 6290 6291A 66200A-10 680-SMG 681-PMG CXS3102A14S2P CXS3102A181S 7251-5SG-300 7271-6SG-300 7282-3PG-300-CH3 75-474618-01S 75-474618-04P 75-474618-04S 799539-000 MI8-SE 805-005-07NF11-19PC 805-005-07NF15-7PA 8280-4PG-516 8280-7PG-519 8282-5PG-519 836783-1 MP-4102-25P-C 862256-1 864019-2 866857-1 867865-1 PT01SP-14-18P PT08P-14-5S PTSF06SE-14-12S 120-1833-000 QCM019PC2DC012B 1-2069279-1 121583-0217 121667-0020 129591AU 1000B BULK RD10A16-19-P6CS051/1 RD10A20-31-P8CS051/1 RD16A14-12-S6CS051/2 1301240290 1301240347 1301860202