



BTE-040-02-L-D-A



BTE-060-02-F-D-A

BSE-020-01-F-D-A



**BTE, BSE SERIES**

**(0.80 mm) .0315"**

# BASIC BLADE & BEAM HEADER & SOCKET

## SPECIFICATIONS

For complete specifications and recommended PCB layouts see [www.samtec.com?BTE](http://www.samtec.com?BTE) or [www.samtec.com?BSE](http://www.samtec.com?BSE)

- Insulator Material:** Liquid Crystal Polymer
- Contact Material:** Phosphor Bronze
- Plating:** Au or Sn over 50 μ" (1.27 μm) Ni
- Current Rating:** 2 A per pin (2 pins powered)
- Operating Temp Range:** -55 °C to +125 °C
- Voltage Rating:** 225 VAC with 5 mm Stack Height
- Max Cycles:** 100
- RoHS Compliant:** Yes

## PROCESSING

- Lead-Free Solderable:** Yes
- SMT Lead Coplanarity:** (0.10 mm) .004" max (020-080) (0.15 mm) .006" max (100-120)\* (.004" stencil solution may be available; contact [IPG@samtec.com](mailto:IPG@samtec.com))
- Board Stacking:** For applications requiring more than two connectors per board or 80 positions or higher, contact [ipg@samtec.com](mailto:ipg@samtec.com)

## RECOGNITIONS

For complete scope of recognitions see [www.samtec.com/quality](http://www.samtec.com/quality)



## ALSO AVAILABLE (MOQ Required)

- 30 μ" (0.76 μm) Gold
- Edge Mount Capability
- Friction Lock option
- 11 mm, 14 mm, 16.10 mm, 19.10 mm, 22 mm, 25 mm and 30 mm Stack Height (Caution: Some automatic placement/inspection machines may have component height restrictions. Please consult machinery specifications.)

**Note:** Some lengths, styles and options are non-standard, non-returnable.

**BTE** — **NO. OF POSITIONS PER ROW** — **LEAD STYLE** — **PLATING OPTION** — **D** — **A** — **OTHER OPTION**

Mates with: **BSE**

**-020, -040, -060, -080, -100, -120**

Specify LEAD STYLE from chart

LEAD STYLE	A
-01	(4.27) .168
-02	(7.21) .284

**-F** = Gold Flash on contact, Matte Tin on tail

**-L** = 10 μ" (0.25 μm) Gold on contact, Matte Tin on tail

**-C\*** = Electro-Polished Selective 50 μ" (1.27 μm) min Au over 150 μ" (3.81 μm) Ni on Signal Pins in contact area, Matte Tin over 50 μ" (1.27 μm) min Ni on all solder tails

**-K** = (7.00 mm) .275" DIA Polyimide Film Pick & Place Pad

**-TR** = Tape & Reel (80 positions maximum)

**-FR** = Full Reel Tape & Reel (must order maximum quantity per reel; contact Samtec for quantity breaks) (80 positions maximum)

\*Note: -C Plating passes 10 year MFG testing

LEAD STYLE	MATED HEIGHT*
-01	(5.00) .197
-02	(8.00) .315

\*Processing conditions will affect mated height.

**BSE** — **NO. OF POSITIONS PER ROW** — **01** — **PLATING OPTION** — **D** — **A** — **OTHER OPTION**

Mates with: **BTE**

**-020, -040, -060, -080, -100, -120**

**-F** = Gold Flash on contact, Matte Tin on tail

**-L** = 10 μ" (0.25 μm) Gold on contact, Matte Tin on tail

**-C\*** = Electro-Polished Selective 50 μ" (1.27 μm) min Au over 150 μ" (3.81 μm) Ni on Signal Pins in contact area, Matte Tin over 50 μ" (1.27 μm) min Ni on all solder tails

**-TR** = Tape & Reel (80 positions maximum)

**-FR** = Full Reel Tape & Reel (must order maximum quantity per reel; contact Samtec for quantity breaks) (80 positions maximum)

\*Note: -C Plating passes 10 year MFG testing

Due to technical progress, all designs, specifications and components are subject to change without notice.

[WWW.SAMTEC.COM](http://WWW.SAMTEC.COM)

All parts within this catalog are built to Samtec's specifications. Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Board to Board & Mezzanine Connectors](#) category:*

*Click to view products by [Samtec](#) manufacturer:*

Other Similar products are found below :

[10135583-642402LF](#) [89885-310LF](#) [589158040000018](#) [6-1393048-0](#) [68683-613](#) [MDF7-12DP-2.54DSA](#) [MDF7-18P-2.54DSA\(01\)](#) [MDF7-20DP-2.54DSA](#) [MDF7-26D-2.54DSA\(55\)](#) [MDF7-3P-2.54DSA\(01\)](#) [MDF7B-3P-2.54DSA\(55\)](#) [MDF7C-11P-2.54DSA\(55\)](#) [MDF7C-18P-2.54DSA\(55\)](#) [MDF7C-5P-2.54DSA\(01\)](#) [MDF7P-5P-2.54DSA\(55\)](#) [75234-0516](#) [FCN-230C068-11](#) [FCN-268F012-G/BD](#) [FCN-268F036-G/BD](#) [FCN-268M012-G/0D](#) [FCN-268M024-G/1D](#) [FCN-360C008-C](#) [FCN-360C040-C](#) [FCN-723J004/1](#) [MIS-048-01-F-D-DP-K](#) [832-10-034-10-001000](#) [93696-325LF](#) [11828-1FA](#) [AXK630345P](#) [18097-0013](#) [ICA-328STT](#) [2007042-2](#) [304400-2](#) [FCN-214Q030-G/0](#) [FCN-215Q040-G/0](#) [FCN-230C068-ESA](#) [FCN-234P048-G/0](#) [FCN-235D050-G/C](#) [FCN-360A3](#) [FCN-360C040-B](#) [210-93-314-41-105000](#) [2-22603-0](#) [379-064-521-202](#) [MDF7-12P-2.54DSA\(01\)](#) [MDF7-16P-2.54DS\(56\)](#) [MDF7-40DP-2.54DSA\(55\)](#) [MDF7-8P-2.54DSA\(55\)](#) [MDF7B-16P-2.54DSA\(55\)](#) [AXG720047](#) [5031084030](#)