



(2.54 mm) .100"

BSW SERIES

BOTTOM MOUNT SOCKET STRIPS

Mates with:

TSW, MTSW, HTSW,
MTLW, TSM, EW, ZW,
HW, DW, PHT

FEATURES

- Bottom mount socket strips accept .025" SQ terminals.
- Ideal for soldering and plugging from the same side of the board.
- For low-profile connections and high temperature soldering.

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?BSW

Insulator Material:
Black Thermoplastic
Insulation Resistance:
5000 MΩ min
Contact Material:
Phosphor Bronze
Plating:
Au or Sn over
50 μ" (1.27 μm) Ni
Operating Temp Range:
-55 °C to +125 °C with Gold
-55 °C to +105 °C with Tin
Withstanding Voltage:
1000 VRMS @ 60 Hz
Insertion Depth:
(3.68 mm) .145" to
(6.35 mm) .250"
RoHS Compliant:
Yes
Lead-Free Solderable:
Wave only

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality



ALSO AVAILABLE (MOQ Required)

- Other platings

Note:
Some lengths, styles and options are non-standard, non-returnable.

BSW	1	NO. PINS PER ROW	LEAD STYLE	PLATING OPTION	ROW OPTION	OTHER OPTION								
<p>02 thru 36</p>			<p>-04 = Standard Lead</p> <p>-24 = Low Insertion Force</p>	<p>-L = 10 μ" (0.25 μm) Gold contact, Matte Tin on tail</p> <p>-G = 20 μ" (0.51 μm) Gold contact, Gold Flash on tail</p> <p>-T = Matte Tin (N/A with Low Insertion Force)</p>	<p>-S = Standoffs for single and double rows only.</p>									
<table border="1"> <thead> <tr> <th>Row Option</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td>-S*</td> <td>(4.31) .170</td> </tr> <tr> <td>-M</td> <td>(3.43) .135</td> </tr> <tr> <td>-D*</td> <td>(4.32) .170</td> </tr> </tbody> </table> <p>*Less (0.38 mm) .015" with standoffs</p>			Row Option	Z	-S*	(4.31) .170	-M	(3.43) .135	-D*	(4.32) .170				
Row Option	Z													
-S*	(4.31) .170													
-M	(3.43) .135													
-D*	(4.32) .170													

Row Option	X	Y
-S	(2.54) .100	(5.08) .200
-M	(3.81) .150	(6.35) .250

Body design may vary slightly from drawing shown.

-S
= Single Row

-M
= Single Row
More Plug Space

-D
= Double Row

APPLICATIONS

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

All parts within this catalog are built to Samtec's specifications.
Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Board to Board & Mezzanine Connectors](#) category:

Click to view products by [Samtec](#) manufacturer:

Other Similar products are found below :

[10135583-642402LF](#) [89885-310LF](#) [589158040000018](#) [6-1393048-0](#) [68683-613](#) [MDF7-12DP-2.54DSA](#) [MDF7-18P-2.54DSA\(01\)](#) [MDF7-20DP-2.54DSA](#) [MDF7-26D-2.54DSA\(55\)](#) [MDF7-3P-2.54DSA\(01\)](#) [MDF7B-3P-2.54DSA\(55\)](#) [MDF7C-11P-2.54DSA\(55\)](#) [MDF7C-18P-2.54DSA\(55\)](#) [MDF7C-5P-2.54DSA\(01\)](#) [MDF7P-5P-2.54DSA\(55\)](#) [75234-0516](#) [FCN-230C068-11](#) [FCN-268F012-G/BD](#) [FCN-268F036-G/BD](#) [FCN-268M012-G/0D](#) [FCN-268M024-G/1D](#) [FCN-360C008-C](#) [FCN-360C040-C](#) [FCN-723J004/1](#) [MIS-048-01-F-D-DP-K](#) [832-10-034-10-001000](#) [93696-325LF](#) [11828-1FA](#) [AXK630345P](#) [18097-0013](#) [ICA-328STT](#) [2007042-2](#) [304400-2](#) [FCN-214Q030-G/0](#) [FCN-215Q040-G/0](#) [FCN-230C068-ESA](#) [FCN-234P048-G/0](#) [FCN-235D050-G/C](#) [FCN-360A3](#) [FCN-360C040-B](#) [210-93-314-41-105000](#) [2-22603-0](#) [379-064-521-202](#) [MDF7-12P-2.54DSA\(01\)](#) [MDF7-16P-2.54DS\(56\)](#) [MDF7-40DP-2.54DSA\(55\)](#) [MDF7-8P-2.54DSA\(55\)](#) [MDF7B-16P-2.54DSA\(55\)](#) [AXG720047](#) [5031084030](#)