


OPTICAL MICRO FLYOVER SYSTEM[™]



FEATURES

- Supports data center and HPC protocols, including: Ethernet, InfiniBand[™], Fibre Channel
- Customizable optical connectors
- Integrated coupling capacitors
- Standard temperature range 0 °C to +70 °C
- Evaluation & Development boards available




TOOLING


Insertion Tool: CAT-IN-ECUO-02

Notes: MTP[®] is a registered trademark of US Conec Ltd.

All FireFly[™] designs, specifications and components are preliminary and subject to change without notice.

Some lengths, styles and options are non-standard, non-returnable.





-1 FLAT HEAT SINK

*	→	.386	_
(8.00) .315	สร		

1 (0 80) 1

1111-

-3 FLAT WITH GROOVE HEAT SINK (MULTI-ROW CONFIGURATION)

View complete specifications at: samtec.com?ECUO

÷

samtec.com/FireFly

Unless otherwise approved in writing by Samtec, all parts and components are designed and built according to Samtec's specifications which are subject to change without notice.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Fibre Optic Cable Assemblies category:

Click to view products by Samtec manufacturer:

Other Similar products are found below :

 7-21002-9
 760-1518
 FA04390-50-M-72-LC-N
 MLB 501 V RED
 MLB 501 V YELLOW
 1-3636-600-5208
 2061529-7
 1-6693182-0

 1754898-1
 21055-6
 FXBSCSCE2LM002
 3000005
 3-21053-2
 MLB 200/1 V BLACK
 MLB 2001 V RED
 MLB 2001 V YELLOW
 MLB 501

 V BLACK
 5492011-6
 106284-7000
 5492011-5
 5492011-9
 8-21007-5
 2123524-2
 2123524-1
 106386-4447
 DFSM-SCSC-2M

 2123909-4
 2123909-8
 106273-0629
 2125046-1
 2821236-3
 2821310-2
 2821310-3
 2821313-4
 FX2ERLNLNSNM0.5
 CF-980062-074
 CF

 901200-394
 CF-980062-073
 CF-980062-071
 CF-980062-075
 CF-980062-072
 17-300310-100
 2821236-2
 2821313-1
 G-FC-FC-S-002.0-DX

 A-18-Y
 G-E2A-E2A-S-003.0-SX-A-18-Y
 956-322-502214
 FA04474
 1083665
 1083665