



(0.50 mm) .0197"

FJH SERIES

FLAT FLEXIBLE CABLE (FFC) JUMPER

SPECIFICATIONS

For complete specifications see www.samtec.com?FJH

- Conductor:** Tin Plated Copper
- Conductor Resistance:** 1000 Ω/km max
- Insulation Resistance:** 10 MΩ/km min (conductor-to-conductor)
- Dielectric Test:** 400 VAC during 1 minute (conductor-to-conductor)
- Temperature Rating:** -30 °C to +80 °C
- Voltage Rating:** 60 VAC
- RoHS Compliant:** Yes

Mates with:
ZF5S



ALSO AVAILABLE (MOQ Required)

- Other Lengths

FJH	NO. OF POSITIONS	STYLE	LENGTH	STRIP LENGTH																											
			Length in inches																												
	-10, -15, -20, -25, -30, -40, -43, -50	-D = Double End -R = Reversed End	-03.00 = (76.2 mm) 3.00" -06.00 = (152.4 mm) 6.00" -12.00 = (304.8 mm) 12.00" -24.00 = (609.6 mm) 24.00" (Standard Lengths)	-4 = (4.00 mm) .157"																											
<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p>-D Style</p> </div> <div style="text-align: center;"> <p>-R Style</p> </div> </div>																															
		<table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th style="background-color: #333; color: white;">NO. OF POSITIONS</th> <th style="background-color: #333; color: white;">A</th> <th style="background-color: #333; color: white;">B</th> </tr> </thead> <tbody> <tr><td style="background-color: #333; color: white;">-10</td><td>(5.50) .217</td><td>(4.50) .177</td></tr> <tr><td style="background-color: #333; color: white;">-15</td><td>(8.00) .315</td><td>(7.00) .276</td></tr> <tr><td style="background-color: #333; color: white;">-20</td><td>(10.50) .413</td><td>(9.50) .374</td></tr> <tr><td style="background-color: #333; color: white;">-25</td><td>(13.00) .512</td><td>(12.00) .472</td></tr> <tr><td style="background-color: #333; color: white;">-30</td><td>(15.50) .610</td><td>(14.50) .571</td></tr> <tr><td style="background-color: #333; color: white;">-40</td><td>(20.50) .807</td><td>(19.50) .768</td></tr> <tr><td style="background-color: #333; color: white;">-43</td><td>(22.00) .866</td><td>(21.00) .827</td></tr> <tr><td style="background-color: #333; color: white;">-50</td><td>(25.50) 1.00</td><td>(24.50) 965</td></tr> </tbody> </table>			NO. OF POSITIONS	A	B	-10	(5.50) .217	(4.50) .177	-15	(8.00) .315	(7.00) .276	-20	(10.50) .413	(9.50) .374	-25	(13.00) .512	(12.00) .472	-30	(15.50) .610	(14.50) .571	-40	(20.50) .807	(19.50) .768	-43	(22.00) .866	(21.00) .827	-50	(25.50) 1.00	(24.50) 965
NO. OF POSITIONS	A	B																													
-10	(5.50) .217	(4.50) .177																													
-15	(8.00) .315	(7.00) .276																													
-20	(10.50) .413	(9.50) .374																													
-25	(13.00) .512	(12.00) .472																													
-30	(15.50) .610	(14.50) .571																													
-40	(20.50) .807	(19.50) .768																													
-43	(22.00) .866	(21.00) .827																													
-50	(25.50) 1.00	(24.50) 965																													

Notes:
Stiffener color will be blue or black at Samtec's discretion. Some sizes, styles and options are non-standard, non-returnable.

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

All parts within this catalog are built to Samtec's specifications. Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [FFC / FPC Jumper Cables](#) category:

Click to view products by [Samtec](#) manufacturer:

Other Similar products are found below :

[6-1437161-1](#) [MDM96521-744](#) [8-1474659-7](#) [FSK-21.5A-20](#) [FSK-72.5KD-17](#) [FSN-21A-18](#) [FSN-21A-2](#) [FSN-23A-3](#) [FSN-24A-2](#) [FSP-23A-14](#)
[FSP-25A-8-TB](#) [FST-24A-5](#) [9-1474653-6](#) [1474494-5](#) [1474659-1](#) [1474448-1](#) [1474494-2](#) [1557385-1](#) [2-1437168-4](#) [22034.1](#) [237-0736-003](#) [2-](#)
[6447164-4](#) [1-6437133-3](#) [1-6437159-8](#) [1832785-1](#) [FSN-23A-5](#) [FSN-26A-3](#) [FSN-28A](#) [FSN-61.1AB-30](#) [FSP-23A-11](#) [2-1437181-9](#) [2-](#)
[1437186-7](#) [238-9503-000](#) [2-6474621-5](#) [3-1437186-4](#) [3-1474654-1](#) [4-1437180-6](#) [4-1474659-8](#) [3-1437144-3](#) [3-1474654-4](#) [357-9509-000](#) [5-](#)
[1474653-2](#) [5-1474654-9](#) [1-1437173-3](#) [1-1474671-7](#) [1-1474612-2](#) [6474462-1](#) [6-6437158-0](#) [5-1474653-4](#) [D130361-5](#)