

(1.27 mm) .050"

FTS SERIES

# MICRO LOW-PROFILE TERMINAL STRIPS

## SPECIFICATIONS

For complete specifications and recommended PCB layouts see [www.samtec.com?FTS](http://www.samtec.com?FTS)

### HI-TEMP

**Insulator Material:** Black Liquid Crystal Polymer  
**Terminal Material:** Phosphor Bronze  
**Operating Temp Range:** -55 °C to +125 °C  
**Plating:** Sn or Au over 50 μ" (1.27 μm) Ni  
**Current Rating:** 3.4 A per pin (2 pins powered)  
**RoHS Compliant:** Yes  
**Lead-Free Solderable:** Yes  
**SMT Lead Coplanarity:** .004" (0.10 mm) max

## RECOGNITIONS

For complete scope of recognitions see [www.samtec.com/quality](http://www.samtec.com/quality)




## ALSO AVAILABLE (MOQ Required)

- Alignment pin

**Board Mates:** CLP, FLE

**Cable Mates:** FFSD

## OPTIONS



Mates with socket strips or IDC cable

Surface mount or through-hole

Micro pitch .050" x .050" (1.27 mm x 1.27 mm)

Low-profile (1.27 mm) .050"

Shrouded and alignment pin options available

Impedance matched for high-speed applications

FTS	1	NO. PINS PER ROW	LEAD STYLE	PLATING OPTION	ROW OPTION	OTHER OPTION										
		02 thru 50 (except -S & -SA option = 05 thru 46)	<p><b>-01</b> = .120" (3.05 mm) Post (Mates with FFSD)</p> <p><b>-02</b> = .075" (1.91 mm) Post (Mates with FLE)</p> <p><b>-03</b> = .065" (1.65 mm) Post (Mates with CLP)</p> <p><b>-04</b> = .150" (3.81 mm) Post</p>	<p><b>-F</b> = Gold flash on post, Matte Tin on tail</p> <p><b>-L</b> = 10 μ" (0.25 μm) Gold on post, Matte Tin on tail</p>	<p><b>-D</b> = Double Through-hole</p> <p><b>-DV</b> = Double Vertical SMT</p> <p><b>-S</b> = Single Through-hole</p> <p><b>-SV</b> = Single Vertical SMT</p>	<p>(-D &amp; -DV only)</p> <p><b>-SA</b> = End Shroud with Alignment Pin (05 thru 46 positions. Style -02 &amp; -03 only)</p> <p><b>-S</b> = End Shroud (05 thru 46 positions. Style -02 &amp; -03 only)</p> <p><b>-P</b> = Pick &amp; Place Pad (04 positions minimum)</p> <p><b>-TR</b> = Tape &amp; Reel (-DV only) (Required callout for positions 2 thru 4)</p>										
			<table border="1"> <thead> <tr> <th>LEAD STYLE</th> <th>A</th> </tr> </thead> <tbody> <tr> <td>-01</td> <td>(3.05) .120</td> </tr> <tr> <td>-02</td> <td>(1.91) .075</td> </tr> <tr> <td>-03</td> <td>(1.65) .065</td> </tr> <tr> <td>-04</td> <td>(3.81) .150</td> </tr> </tbody> </table>				LEAD STYLE	A	-01	(3.05) .120	-02	(1.91) .075	-03	(1.65) .065	-04	(3.81) .150
LEAD STYLE	A															
-01	(3.05) .120															
-02	(1.91) .075															
-03	(1.65) .065															
-04	(3.81) .150															

**Note:** Some lengths, styles and options are non-standard, non-returnable.

Due to technical progress, all designs, specifications and components are subject to change without notice.

[WWW.SAMTEC.COM](http://WWW.SAMTEC.COM)

All parts within this catalog are built to Samtec's specifications. Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Samtec manufacturer](#):*

Other Similar products are found below :

[ESQT-135-03-F-D-380](#) [QTE-060-01-L-D-A](#) [MSAS-179-ZUGG-18](#) [MTSW-103-07-F-S-240](#) [BCS-116-L-S-TE](#) [ERF8-020-05.0-S-DV-K-TR](#)  
[ERF8-060-05.0-L-DV-K-TR](#) [IDMD-10-T-12.00-A-G-R](#) [SFML-115-01-S-D](#) [SFML-125-01-S-D](#) [LSHM-120-02.5-L-DV-A-N-K-TR](#) [ESQ-110-14-G-D](#) [ESQT-125-03-F-D-310](#) [SO-0515-01-01-02](#) [FJH-50-D-12.00-4](#) [CES-150-01-T-D](#) [QTE-040-04-L-D-A](#) [QTH-020-04-F-D-DP-A-K-TR](#)  
[QTH-060-01-F-D-A](#) [QTH-090-04-L-D-A](#) [TCSD-10-S-05.00-01-F-N](#) [TCSD-15-D-02.00-01-N](#) [TFM-115-02-L-DH](#) [TFM-120-12-S-D-LC](#)  
[TFML-140-02-S-D](#) [TLW-107-05-G-D](#) [BDL-136-T-E](#) [TSS-132-01-G-S](#) [TST-113-04-S-D-RA](#) [TSW-105-14-F-D](#) [MMS-110-01-H-DH](#) [HPF-03-02-T-S](#) [DW-25-11-L-D-450](#) [ERF8-020-01-L-D-RA-L-TR](#) [ERF8-040-05.0-L-DV-TR](#) [SL-120-T-10](#) [SLM-115-01-S-D](#) [CLP-132-02-G-D](#)  
[TFC-125-02-F-D-A-K](#) [TSW-202-07-T-S](#) [ISDF-25-D-M](#) [IPT1-105-01-S-D-RA](#) [IPL1-125-01-S-D-RA](#) [ICO-422-L-GT](#) [HTSW-116-15-L-S-LL](#)  
[HTSW-103-08-L-S-RA](#) [ESQ-116-33-T-T](#) [ERM8-020-02.0-S-DV-TR](#) [TCSD-10-D-06.00-01-N](#) [TCSD-20-D-12.00-01-N](#)