



HDMR-19-01-S-SM-PF



HDMR-19-02-S-SM



HDMR-29-01-S-SM

HDMR SERIES

HIGH-SPEED I/O RECEPTACLES

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?HDMR

- Insulator Material:**
High Temperature Thermoplastic
- Contact Material:**
Copper Alloy
- Shell Material:**
Nickel Plated Brass
- Operating Temp Range:**
-25 °C to +85 °C
- Plating:**
Gold on Contacts, Nickel on Shell and Tin on Tails
- Current Rating:**
1.3 A per pin
(6 adjacent pins powered)
- Voltage Rating:**
40 VAC
- Minimum Cycles:**
100
- Lead-Free Solderable:**
Yes
- RoHS Compliant:**
Yes

Meets Digital Display Working Group Single Monitor Interface Specifications

Hot Pluggable

Optional Panel Flange (19 position only)

Selectively Plated

19 or 29 Positions

Surface Mount or Through-hole Signal Leads

Through-hole or Surface Mount (19 only) Ground tails

HDMR	NO. OF POSITIONS	LEAD STYLE	PLATING	TAIL OPTION	OPTIONS	"X" R
	-19 = 19 Positions / Mates with HPXXX 5 Pairs -29 = 29 Positions / Mates with HPXXX 8 Pairs	-01 = Through-hole Ground Tails -02 = Surface Mount Ground Tails (-19 only)	-S = 30 μ" (0.76 μm) Gold on Mating Area, Tin on Tails	-SM = Surface Mount (Signal Leads) -TH = Through-hole (Only available on HDMR-19-01-X-TH-PF-L)	-PF = Panel Flange -L = Locking Option (Only available on HDMR-19-01-X-TH-PF-L & HDMR-29-01-X-TH-PF-L)	-TR = Tape & Reel -FR = Full Reel Tape & Reel (must order max. quantity per reel; contact Samtec for quantity breaks)

NO. OF POSITIONS	A
-19	(15.00) .591
-29	(22.30) .878

Note:
Some lengths, styles and options are non-standard, non-returnable.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [I/O Connectors](#) category:

Click to view products by [Samtec](#) manufacturer:

Other Similar products are found below :

[571763P](#) [61-168618-12P](#) [72.250.1628.2](#) [72.250.2428.2](#) [74720-0505](#) [76.350.0729.0](#) [76871-1403](#) [MP-5T180MUNNA-005](#) [PCR-E36PM](#) [PCS-XES68MS+](#) [G38A71314B](#) [9776-18-6](#) [1571250010](#) [157-22500-3](#) [MS3471L14-19P L/C](#) [192991-0703](#) [91-644626-35P](#) [SM3100F14S-58S](#)
[172501-6002](#) [FCN-260C008-A/L0](#) [FCN-260C024-AL0](#) [FCN-261Z008](#) [2000314-1](#) [200331-1](#) [PCR-E36FC+](#) [PCS-E28FS+](#) [PCS-XE26SLFD+](#)
[PCS-XE26SLFDT+](#) [G730VID08BDC24](#) [HDMR-29-01-S-SM-TR](#) [HDRA-E68W1LFDTC-SL+](#) [HDR-E14MSG1+](#) [54182-0605](#) [38113800006](#)
[DP3AR020WQ1R200](#) [Z4.102.0680.0](#) [500-1040](#) [500-1052](#) [500-1054](#) [ZP-4008-66L](#) [10-584459-12P](#) [SM3106F14S-7S-LC](#) [SM3106R18-18S](#)
[U90B3054061110](#) [U65-E04-4020](#) [ZPF000000000097891](#) [557-262M2-06C](#) [60-042222-02S](#) [10099439-003C-TRLF](#) [226-0348-000](#)