



HPMC-124-04-L-D-04

HPFC-114-02-L-D-02

(2,54 mm) .100"

HPFC, HPMC SERIES

# SIGNAL POWER COMBO SYSTEM

## SPECIFICATIONS

For complete specifications and recommended PCB layouts see [www.samtec.com?HPFC](http://www.samtec.com?HPFC) or [www.samtec.com?HPMC](http://www.samtec.com?HPMC)

**Insulator Material:**  
Black Liquid Crystal Polymer  
**Signal Contact (HPFC):**  
Phosphor Bronze  
**Power Contact (HPFC):**  
BeCu  
**Terminal (HPMC):**  
Phosphor Bronze (Signal & Power)  
**Plating:**  
Sn or Au over 50µ" (1,27 µm)  
Ni on signal pins; Sn over 50µ" (1,27 µm) Ni on power pins  
**Operating Temp Range:**  
-55°C to +105°C with Tin;  
-55°C to +125°C with Gold  
**Contact Resistance:**  
10 mΩ  
**Insertion Depth:**  
(3,68 mm) .145" to (8,26 mm) .325"  
**Wiping Distance:**  
(0,381 mm) .015"  
**Insertion Force:**  
(Single contact only)  
5 oz (1,39 N) avg. (signal pins)  
56 oz (15,57 N) avg. (power pins)  
**Withdrawal Force:**  
(Single contact only)  
3 oz (0,83 N) avg. (signal pins)  
52 oz (14,46 N) avg. (power pins)  
**Voltage Rating:**  
850 VAC/1201 VDC  
**RoHS Compliant:**  
Yes

**Processing:**  
**Lead-Free Solderable:**  
Yes  
**SMT Lead Coplanarity:**  
(0,15 mm) .006" max (02-20)  
(0,20 mm) .008" max (21-24)

## RECOGNITIONS

For complete scope of recognitions see [www.samtec.com/quality](http://www.samtec.com/quality)



**Note:**  
Some lengths, styles and options are non-standard, non-returnable.

<b>HPFC</b>	<b>1</b>	<b>SIGNAL PIN PER ROW</b>	<b>LEAD STYLE</b>	<b>SIGNAL PIN PLATING</b>	<b>D</b>	<b>POWER PINS</b>	<b>OPTION</b>
Mates with: HPMC		<b>02 thru 24</b>	<b>-01</b> = Through-Hole <b>-02</b> = Surface Mount	<b>-L</b> = 10µ" (0,25 µm) Gold on contact area, Matte Tin on tail (Power Pins = All Matte Tin) <b>-T</b> = Matte Tin		<b>02 thru 04</b>	<b>-LC</b> = Locking Clip (Manual placement required) (Not available with -01 lead style) <b>-K</b> = (6,50 mm) .256" DIA Polyimide film Pick & Place Pad (5 positions minimum)

**RUGGEDIZED SAMTEC**  
• Locking clip option

<b>HPMC</b>	<b>1</b>	<b>SIGNAL PIN PER ROW</b>	<b>LEAD STYLE</b>	<b>SIGNAL PIN PLATING</b>	<b>D</b>	<b>POWER PINS</b>
Mates with: HPFC		<b>02 thru 24</b>	Specify LEAD STYLE from chart	<b>-L</b> = 10µ" (0,25 µm) Gold on contact area, Matte Tin on tail (Power Pins = All Matte Tin) <b>-T</b> = Matte Tin		<b>02 thru 04</b>

LEAD STYLE	A
-01, -02	(5,84) .230
-03, -04	(8,13) .320

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Power to the Board](#) category:*

*Click to view products by [Samtec](#) manufacturer:*

Other Similar products are found below :

[6450552-7](#) [6643429-1](#) [6646040-2](#) [6766604-1](#) [120959-1](#) [1393557-2](#) [1393532-2](#) [1393532-3](#) [1393532-4](#) [1393557-1](#) [1744132-7](#) [1766250-1](#)  
[1892109-1](#) [1-6450850-6](#) [1-6450869-6](#) [1645526-2](#) [2005243-2](#) [377-0020-11130](#) [MC116N](#) [TE34-12-16P-F0](#) [51700-10201602AALF](#) [51970-004](#) [5-6450830-6](#) [4-6600333-3](#) [10125416-4050LF](#) [10130248-005LF](#) [6600320-3](#) [IPBT-103-H1-T-S-RA](#) [1888123-2](#) [6766605-1](#) [701-15-02109](#)  
[6450810-7](#) [46437-1112](#) [6450813-2](#) [6450842-4](#) [10108877-R24403SLF](#) [1645523-1](#) [PSS-06-01-T-S](#) [FWS-03-04-T-S](#) [51760-10301603ABLF](#)  
[MDF6-TA2022HC](#) [FWS-05-01-T-S](#) [51720-10206002AALF](#) [QE-POL-KEY](#) [FWS-08-01-T-S](#) [698-0075-04](#) [6651670-1](#) [MC120N](#) [2-1600788-6](#)  
[1761385-3](#)