

Q PAIRS® TWINAX CABLE ASSEMBLIES



(0.50 mm) .0197" & (0.80 mm) .0315" PITCH • HQDP/EQDP SERIES

EQDP

Mates:

QTE-DP, QSE-DP

HQDP

Mates: QTH-DP, QSH-DP

SPECIFICATIONS

Cable:

30 AWG twinax ribbon

Signal Routing: 100Ω Differential Cable Bending Radius:

(3.18 mm) 1/8" min Plating:
Au over 50 μ" (1.27 μm) Ni Current Rating:
EQDP = 500 mA per pin HQDP = 400 mA pe

(6 adjacent pins powered) **Propagation Delay:** 4.67 nsec/meter

Operating Temp Range: -25 °C to +105 °C

Skew (pair-to-pair):

<10 ps/ft

Skew (within a pair): /sa 5>

EMI Performance:

FCC Class A

SERIES

HQDP = (0.50 mm) .0197" pitch

EQDP = (0.80 mm).0315" pitch

PAIRS

-020,

-040, -060 (20 pairs per bank) HQDP Series

-014, -028, -042 (14 pairs per bank) EQDP Series

LENGTH

-"XX.XX" = Wire Length

in Inches (43.7 mm) 01.72" minimum

NO. 1

NO. 2

Specify END ASSEMBLIES from chart

-5 Pin 1 to Pin 1

WIRING

OPTION

-6 = Pin 1 to Pin 2

-7 = Pin 1 to Second Last Pin

-8 = Pin 1 to Last Pin

SCREW OPTION

Leave blank for no Screw Option

> -F = End No. 1

-S = End No. 2

-B = Both Ends

	← OA	AL = Wire Length + (20.32)	300 ± (3.81) .150 →
	—	Wire Length ± (1.27) .0	950 +
Chille.			
	END NO. 1 (-TEU SHOW	N)	END NO. 2
			(-TTR SHOWN)

END	SURFACE MOUNT	
TTR	Terminal, Top, Notch Right	
TTL	Terminal, Top, Notch Left	
TBR	Terminal, Bottom, Notch Right	
TBL	Terminal, Bottom, Notch Left	
STR	Socket, Top, Notch Right	
STL	Socket, Top, Notch Left	
SBR	Socket, Bottom, Notch Right	
SBI	Socket, Bottom, Notch Left	

END	EDGE MOUNT
TEU	Terminal, Edge, Notch Up
TED	Terminal, Edge, Notch Down
SEU	S ocket, E dge, Notch U p
SED	Socket, Edge, Notch Down

WIRING REQUIREMENTS				
WIRING OPTION	END OPTIONS			
5 or 6	TTR, TBL, STL, SBR, TEU, SED to TTR, TBL, STL, SBR, TED, SEU or TTL, TBR, STR, SBL, TED, SEU to TTL, TBR, STR, SBL, TEU, SED			
7 or 8	TTR, TBL, STL, SBR, TEU, SED to TTL, TBR, STR, SBL, TEU, SED or TTL, TBR, STR, SBL, TED, SEU to TTR, TBL, STL, SBR, TED, SEU			

Cable lengths longer than 40.00" (1 meter) are not supported with S.I. test data.

Design your full cable assembly with Samtec's High-Speed Cable Builder at www.samtec.com/cablebuilder

This Series is non-standard, non-returnable.



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Rectangular Cable Assemblies category:

Click to view products by Samtec manufacturer:

Other Similar products are found below:

MC320E-N-23 A08KR08KR26E203B G125FC10668L0-0300L G125FC10668L0-0150L G125-FC11068L0-0150L G125-FC11068L0-0300L A06XAF06XAF22K254B A10XAF10XAF22K152B A13KR13KR26E254B A12SUR12SUR32W203A A16KR16KR26E203B A12KR12KR26E305A A12KR12KR26E305B A12ZR12ZR28H203B A12ZR12ZR28H203A A10SR10SR30K254A A09SR09SR30K305A A14KR14KR26E254B A10ZR10ZR28H254A A09ZR09ZR28H305A A09ZR09ZR28H305B A13ZR13ZR28H203A A15KR15KR26E254A A13KR13KR26E305B A11ZR11ZR28H254A A11ZR11ZR28H254B A11SR11SR30K254A A12SUR12SUR32W254A A10ZR10ZR28H305A A14KR14KR26E305B A10ZR10ZR28H305B A12ZR12ZR28H254A A15KR15KR26E305A A15KR15KR26E305B A11ZR11SR30K305A A11ZR11ZR28H305B A12ZR12ZR28H254A A12SUR12SUR32W305A A15KR15KR26E305B A11ZR11SR30K305A A11ZR11ZR28H305B A13ZR13ZR28H254A A12SUR12SUR32W305A A12ZR12ZR28H305A A12ZR12ZR28H305A A12ZR12ZR28H305A A12ZR12ZR28H305A A12ZR12ZR28H305A A12ZR12ZR28H305A A12ZR12ZR28H305A A12ZR12ZR28H305A A12ZR12ZR28H305B A20XAF20XAF22K51B A13ZR13ZR28H305A A20XAF20XAF22K102B A20XAF20XAF22K102B A20XAF20XAF22K305B A20XAF20XAF22K254B A20XAF20XAF22K305B A16XSR16XSR36R254B