



HSC8-050-02-19-DP

RU8-160-25-SE-L-DV-BL

**RU8, HSC8 SERIES**

**(0.80 mm) .0315"**

# HIGH-SPEED RISER CARD KIT

## SPECIFICATIONS

For complete specifications and recommended PCB layouts see [www.samtec.com?RU8](http://www.samtec.com?RU8)

## CONNECTOR

**Insulator Material:**  
Black LCP  
**Contact:**  
BeCu  
**Plating:**  
Au or Sn over  
50 μm (1.27 μm) Ni  
**Current Rating:**  
3.1 A per pin  
(6 adjacent pins powered)  
**Operating Temp:**  
-55 °C to +125 °C



## PROCESSING

**Lead-Free Solderable:** Yes  
**SMT Lead Coplanarity:**  
(0.10 mm) .004" max (40-60)  
**RoHS Compliant:** Yes

## RECOGNITIONS

For complete scope of recognitions see [www.samtec.com/quality](http://www.samtec.com/quality)



**Note:** While optimized for 50 Ω applications, this connector with alternative signal/ground patterns may also perform well in certain 75 Ω applications.

**RU8** - **1** POSITIONS PER ROW - **STACK HEIGHT** - **SIGNAL ROUTING** - **PLATING OPTION** - **DV** - **BL** - **OTHER OPTION**

**40, 50, 60**  
Kit contains two connectors and one card. Assembly required.

**-19**  
= (19 mm) .748"

**-25**  
= (25 mm) .984"

**-30**  
= (30 mm) 1.180"

**-SE**  
= Single-Ended

**-DP**  
= Differential Pair

**-L**  
= 10 μm (0.25 μm) Gold on contact, Matte Tin on tail (Plating for connectors) Plating for Card is Hard Gold

**-BL**  
= Board Locks (Bottom Socket only) (Not available on -19 stack height)

**-K**  
= (5.50 mm) .217" DIA Polyimide Film Pick & Place Pad

**-TR**  
= Tape & Reel

**Note:** Other Gold plating options available.

NO. OF POSITIONS PER SIDE	A	B	-SE TOTAL SIGNAL LINES	-DP TOTAL SIGNAL PAIRS
40	(39.80) 1.567	(51.05) 2.010	40	26
50	(47.80) 1.882	(59.05) 2.325	50	32
60	(55.80) 2.197	(67.05) 2.640	60	38

**Note:** Some lengths, styles and options are non-standard, non-returnable.

**Mates with:**  
HSEC8

## SPECIFICATIONS

For complete specifications see [www.samtec.com?HSC8](http://www.samtec.com?HSC8)

**Conductor:**  
1/2 oz Copper  
**Contact Area:**  
Hard Gold Plated  
**Insulator:** FR-4  
**RoHS Compliant:**  
Yes

NO. OF POSITIONS PER SIDE	-SE TOTAL SIGNAL LINES	-DP TOTAL SIGNAL PAIRS
-40	40	26
-50	50	32
-60	60	38

**Note:** Some sizes, styles and options are non-standard, non-returnable.

**HSC8** - **NUMBER OF POSITIONS PER SIDE** - **CARD STYLE** - **STACK HEIGHT** - **SIGNAL ROUTING**

**-040, -050, -060**

**-02**  
= (1.60 mm) .062" thick card

**-19**  
= (19 mm) .748"

**-25**  
= (25 mm) .984"

**-30**  
= (30 mm) 1.180"

**-SE**  
= Single-Ended

**-DP**  
= Differential Pair

STACK HEIGHT	A
-19	(14.84) .584
-25	(20.84) .820
-30	(25.84) 1.017

**Note:** Due to technical progress, all designs, specifications and components are subject to change without notice.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Standard Card Edge Connectors](#) category:*

*Click to view products by [Samtec](#) manufacturer:*

Other Similar products are found below :

[6565204-6](#) [PKC-156](#) [1437274-4](#) [147889-1](#) [1489165-4](#) [EBT156-12B1X](#) [EBT15622B2X](#) [EBT156-22R2W](#) [1-582587-1](#) [1-582589-1](#) [2-6437275-9](#) [284-0102-12100](#) [306022901000000](#) [307-012-502-202](#) [307-024-526-201](#) [307-056-520-300](#) [307-080-526-208](#) [1926088-2](#) [245-062-520-350](#) [287-0032-12101](#) [306-010-500-112](#) [306-028-525-102](#) [306-240-318](#) [307-036-502-202](#) [307-036-521-301](#) [307-072-526-202](#) [345-060-559-303](#) [368-004-520-201](#) [392-008-559-201](#) [534671-1](#) [5-530501-5](#) [341-240-317](#) [345-029-520-300](#) [345-030-500-301](#) [345-044-500-300](#) [345-220-058](#) [346-240-318](#) [387-012-523-300](#) [395-044-520-300](#) [395-100-524-300](#) [50-12B-10](#) [50-6SN-5](#) [09-07-2032](#) [10035388-106LF](#) [10035388-802LF](#) [10115859-011LF](#) [10122859-009LF](#) [101269333204245CLF](#) [10127905-B04B24BLF](#) [530555-1](#)