
HIGH-SPEED EDGE CARD SYSTEMS

0.60 mm, 0.80 mm and 1.00 mm PITCH



FEATURES & BENEFITS

- 56 Gbps PAM4 performance
- PCI Express[®] 3.0, 4.0 and 5.0
- Edge Rate® contacts optimized for signal integrity performance and cycle life
- Up to 200 positions available
- Vertical, right-angle, edge mount, pass-through orientations
- Power/signal combo, press-fit tails, rugged weld tabs, locks and latches
- Mating cable assemblies available







Rugged tucked beam technology (HTEC8)



Differential pair for increased speed (HSEC8-DP)



Custom designs allow for misalignment in the X-Y axes (HSEC1)


KEY SPECIFICATIONS

SERIES	PITCH	TOTAL POSITIONS	INSULATOR MATERIAL	CONTACT MATERIAL	OPERATING TEMP RANGE	CURRENT RATING	VOLTAGE RATING	LEAD-FREE SOLDERABLE
HSEC6	0.60 mm	56-168	Black LCP	Copper Alloy	-55 °C to +125 °C	0.8 A (12 pins)	300 VAC	Yes
HTEC8	0.80 mm	40-200	Black LCP	Copper Alloy	-55 °C to +125 °C	3.0 A (2 pins)	215 VAC	Yes
HSEC8	0.80 mm	18-200	Black LCP	BeCu	-55 °C to +125 °C	2.8 A (2 pins)	240 VAC	Yes
HSEC1	1.00 mm	20-140	Black LCP	Phosphor Bronze	-55 °C to +125 °C	2.2 A (2 pins)	215 VAC	Yes





(0.80 mm) .0315" PITCH • RIGHT-ANGLE & EDGE MOUNT SOCKET



HSEC8-RA


Card Mates: (1.60 mm) .062" thick card,


Cable Mates: ECDP


HSC8



POSITIONS PER ROW	A	В	С
40	(43.80) 1.724	(18.90) .744	(36.60) 1.441
50	(51.80) 2.039	(22.90) .902	(44.60) 1.756
60	(59.80) 2.354	(26.90) 1.059	(52.60) 2.071
40-BL	(51.30) 2.020	(18.90) .744	(36.60) 1.441
50-BL	(59.30) 2.335	(22.90) .902	(44.60) 1.756
60-BL	(67.30) 2.650	(26.90) 1.059	(52.60) 2.071









quantity breaks)

10, 20 & 30 POSITIONS

View complete specifications at: samtec.com?HSEC8-RA




-S = 30 μ" (0.76 μm) Gold on contact area, Matte Tin on tail


HSEC8-EM

Card Mates: (1.60 mm) .062" thick card, HSC8


Cable Mates: ECDP







POSITIONS PER ROW A B 40 (18.90) .744 (36.60) 1.441 50 (22.90) .902 (44.60) 1.756 60 (26.90) 1.059 (52.60) 2.071



Note:

Some sizes, styles and options are non-standard, non-returnable.

View complete specifications at: samtec.com?HSEC8-EM

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Standard Card Edge Connectors category:

Click to view products by Samtec manufacturer:

Other Similar products are found below:

CR7E-30DB-3.96E(72) 6364499-1 6565204-6 PKC-156 1437274-4 147889-1 1489165-4 EBT15622B2X 1-582587-1 284-0102-12100 286-0052-12101A 306022901000000 307-012-502-202 307-056-520-300 2129318-1 245-062-520-350 287-0032-12101 306-028-525-102 307-072-526-202 345-060-559-303 392-008-559-201 534671-1 341-240-317 345-044-500-300 346-240-318 395-100-524-300 09-07-2032 10035388-802LF 10115859-011LF 10122859-009LF 10127905-B04B24BLF 530555-1 5-678046-1 73726-0005 66308-1 1-1437275-6 PEC-07-02-T-S-A 346-014-520-801 307-048-502-202 CE100F22-9-C CE100F26-7-C CE100F28-3-D CE156F18-9-C CE156F22-5-D CE156F22-9-C CT100F22-2-D CT100F22-3-D CT100F24-2-D CT100F24-3-D CT100F24-6-C