



(2.54 mm) .100"

MMTD, MMTDT, MMTS, MMTST, IPM1, T1M74-L, T1M74-R SERIES

DISCRETE WIRE COMPONENTS & TOOLING

Mates with:
MMSD(T), MMSS(T)

-TXS Mates with:
IPL1

SPECIFICATIONS

For complete specifications see www.samtec.com?MMTD, www.samtec.com?MMTDT, www.samtec.com?MMTS or www.samtec.com?MMTST

Insulator Material:
Nylon, White
Contact Material:
Phosphor Bronze
Wire: 20 to 30 AWG
Plating:

Au over 50 μ" (1.27 μm) Ni
Operating Temp Range:
-10 °C to +105 °C (20-26 AWG)
-10 °C to +80 °C (28-30 AWG)
-40 °C to +125 °C (*Teflon®)
Voltage Rating: 600 VAC
RoHS Compliant: Yes

*DuPont™ Teflon® is a registered trademark of the E.I. du Pont de Nemours and Company or its affiliates.

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality



TYPE	PINS PER ROW	WIRE GAUGE	PLATING OPTION	ASSEMBLY LENGTH	END OPTION	OPTION
MMTD = Double Row PVC Cable	-02, -03, -04, -05, -06, -08, -10, -12, -15, -16, -20, -25 (Standard sizes)	-20 -20C = Color Coded Cable (MMTD & MMTS only) -22 -24 -24C = Color Coded Cable (MMTD & MMTS only) -26 -28 -28C = Color Coded Cable (MMTD & MMTS only) -30	-F = Gold flash on contact -L = 10 μ" (0.25 μm) Gold on contact	-“XX.XX” = Assembly Length in Inches -S= (76.2 mm) 03.00" min. -D= (82.6 mm) 03.25" min.	-S = Single End -D = Double End	(Only available with -D) -TUS = Socket on End 2, latch up -TDS = Socket on End 2, latch down

MMTD(T)

MMTS(T)

Notes:
Teflon® cable is intended for crimp only. Contact Samtec for solderable cable applications.

Some lengths, styles and options are non-standard, non-returnable.

APPLICATION

-20C, -24C, -28C
CABLE
COLOR CODING
(PVC CABLE ONLY)

PIN	COLOR
1	BROWN
2	RED
3	ORANGE
4	YELLOW
5	GREEN
6	BLUE
7	VIOLET
8	GRAY
9	WHITE
10	BLACK
ETC	REPEAT

SPECIFICATIONS

For complete specifications see www.samtec.com?IPM1, www.samtec.com?T1M74-L or www.samtec.com?T1M74-R

TOOLING

- Hand Tool:
CAT-HT-174-2030-13
- Mini Applicator (20-24 AWG):
CAT-MC-174-2024-XX-01
- Mini Applicator (26-30 AWG):
CAT-MC-174-2630-XX-01
- Extraction Tool:
CAT-EX-74-01

TYPE	POSITIONS PER ROW	ROW OPTION	TYPE	WIRE GAUGE	PLATING OPTION
IPM1 = Body, Loose	-02, -03, -04, -05, -06, -08, -10, -12, -15, -16, -20, -25 (Standard sizes)	-S = Single Row -D = Double Row	T1M74-L = Contact, Loose T1M74-R = Contact, Full Reel (15,300 Parts per Reel)	-01 = 26 to 30 AWG -02 = 20 to 24 AWG	-F = Gold flash on contact -L = 10 μ" (0.25 μm) Gold on contact

IPM1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Samtec](#) manufacturer:

Other Similar products are found below :

[892-18-020-10-001101](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#)
[609-3404](#) [61062-3](#) [61082-181009](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [641991-4](#) [644827-2](#) [65817-](#)
[010LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68645-018](#) [68648-049](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)
[4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71918-208LF](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [79531-3000](#)
[FCN-360C032-B](#) [FCN-367T-T012/H](#) [FCN-723D010/2](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#)