

# 50 Ω MCX TO 6 GHz

## **MCX Cable Assemblies** RF174, RF178, RF316, **RS316**



# **SERIES**

**RF174** 

= RG 174 Cable

**RF178** 

= RG 178 Cable

**RF316** = RG 316 Cable, Single Braid Shield **RS316** = RG 316 Cable, Double Shielded

END 1 CONNECTOR

END 2 CONNECTOR

**OVERALL LENGTH** 

#### -02SJ1

= MCX Straight Jack

#### -02RP1

= MCX Right-angle Plug (RS316 not available)

**-02SP1** = MCX Straight Plug

-"XXXX" = Overall Length in millimeters

-0100 (100 mm) 3.94" minimum

## **ALSO AVAILABLE**

50  $\Omega$ : MMCX, SMA, SMB, BNC, TNC, N Type = RF174, RF178, RF316 50  $\Omega$ : MMCX, SMA, BNC, TNC = RS316

### **MCX Cable Connectors** MCX-CA



Supplied with pins and ferrules. See website for dimensions.

CONNECTORS FOR INDUSTRY STANDARD CABLES				
MCX-J-C-H-ST-CA1	RG 174/316 Cable			
MCX-J-C-H-ST-CA2	RG 178 Cable			
MCX-J-C-HF-ST-CA1S	RG 316 Double Shielded Cable			
MCX-P-C-H-ST-CA1	RG 174/316 Cable			
MCX-P-C-H-ST-CA2	RG 178 Cable			
MCX-P-C-HF-ST-CA1S	RG 316 Double Shielded Cable			
MCX-P-C-H-RA-CA1	RG 174/316 Cable			
MCX-P-C-H-RA-CA2	RG 178 Cable			

P-C = Cable Plug

J-C = Cable Jack

H or HF = Plating (30  $\mu$ " Gold center contact, 3 μ" Gold outer contact)


ST = Straight


RA = Right-angle


CONNECTORS FOR INDUSTRY STANDARD CABLES				
MCX-J-C-H-ST-CA1	RG 174/316 Cable			
MCX-J-C-H-ST-CA2	RG 178 Cable			
MCX-J-C-HF-ST-CA1S	RG 316 Double Shielded Cable			
MCX-P-C-H-ST-CA1	RG 174/316 Cable			
MCX-P-C-H-ST-CA2	RG 178 Cable			
MCX-P-C-HF-ST-CA1S	RG 316 Double Shielded Cable			
MCX-P-C-H-RA-CA1	RG 174/316 Cable			
MCX-P-C-H-RA-CA2	RG 178 Cable			

TYPE (-RA)	A	В
-P-CA1	(7.78) .306	(9.50) .374
-P-CA2	(8.58) .338	(10.00) .394

TYPE (-ST)	E	F
-J-CA1	(4.50) .177	(15.50) .610
-J-CA2	(4.78) .188	(15.00) .591
L C \ 1 C	(4 EO) 177	(1E EO) 410








### **MCX Board Connectors** MCX-TH, MCX-SM, MCX-EM, MCX-MT

#### Cable Mates: RF174, RF178, RF316, RS316, GRF1H-C, IJ5H



GENDER

**TYPE** 

**-H** = 30 μ" (0.76 μm) Gold center contact,

**PLATING** 

-ST = Straight

**ORIENTATION** 

-RA = Right-angle

# -TH2 = Elevated Through-hole (–ST plug only)

# -SM1

**TERMINATION** 

**-TH1**= Through-hole
(-ST plug not available)

= Surface Mount (Jack only)

**-EM1** = Edge Mount (-ST Jack only)

## -MT1

= Mixed Technology (-ST Jack only)

# **MCX**

# **\_J** = Jack -P = Plug

= PCB Mount

(6.00) .236

-ST-SM1 (Jack)

3 μ" (0.08 μm) Gold outer contact

-RA-TH1 (Plug)

# samtec.com/MCX

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Connectors / Coaxial Connectors category:

Click to view products by Samtec manufacturer:

Other Similar products are found below:

8915-1511-000 89674-0827 6001-7071-019 6002-7051-003 6002-7551-202 6059674-1 619550-1 630059-000 M39030/3-01N 6500-7071-046 6769 CX050L2AQ 7002-1541-010 7002-1542-011 7004-1512-000 7009-1511-004 7010-1511-000 7029-1511-060 7101-1541-010 7101-1571-002 7105-1521-002 7145-1521-002 7203-1571-003 7209-1511-011 7210-1511-015 7210-1511-019 73137-5015 73216-2241 73404-2300 7405-1521-005 7405-1521-802 8527 8547 FS11V 877931 8808-1511-001 9074-9513-000 9101-9573-002 910A205F 9130-9573-002 PL11SC-026 PL375-33 PL40-5 PL74C-221 PL75MC-217 PL803-7 1200690078 1-201144-1 R107003010W R110A172100