



(2,00 mm) .0787"

MMS SERIES

# BOX CONTACT SOCKET

**Mates with:**  
TMMH, TMM, MTMM,  
MMT, TW, LTMM,  
ZLTMM, TCMD, TSH

## SPECIFICATIONS

For complete specifications see [www.samtec.com?MMS](http://www.samtec.com?MMS)

**Insulator Material:**  
Black LCP

**Contact Material:**  
Phosphor Bronze

**Plating:** Sn or Au over 50µ" (1,27 µm) Ni

**Operating Temp Range:**  
-55°C to +125°C with Gold  
-55°C to +105°C with Tin

**Contact Resistance:**  
10 mΩ

**Current Rating:**  
2A per contact @ 80°C ambient

**Insertion Depth:**  
DH = (2,13 mm) .084" to (2,79 mm) .110",  
SH = (2,13 mm) .084" minimum or pass-through Top Entry DV/SV = (2,13 mm) .084" to (4,32 mm) .170" Bottom Entry DV/SV = (4,27 mm) .168" minimum (Plus board)

**Insertion Force:**  
(Single contact only)  
3.7 oz (1,03 N) avg.

**Withdrawal Force:**  
(Single contact only)  
2.2 oz (0,61 N) avg.

**RoHS Compliant:**  
Yes

**Processing:**  
Lead-Free Solderable:  
Yes  
SMT Lead Coplanarity:  
(0,15 mm) .006" max



MMS	1	NO. PINS PER ROW	01	PLATING OPTION	ROW OPTION	OTHER OPTION
02 thru 40			-F = Gold flash on contact, Matte Tin on tail	-SV = Single Vertical	-SH = Single Horizontal	-“XX” = Polarized Position
			-L = 10µ" (0,25 µm) Gold contact, Matte Tin on tail	-DV = Double Vertical	-DH = Double Horizontal	
			-T = Matte Tin			

MMS	1	NO. PINS PER ROW	02	PLATING OPTION	ROW OPTION	OTHER OPTION
02 thru 40			-F = Gold flash on contact, Matte Tin on tail	-SV = Single Vertical	-SH = Single Horizontal	-“XX” = Polarized Position
			-L = 10µ" (0,25 µm) Gold contact, Matte Tin on tail	-DV = Double Vertical	-DH = Double Horizontal	-K = (5,50 mm) .217" DIA Polyimide Film Pick & Place Pad (-SV & -DV only) (-SV = 3 positions min.) (-DV = 4 positions min.)
			-T = Matte Tin	-M = Metal Pick & Place Pad (4 positions min.) (-DV only)	-P = Plastic Pick & Place Pad (4 pos. min., -SV only) (5 pos. min., -DV only)	-TR = Tape & Reel Packaging

## APPLICATION SPECIFIC OPTIONS

- Alignment Pin (-DV only).
  - Locking clips and Through-hole pass-through options available.
- Call Samtec.

**Note:** Some lengths, styles and options are non-standard, non-returnable.

Due to technical progress, all designs, specifications and components are subject to change without notice.

[WWW.SAMTEC.COM](http://WWW.SAMTEC.COM)

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Samtec manufacturer](#):*

Other Similar products are found below :

[ESQT-135-03-F-D-380](#) [QTE-060-01-L-D-A](#) [MSAS-179-ZUGG-18](#) [MTSW-103-07-F-S-240](#) [BCS-116-L-S-TE](#) [ERF8-020-05.0-S-DV-K-TR](#)  
[ERF8-060-05.0-L-DV-K-TR](#) [IDMD-10-T-12.00-A-G-R](#) [SFML-115-01-S-D](#) [SFML-125-01-S-D](#) [LSHM-120-02.5-L-DV-A-N-K-TR](#) [ESQ-110-14-G-D](#) [ESQT-125-03-F-D-310](#) [SO-0515-01-01-02](#) [FJH-50-D-12.00-4](#) [CES-150-01-T-D](#) [QTE-040-04-L-D-A](#) [QTH-020-04-F-D-DP-A-K-TR](#)  
[QTH-060-01-F-D-A](#) [QTH-090-04-L-D-A](#) [TCSD-10-S-05.00-01-F-N](#) [TCSD-15-D-02.00-01-N](#) [TFM-115-02-L-DH](#) [TFM-120-12-S-D-LC](#)  
[TFML-140-02-S-D](#) [TLW-107-05-G-D](#) [BDL-136-T-E](#) [TSS-132-01-G-S](#) [TST-113-04-S-D-RA](#) [TSW-105-14-F-D](#) [MMS-110-01-H-DH](#) [HPF-03-02-T-S](#) [DW-25-11-L-D-450](#) [ERF8-020-01-L-D-RA-L-TR](#) [ERF8-040-05.0-L-DV-TR](#) [SL-120-T-10](#) [SLM-115-01-S-D](#) [CLP-132-02-G-D](#)  
[TFC-125-02-F-D-A-K](#) [TSW-202-07-T-S](#) [ISDF-25-D-M](#) [IPT1-105-01-S-D-RA](#) [IPL1-125-01-S-D-RA](#) [ICO-422-L-GT](#) [HTSW-116-15-L-S-LL](#)  
[HTSW-103-08-L-S-RA](#) [ESQ-116-33-T-T](#) [ERM8-020-02.0-S-DV-TR](#) [TCSD-10-D-06.00-01-N](#) [TCSD-20-D-12.00-01-N](#)