


QTT-117-04-G-5



QST-117-02-G-T

(2,00 mm) .0787"

QTT, QST SERIES

POWER PLANE TERMINAL & SOCKET

SPECIFICATIONS

For complete specifications see www.samtec.com?QTT or www.samtec.com?QST

Insulator Material: Black Liquid Crystal Polymer

Terminal Material (QTT): Phosphor Bronze

Contact Material (QST): Phosphor Bronze

Operating Temp Range: -55°C to +105°C with Tin; -55°C to +125°C with Gold

Plating: Sn or Au over 50µ" (1,27 µm) Ni

Insertion Force (QST): 4 oz (1,11 N) avg

Withdrawal Force (QST): 3 oz (0,837 N) avg

Impedance: 50Ω ±5% @ 170 MHz

50Ω ±20% @ 253 MHz (system @ 50Ω)

RoHS Compliant: Yes

Yes

QTT - **1** NO. PINS PER ROW

LEAD STYLE

Specify LEAD STYLE from chart

LEAD STYLE	A
-01	(7,00) .276
-02	(9,00) .355
-03	(11,00) .433
-04	(13,00) .512

PLATING OPTION

-G = 20µ" (0,51 µm) Gold on contact area Gold flash on tail

-S = 30µ" (0,76 µm) Gold on contact area, Tin on tail

-L = 10µ" (0,25 µm) Gold on contact area, Tin on tail

-F = Gold flash on contact area, Tin on tail


ROW OPTION

-T = Triple Row (Row 2 is Ground Plane)

-5 = Five Row (Rows 2 and 4 are Ground Planes)


10 thru 50

APPLICATIONS



QTT	QST	SPACING
-01	-02	(19,71) .776
-02	-02	(21,72) .855
-03	-03	(27,51) 1.083
-04	-04	(32,31) 1.272

OTHER SOLUTIONS



Note: Some lengths, styles and options are non-standard, non-returnable.

QST - **1** NO. PINS PER ROW

LEAD STYLE

Specify LEAD STYLE from chart

LEAD STYLE	A	B
-01	(16,21) .638	(5,39) .212
-02	(12,70) .500	(3,18) .125
-03	(16,51) .650	(2,29) .090
-04	(19,30) .760	

PLATING OPTION

-G = 20µ" (0,51 µm) Gold on contact area, Gold flash on tail

-S = 30µ" (0,76 µm) Gold on contact area, Tin on tail

-L = 10µ" (0,25 µm) Gold on contact area, Tin on tail

-F = Gold flash on contact area, Tin on tail

ROW OPTION

-T = Triple Row (Row 2 is Ground Plane)

-5 = Five Row (Rows 2 and 4 are Ground Planes)

10 thru 50

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Board to Board & Mezzanine Connectors](#) category:

Click to view products by [Samtec](#) manufacturer:

Other Similar products are found below :

[10135583-642402LF](#) [89885-310LF](#) [589158040000018](#) [6-1393048-0](#) [68683-613](#) [MDF7-12DP-2.54DSA](#) [MDF7-18P-2.54DSA\(01\)](#) [MDF7-20DP-2.54DSA](#) [MDF7-26D-2.54DSA\(55\)](#) [MDF7-3P-2.54DSA\(01\)](#) [MDF7B-3P-2.54DSA\(55\)](#) [MDF7C-11P-2.54DSA\(55\)](#) [MDF7C-18P-2.54DSA\(55\)](#) [MDF7C-5P-2.54DSA\(01\)](#) [MDF7P-5P-2.54DSA\(55\)](#) [75234-0516](#) [FCN-230C068-11](#) [FCN-268F012-G/BD](#) [FCN-268F036-G/BD](#) [FCN-268M012-G/0D](#) [FCN-268M024-G/1D](#) [FCN-360C008-C](#) [FCN-360C040-C](#) [FCN-723J004/1](#) [MIS-048-01-F-D-DP-K](#) [832-10-034-10-001000](#) [93696-325LF](#) [11828-1FA](#) [AXK630345P](#) [18097-0013](#) [ICA-328STT](#) [2007042-2](#) [304400-2](#) [FCN-214Q030-G/0](#) [FCN-215Q040-G/0](#) [FCN-230C068-ESA](#) [FCN-234P048-G/0](#) [FCN-235D050-G/C](#) [FCN-360A3](#) [FCN-360C040-B](#) [210-93-314-41-105000](#) [2-22603-0](#) [379-064-521-202](#) [MDF7-12P-2.54DSA\(01\)](#) [MDF7-16P-2.54DS\(56\)](#) [MDF7-40DP-2.54DSA\(55\)](#) [MDF7-8P-2.54DSA\(55\)](#) [MDF7B-16P-2.54DSA\(55\)](#) [AXG720047](#) [5031084030](#)