

(1.27 mm) .050"

RSM SERIES


SMT MICRO SOCKET

SPECIFICATIONS


For complete specifications and recommended PCB layouts see www.samtec.com?RSM

Insulator Material:
Black Liquid Crystal Polymer
Contact Material:
Phosphor Bronze
Plating:
Au or Sn over
50 μ" (1.27 μm) Ni
Current Rating (RSM/FTR):
3.1 A per pin
(2 pins powered)
Operating Temp Range:
-55 °C to +125 °C
Lead Size Accepted:
(0.46 mm) .018" SQ
Insertion Depth:
Top Entry = (2.64 mm) .104"
to (5.84 mm) .230" with
(0.38 mm) .015" wipe, or
pass-through.
Bottom Entry = (5.49 mm)
.216" minimum
(Add board thickness for
correct post OAL)
RoHS Compliant:
Yes

Mates with:
FTR, HTMS, HDWM,
DWM, TML, ZML, TMS



Optional
pick & place
pad



PROCESSING

Lead-Free Solderable:
Yes
SMT Lead Coplanarity:
(0.10 mm) .004" max


RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality



ALSO AVAILABLE (MOQ Required)

- Other platings
- Locking clips



PLATING OPTION

-L
= 10 μ" (0.25 μm)
Gold on contact,
Matte Tin on tail

ROW OPTION

-S
= Single Row



-D
= Double Row

OPTION


-K
= (6.25 mm)
.246" DIA
Polyimide film
Pick & Place Pad
(5 positions
minimum
for -D)
(7 positions
minimum
for -S)

-P
= Plastic
Pick & Place Pad
(-D = 5
positions
minimum
-S = 6
positions
minimum)

-TR
= Tape & Reel



-S option
Pick & Place Pad



-D option
Pick & Place Pad

Note: Some sizes, styles and options are non-standard, non-returnable.

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

All parts within this catalog are built to Samtec's specifications. Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Board to Board & Mezzanine Connectors](#) category:

Click to view products by [Samtec](#) manufacturer:

Other Similar products are found below :

[10135583-642402LF](#) [89885-310LF](#) [589158040000018](#) [6-1393048-0](#) [68683-613](#) [MDF7-12DP-2.54DSA](#) [MDF7-18P-2.54DSA\(01\)](#) [MDF7-20DP-2.54DSA](#) [MDF7-26D-2.54DSA\(55\)](#) [MDF7-3P-2.54DSA\(01\)](#) [MDF7B-3P-2.54DSA\(55\)](#) [MDF7C-11P-2.54DSA\(55\)](#) [MDF7C-18P-2.54DSA\(55\)](#) [MDF7C-5P-2.54DSA\(01\)](#) [MDF7P-5P-2.54DSA\(55\)](#) [75234-0516](#) [FCN-230C068-11](#) [FCN-268F012-G/BD](#) [FCN-268F036-G/BD](#) [FCN-268M012-G/0D](#) [FCN-268M024-G/1D](#) [FCN-360C008-C](#) [FCN-360C040-C](#) [FCN-723J004/1](#) [MIS-048-01-F-D-DP-K](#) [832-10-034-10-001000](#) [93696-325LF](#) [11828-1FA](#) [AXK630345P](#) [18097-0013](#) [ICA-328STT](#) [2007042-2](#) [304400-2](#) [FCN-214Q030-G/0](#) [FCN-215Q040-G/0](#) [FCN-230C068-ESA](#) [FCN-234P048-G/0](#) [FCN-235D050-G/C](#) [FCN-360A3](#) [FCN-360C040-B](#) [210-93-314-41-105000](#) [2-22603-0](#) [379-064-521-202](#) [MDF7-12P-2.54DSA\(01\)](#) [MDF7-16P-2.54DS\(56\)](#) [MDF7-40DP-2.54DSA\(55\)](#) [MDF7-8P-2.54DSA\(55\)](#) [MDF7B-16P-2.54DSA\(55\)](#) [AXG720047](#) [5031084030](#)