HIGH-SPEEDTHROUGH BOARD SOCKET



-FR = Full Reel Tape & Reel

(must order

maximum quantity per

reel; contact Samtec for quantity breaks)

(1.00 mm) .0394" PITCH • SAL1 SERIES

SAL1

Card Mates:

(1.60 mm) .062" or (2.36 mm) .093" card

SPECIFICATIONS

Insulator Material: Black LCP

Contact Material: BeCu.

Plating: Au or \$n over 50 μ" (1.27 μm) Ni Operating Temp Range: -55 °C to +125 °C


Current Rating:

2.9 A per pin (2 adjacent pins powered)


PROCESSING


Lead-Free Solderable:

SMT Lead Coplanarity: (0.10 mm) .004" max



Matte tin on tail






OTHER SOLUTION HSEC8-PE Card pass-through option. See HSEC8-PE Series.

Notes:

While optimized for 50 Ω applications, this connector with alternative signal/ground patterns may also perform well in certain 75 Ω applications..

Some lengths, styles and options are non-standard, non-returnable.



View complete specifications at: samtec.com?SAL1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for I/O Connectors category:

Click to view products by Samtec manufacturer:

Other Similar products are found below:

571763P 72.250.1628.2 72.250.2428.2 74720-0505 76.350.0729.0 76871-1403 FCN-244F080-G/1 FCN-260A9920 MP-5T180MUNNA-005
PCR-E36PM PCS-XE26MA+ G38A71314B 1571250010 157-22500-3 MS3471L14-19P L/C 91-569786-35H 172501-4002 172501-6002
FCN-260C008-A/L0 FCN-260C024-AL0 FCN-261Z008 2000314-1 200331-1 PCR-E36FC+ PCS-E28FS+ PCS-XE26SLFD+ PCS-XE26SLFD+ PCS-XE26SLFD+ G730VID08BDC24 U90B2054081210 UE86K842720321 38113800006 DP3AR020WQ1R200 Z4.102.0680.0 500-1040
500-1052 500-1054 ZP-4008-66L 0709821002 10-565995-597N DX40-20P(55) 5554841-1 MS3474W18-8P-LC* U90B3054061110 U65-E04-4020 ZPF00000000000097891 557-262M2-06C 747360449 10099439-003C-TRLF 10137239-0021LF E9320-001-01