

(1.27 mm) .050" PITCH • PRESS-FIT & 85 Ω OPEN-PIN-FIELD ARRAYS

SERIES	POSITIONS PER ROW	LEAD STYLE	PLATING OPTION	NO. OF ROWS	OPTION	PACKAGING										
SEAMP Terminal	-10, -20, -30, -40, -50	-02.0 (SEAMP only)	-L = 10 μ" (0.25 μm) Gold on contact area, Matte Tin on tail	-04, -06, -08, -10	-GP Guide Post (SEAMP only)	-TR = Tape & Reel										
SEAFP Socket		-05.0 (SEAFP only)	-S = 30 μ" (0.76 μm) Gold on contact area, Matte Tin on tail	SEAFP: -04 & -06 Rows only		-FR = Full Reel Tape & Reel (must order max. quantity per reel; contact Samtec for quantity breaks)										
SEAMP Board Mates: SEAF, SEAF-RA-GP, SEAFP					<table border="1"> <thead> <tr> <th>NO. OF ROWS</th> <th>A</th> </tr> </thead> <tbody> <tr> <td>-04</td> <td>(7.06) .278</td> </tr> <tr> <td>-06</td> <td>(9.60) .378</td> </tr> <tr> <td>-08</td> <td>(12.14) .478</td> </tr> <tr> <td>-10</td> <td>(14.68) .578</td> </tr> </tbody> </table>	NO. OF ROWS	A	-04	(7.06) .278	-06	(9.60) .378	-08	(12.14) .478	-10	(14.68) .578	
NO. OF ROWS	A															
-04	(7.06) .278															
-06	(9.60) .378															
-08	(12.14) .478															
-10	(14.68) .578															

SEAFP Board Mates: SEAM, SEAM-RA, SEAMP					<table border="1"> <thead> <tr> <th>NO. OF ROWS</th> <th>A</th> </tr> </thead> <tbody> <tr> <td>-04</td> <td>(5.61) .221</td> </tr> <tr> <td>-06</td> <td>(8.15) .321</td> </tr> </tbody> </table>	NO. OF ROWS	A	-04	(5.61) .221	-06	(8.15) .321	
NO. OF ROWS	A											
-04	(5.61) .221											
-06	(8.15) .321											

View complete specifications at: samtec.com?SEAMP & samtec.com?SEAFP. Visit samtec.com?SEAFP-RA for right-angle socket.

SERIES	POSITIONS PER ROW	LEAD STYLE	NO. OF ROWS	085															
SEAR 85 Ω Tuned Riser	-40, -50	-10.0 = 20 mm Mated Height -20.0 = 30 mm Mated Height -30.0 = 40 mm Mated Height	-06, -08, -10																
SEAR Board Mates: SEAF				<table border="1"> <thead> <tr> <th>POSITIONS PER ROW</th> <th>A</th> </tr> </thead> <tbody> <tr> <td>-40</td> <td>(71.42) 2.812</td> </tr> <tr> <td>-50</td> <td>(84.12) 3.312</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th>NO. OF ROWS</th> <th>B</th> </tr> </thead> <tbody> <tr> <td>-06</td> <td>(11.43) .450</td> </tr> <tr> <td>-08</td> <td>(13.97) .550</td> </tr> <tr> <td>-10</td> <td>(16.51) .650</td> </tr> </tbody> </table>	POSITIONS PER ROW	A	-40	(71.42) 2.812	-50	(84.12) 3.312	NO. OF ROWS	B	-06	(11.43) .450	-08	(13.97) .550	-10	(16.51) .650	
POSITIONS PER ROW	A																		
-40	(71.42) 2.812																		
-50	(84.12) 3.312																		
NO. OF ROWS	B																		
-06	(11.43) .450																		
-08	(13.97) .550																		
-10	(16.51) .650																		

SERIES	POSITIONS PER ROW	11.0	PLATING OPTION	NO. OF ROWS	SOLDER TYPE	A	K	"X"R						
SEAMI 85 Ω Tuned Terminal	-40 -50		-L = 10 μ" (0.25 μm) Gold on contact area, Matte Tin on solder tail	-08 -10	-1 = Tin/Lead Alloy Solder Charge			-TR = Tape & Reel						
SEAMI Board Mates: SEAF			-S = 30 μ" (0.76 μm) Gold on contact area, Matte Tin on solder tail		-2 = Lead-Free Solder Charge			-FR = Full Reel Tape & Reel (must order max. quantity per reel; contact Samtec for quantity breaks)						
Note: Some lengths, styles and options are non-standard, non-returnable								<table border="1"> <thead> <tr> <th>NO. OF ROWS</th> <th>A</th> </tr> </thead> <tbody> <tr> <td>-08</td> <td>(13.41) .528</td> </tr> <tr> <td>-10</td> <td>(15.95) .628</td> </tr> </tbody> </table>	NO. OF ROWS	A	-08	(13.41) .528	-10	(15.95) .628
NO. OF ROWS	A													
-08	(13.41) .528													
-10	(15.95) .628													

View complete specifications at: samtec.com?SEAR & samtec.com?SEAMI.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Board to Board & Mezzanine Connectors](#) category:

Click to view products by [Samtec](#) manufacturer:

Other Similar products are found below :

[589158040000018](#) [MDF7C-18P-2.54DSA\(55\)](#) [FCN-230C068-11](#) [FCN-268F012-G/BD](#) [FCN-268F036-G/BD](#) [FCN-268M012-G/0D](#) [FCN-268M024-G/1D](#) [FCN-723J004/1](#) [MIS-048-01-F-D-DP-K](#) [832-10-034-10-001000](#) [FX4C-80S-1.27DSA](#) [FCN-214Q030-G/0](#) [FCN-234P048-G/0](#) [FCN-235D050-G/C](#) [210-93-314-41-105000](#) [2-22603-0](#) [MDF7-40DP-2.54DSA\(55\)](#) [AXG720047](#) [5031084030](#) [MIT-114-03-F-D-K](#) [55323-1519](#) [DF33-2P-3.3DSA\(24\)](#) [YFT-20-05-H-03-SB-K](#) [503308-3040](#) [026-6203-PDB](#) [027-6203-PDB](#) [069159702701000](#) [10123981-102LF](#) [101A10019X](#) [55650-0588-C](#) [68682-310LF](#) [68684-306](#) [75140-7012](#) [87471-650](#) [YTW-30-07-H-Q-410-140](#) [194261-1](#) [FCN-268F024-G0D](#) [10124054-515LF](#) [68685-603](#) [8-1616154-3](#) [MIS-019-01-F-D](#) [FCN-268M024-G/3D](#) [20021832-06016C1LF](#) [KX15-20KLDL-E1000E](#) [MDF7-16DP-2.54DSA\(55\)](#) [AXE810124](#) [FCN-214J100-G/0](#) [FCN-230C068-E/S](#) [AXE812124](#) [AXE816124](#)