



**SLW, CES SERIES**

**(2.54 mm) .100"**

# LOW-PROFILE SOCKET STRIPS

**SLW Mates with:**  
TLW, TSW, MTLW, MTSW,  
HW, EW, ZW, HTSW,  
HMTSW, TSM

**CES Mates with:**  
TLW, TSW, MTLW,  
MTSW, HW, EW, ZW,  
DW, HTSW, PHT, HMTSW

## SPECIFICATIONS

For complete specifications see [www.samtec.com?SLW](http://www.samtec.com?SLW) or [www.samtec.com?CES](http://www.samtec.com?CES)

**Insulator Material:**  
Black G.F. Polyester  
**Contact Material:**  
Phosphor Bronze  
**Plating:**  
Au or Sn over  
50 μ" (1.27 μm) Ni  
**SLW Current Rating (SLW/TSW):**  
5.2 A per pin  
(2 pins powered)  
**CES Current Rating (TSW/CES):**  
5.5 A per pin  
(2 pins powered)  
**Voltage Rating:**  
SLW: 406 VAC  
CES: 400 VAC  
**Operating Temp Range:**  
-55 °C to +125 °C with Gold  
-55 °C to +105 °C with Tin  
**Insertion Depth:**  
SLW: (2.16 mm) .085" to  
(2.92 mm) .115"  
CES: (2.62 mm) .103" to  
(4.06 mm) .160"  
**RoHS Compliant:**  
Yes  
**Lead-Free Solderable:**  
No, Lead Wave only

## RECOGNITIONS

For complete scope of recognitions see [www.samtec.com/quality](http://www.samtec.com/quality)



## ALSO AVAILABLE (MOQ Required)

- Other platings

**Note:**  
Some lengths, styles and options are non-standard, non-returnable.

<b>SLW</b>	<b>1</b>	<b>NO. PINS PER ROW</b>	<b>01</b>	<b>PLATING OPTION</b>	<b>ROW OPTION</b>
<b>01 thru 50</b>					
				<b>-F</b> = Gold flash on contact, Matte Tin on tail	<b>-S</b> = Single Row
				<b>-L</b> = 10 μ" (0.25 μm) Gold on contact, Matte Tin on tail	<b>-D</b> = Double Row
				<b>-G</b> = 20 μ" (0.51 μm) Gold on contact, Gold flash on balance	
				<b>-T</b> = Matte Tin	

<b>CES</b>	<b>1</b>	<b>NO. PINS PER ROW</b>	<b>LEAD STYLE</b>	<b>PLATING OPTION</b>	<b>ROW OPTION</b>	<b>RA OPTION</b>
<b>01 thru 50</b>						
			<b>-01</b> = (3.25 mm) .128 "A" Dim.	<b>-L</b> = 10 μ" (0.25 μm) Gold contact, Matte Tin on tail	<b>-S</b> = Single Row	<b>-RA</b> = Right-angle version
			<b>-02</b> = (5.66 mm) .223 "A" Dim.	<b>-T</b> = Matte Tin	<b>-D</b> = Double Row	Style -02 only Single Row only

Due to technical progress, all designs, specifications and components are subject to change without notice.

[WWW.SAMTEC.COM](http://WWW.SAMTEC.COM)

All parts within this catalog are built to Samtec's specifications. Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [Samtec](#) manufacturer:*

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [000-34000](#) [0009482033](#) [0009507031](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [647662-1](#) [65039-019ELF](#) [65817-002LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67016-026LF](#) [67046-001LF](#) [67095-007LF](#) [67230-005LF](#)