## 50 $\Omega$ SMA TO 6 GHz

**SMA Cable Assemblies** RF174, RF178, RF316,



**SERIES** 

END 1 CONNECTOR

END 2 CONNECTOR

OVERALL LENGTH

-"XXXX"

millimeters

-0100 (100 mm)

3.94" minimum

Overall Length in

**RF174** 

= RG 174 Cable

**RF178** 

= RG 178 Cable (-01BJ1 & -01BR1 only)

**RF316** 

= RG 316 Cable, Single Braid Shield

**RS316** 

= RG 316 Cable, Double Shield (-01SP1 & -01BJ1 only)

= RG 58 Cable, (-01SP1, -01BJ1 & 01SB1 only)

-01SP1

= SMA Straight Plug

-01RP1

= SMA Right-angle Plug

-01BJ1

= SMA Straight Bulkhead Jack

-01SB1

= Straight Bulkhead Jack, Sealed

-01SR1

= Straight Bulkhead Jack, Sealed, Reversed Polarity

-01BR1

= Straight Bulkhead Jack, Reversed Polarity

-01PN1

= 4-Hole Panel Mount Jack

**ALSO AVAILABLE** 

50 Ω: MCX, MMCX, SMB, BNC, TNC, N Type = RF174, RF178, RF316

 $50 \Omega$ : MCX, MMCX, BNC, TNC = RS316

 $50 \Omega$ : TNC = RF058

**SMA Cable Connectors** 

SMA-CA

Supplied with pins, washers, nuts and ferrules. See website for dimensions.

**SMA GENDER** 

= Jack

(11.00) \_ .433 Hex.

**WWWWWWWW** 

← (12.60) .496 →

-S10, -B10

-P

= Plug

**TYPE** 

-C

= Cable

-C4

= Cable

4-Mounting Screws (–PN1 only)

**PLATING** 

**-H** = 30 μ" (0.76 μm) Gold center contact, 3 µ" (0.08 µm) Gold outer contact (N/A with -BH1S)

-HF

= 30 µ" (0.76 µm) Gold center contact, 3 µ" (0.08 µm) Gold outer contact (-BH1S only)

ORIENTATION

-ST = Straight

RG 174 / 316 Cable -BH2

-BH1

= Bulkhead

= Bulkhead RG 178 Cable

-BR1 = Bulkhead RG 174 / 316, Reversed Polarity

-BR2 = Bulkhead RG 178 Cable, **Reversed Polarity**  -BH1S

**TERMINATION** 

= Bulkhead RG 316 Cable, Double Shield

-B10 Bulkhead RG 58 Cable

-PN1

= 4-Hole Panel Mount RG 174 / 316 Cable

**-S10** = Sealed Bulkhead RG 58 Cable




**SMA Board Connectors** See page 145 for

**Board Connectors** 

**SMA GENDER** 

•

-C = Cable



-ST-C10

**TYPE PLATING** 

**-H** = 30 μ" (0.76 μm) Gold center contact, 3 µ" (0.08 µm) Gold outer contact (-CA1, -C10 only)

**– Η F** = 30 μ" (0.76 μm)

Gold center contact, 3 μ" (0.08 μm) Gold outer contact (-CA1S only)

-ST = Straight

ORIENTATION

-RA

= Right-angle

**-C10** = RG 58 Cable (-ST only)

**TERMINATION** 

-CA1

= RG 174 / 316 Cable

**-CA1S** = RG 316 Double Shielded Cable (-ST only)

Supplied with pins, washers, nuts and ferrules. See website for dimensions.

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Connectors / Coaxial Connectors category:

Click to view products by Samtec manufacturer:

Other Similar products are found below:

8915-1511-000 89674-0827 6001-7071-019 6002-7051-003 6002-7551-202 6059674-1 619550-1 630059-000 M39030/3-01N 6500-7071-046 6769 CX050L2AQ 7002-1541-010 7002-1542-011 7004-1512-000 7009-1511-004 7010-1511-000 7029-1511-060 7101-1541-010 7101-1571-002 7145-1521-002 7203-1571-003 7209-1511-011 7210-1511-015 7210-1511-019 73137-5015 73216-2241 73404-2300 7405-1521-005 7405-1521-802 8527 8547 FS11V 877931 9049-9513-000 9074-9513-000 9101-9573-002 910A205F 9130-9573-002 PL11SC-026 PL375-33 PL40-5 PL74C-221 PL75MC-217 PL803-7 980-8666-005 1200690078 1-201144-1 R107003010W R110A172100