## MICROMATE<sup>™</sup>

# (1.00 mm) .0394" • SINGLE ROW DISCRETE WIRE TERMINAL





### NO. OF **POSITIONS**





### **ASSEMBLED** LENGTH

### **PANEL** OPTION

## **PINOUT**

## T1SS

= Single Row Non-Panel Mount **PVC Cable** 

## T<sub>1</sub>PS

= Single Row Panel Mount **PVC Cable** 

## T1SST

= Single Row Non-Panel Mount Blue \*Teflon® Cable

## T1PST

= Single Row Panel Mount Blue \*Teflon® Cable

## T1SS(T), T1PS(T)

## -02 postions not available with T1PS or T1PST)

-02 thru -10 (Per Row)

## -28 = 28 AWG

-28C = 28 AWG Color Coded Cable (T1SS & T1PS only)

> -30 = 30 AWG

-30C = 30 AWG Color Coded Cable (T1SS & T1PS only)

-GF = 3 µ" (0.07 µm) Gold on contact = Assembled Length and tail

### -"XX.X" (Leave blank for

-28C, –30C CABLE COLOR CODING

**COLOR** 

**BROWN** 

RED

ORANGE

YELLOW GREEN

BLUE

VIOLET

GRAY

WHITE

BLACK

REPEAT

PIN

8

9

10

ETC

in Inches (45.7 mm) 01.8" min. non-panel mount)

-A = Fits .033" (0.84 mm), .062" (1.57 mm) and .090" (2.29 mm) Thick Panels

(Leave blank for single ended

## assembly) -D1

= Double Ended down (Not available with T1PS or T1PST)

## -D3

= Double Ended up (Not available with T1PS or T1PST)

## \_T1

= Transfer to socket down

## -T3

= Transfer to socket up

## Cable Mates:


S1SS, S1SS7

## **SPECIFICATIONS**


Insulator Material: Nylon, Light Green Contact Material: Phosphor Bronze Plating:

Au over 50 µ" (1.27 µm) Ni
Operating Temp Range:
-10 °C to +80 °C (PVC)
-40 °C to +125 °C (Teflon®)

Wire: 28 or 30 AWG



±(3.18) .125



\*DuPont™ Teflon® is a registered trademark of the E.I. du Pont de Nemours and Company or its affiliates.

### Note:

Teflon® cable is intended for crimp only. Contact Samtec for solderable cable applications.

View complete specifications at: samtec.com?T1SS, samtec.com?T1SST, samtec.com?T1PS & samtec.com?T1PST

# **SERIES**

IST1

= Single Row Body

ISP1 = Single Row

Panel Mount Body

## NO. OF POSITIONS


-02 thru -10 (IST1 Body)


**-03 thru -10** (ISP1 Body)

## PANEL THICKNESS

(Leave blank for IST1)

= Fits 0.84 mm, 1.57 mm & 2.29 mm Thick Panels





## **SERIES**

TC37R

= Contact, Full Reel (25,000 Parts per Reel)

**TC37M** = Contact, Mini Reel (1,000 - 5,000 Parts per

Reel)



## **PLATING**

## -GF


= 3 μ" (0.07 μm) Gold contact and tail




Some lengths, styles and options are non-standard. non-returnable.

## No. of positions x (1.00) .03937 + (1.40) .055 (4.65)







## **TOOLING**

Hand Tool: CAT-HT-1137-2830-12

Mini Applicator: CAT-MC-309-2830-XX-01

View complete specifications at: samtec.com?IST1, samtec.com?ISP1, samtec.com?TC37R & samtec.com?TC37M

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Rectangular Cable Assemblies category:

Click to view products by Samtec manufacturer:

Other Similar products are found below:

MC320E-N-23 A08KR08KR26E203B G125FC10668L0-0300L G125FC10668L0-0150L G125-FC11068L0-0150L G125-FC11068L0-0300L A06XAF06XAF22K254B A10XAF10XAF22K152B A13KR13KR26E254B A12SUR12SUR32W203A A16KR16KR26E203B A12KR12KR26E305A A12KR12KR26E305B A12ZR12ZR28H203B A12ZR12ZR28H203A A10SR10SR30K254A A09SR09SR30K305A A14KR14KR26E254B A10ZR10ZR28H254A A09ZR09ZR28H305A A09ZR09ZR28H305B A13ZR13ZR28H203A A15KR15KR26E254A A13KR13KR26E305B A11ZR11ZR28H254A A11ZR11ZR28H254B A11SR11SR30K254A A12SUR12SUR32W254A A10ZR10ZR28H305B A12ZR12ZR28H254A A15KR15KR26E305A A15KR15KR26E305B A11ZR11ZR28H305B A12ZR12ZR28H254A A15KR15KR26E305A A15KR15KR26E305B A11ZR11ZR28H305B A13ZR13ZR28H254A A12SUR12SUR32W305A A12ZR12ZR28H305A A12ZR12ZR28H305B A13ZR13ZR28H254A A12SUR12SUR32W305A A12ZR12ZR28H305A A12ZR12ZR28H305B A20XAF20XAF22K51B A13ZR13ZR28H305A A20XAF20XAF22K102B A20XAF20XAF22K152B A20XAF20XAF22K203B A20XAF20XAF22K305B A16XSR16XSR36R254B A03ZR03ZR28H51B A03SR03SR30K51B