


RUGGED TIGER EYE™ SYSTEMS

(2.00 mm) .0787" PITCH



MAX
3.8
A m p s

8
G b p s

FEATURES & BENEFITS

- Rugged Tiger Eye™ contact system for high-reliability
- Wide range of stack heights (SMM/TMM Series)
- Right-angle mating headers available
- Optional metal latching, screw downs, weld tabs and locking clips
- Surface mount or through-hole
- Discrete wire assemblies available in 24-30 AWG PVC or Teflon® wire; contact.asp@samtec.com for custom solutions



Optional strain relief and variety of wiring options



Components (ISD2/CC81) & tooling available: samtec.com/tooling






KEY SPECIFICATIONS (S2M/T2M)

| PITCH | STACK HEIGHTS | TOTAL PINS | INSULATOR MATERIAL | CONTACT MATERIAL | PLATING | OPERATING TEMP RANGE | CURRENT RATING | MAX CYCLES |
|---------|---------------|------------|--------------------|-------------------------------------|-------------------------------------|----------------------|---|--------------------------------|
| 2.00 mm | 6 & 7 mm | 10 - 60 | Black LCP | BeCu (S2M) Phosphor Bronze (T2M) | Au or Sn over 50 μ" (1.27 μm) Ni | -55 °C to +125 °C | 3.8 A (T2M) 2.6 A (S2M (2 pins powered) | 100 with 10 μ" (0.25 μm) Au |

(2.00 mm) .0787" PITCH • HIGH-RELIABILITY CABLE INTERCONNECTS

| SERIES | 1 | NO. OF POSITIONS | LEAD STYLE | PLATING OPTION | D | OPTIONS | PACKAGING |
|----------------------|---|--|---|--|---|--|--|
| S2M Socket | | 05, 07, 10, 15, 20, 25, 30 (Per Row) | -01 = Through-hole -02 = Surface Mount | -F = Gold flash on contact, Matte Tin on tail -L = 10 μ" (0.25 μm) Gold on contact, Matte Tin on tail | | -K = (5.50 mm) .217" DIA Polyimide film Pick & Place Pad (-02 only) -LC = Locking Clip (Manual placement required) (-02 only) -DS = Screw Down (N/A with -LC) (mates with -T2M-DS) | Leave blank for tube packaging -TR = Tape & Reel (-02 only) -FR = Full Reel Tape & Reel (must order max. quantity per reel; contact Samtec for quantity breaks) (-02 only) |





S2M
Board Mates:
T2M
Cable Mates:
T2SD


View complete specifications at: samtec.com?S2M

| SERIES | 1 | NO. OF POSITIONS | 01 | PLATING OPTION | D | TAIL OPTION | OTHER OPTIONS | PACKAGING |
|----------------------|---|--|----|---|---|--|--|--|
| T2M Header | | 05, 07, 10, 15, 20, 25, 30 (Per Row) | | -L = 10 μ" (0.25 μm) Gold on contact, Matte Tin on tail | | -TH = Through-hole -RA = Right-angle -SM = Surface Mount | -WT = Weld Tab (S2SD & S2SDT, -SR/-DR required mate) -DS = Screw Down (N/A with -RA) (mates with -S2M-DS, S2SD/S2SDT -SS/-DS option) -K = (7.50 mm) .295" DIA Polyimide film Pick & Place Pad (-SM only) | Leave blank for tube packaging -TR = Tape & Reel (-SM only) -FR = Full Reel Tape & Reel (must order max. quantity per reel; contact Samtec for quantity breaks) (-SM only) |

T2M
Board Mates:
S2M
Cable Mates:
S2SD, S2SDT

MATED HEIGHT



SM= (7.06 mm) .278"
THT= (6.17 mm) .243"

View complete specifications at: samtec.com?T2M

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Samtec](#) manufacturer:

Other Similar products are found below :

[892-18-020-10-001101](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#)
[609-3404](#) [61062-3](#) [61082-181009](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [641991-4](#) [644827-2](#) [65817-](#)
[010LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68645-018](#) [68648-049](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)
[4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71918-208LF](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [79531-3000](#)
[FCN-360C032-B](#) [FCN-367T-T012/H](#) [FCN-723D010/2](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#)