


HTSS-125-01-L-DV



(2,54mm) .100"

TSS, TST, HTSS, HTST, ZSS, ZST SERIES

SHROUDED .025" SQ POST HEADERS

TSS, HTSS, ZSS

Mates with:
SSW, SSQ, ESW, ESQ,
SSM, BCS

TST, HTST, ZST

Mates with:
IDSD

SPECIFICATIONS

For complete specifications see www.samtec.com?TSS, www.samtec.com?TST, www.samtec.com?HTSS, www.samtec.com?HTST, www.samtec.com?ZSS or www.samtec.com?ZST

Insulator Material:
Black Glass Filled Polyester (TSS, TST, ZSS, ZST)
Natural PCT (HTSS, HTST)



Insulation Resistance:

5000 MΩ min
Terminal Material:
Phosphor Bronze

Plating:

Au or Sn over 50µ" (1,27µm) Ni

Current Rating:

3A

Operating Temp Range:

-55°C to +125°C with Gold

-55°C to +105°C with Tin

Flammability Rating:

UL 94V-O

Withstanding Voltage:

1000 VRMS

RoHS Compliant:

Yes

Processing:

Lead-Free Solderable:

Yes (HTSS, HTST)

Wave Only (TSS, TST, ZSS, ZST)

SMT Lead Coplanarity:

(0,15mm) .006"

APPLICATION SPECIFIC OPTION

- Alignment Pins
 - Single Row
 - Locking Leads
 - Polarized
- Call Samtec.

Note: Other Gold plating options available. Contact Samtec.

Note: Some lengths, styles and options are non-standard, non-returnable. ZSS, ZST are non-standard, non-returnable.



TSS
= Top Shrouded Connector Strip

TST
= Top Shrouded Cable Strip

HTSS
= High Temp Top Shrouded Connector Strip

HTST
= High Temp Top Shrouded Cable Strip

ZSS
= Elevated Connector Strip

ZST
= Elevated Cable Strip

Specify "LEAD STYLE" from chart

LEAD STYLE	STRAIGHT TAIL LENGTH (A)
-01	(2,92) .115
-02	(4,19) .165
-03	(14,35) .565

LEAD STYLE	ZSS/ZST OVERALL LENGTH (C)
-01	(16,00) .630
-02	(18,54) .730
-03	(21,08) .830
-04	(23,62) .930
-05	(26,16) 1.030
-06	(28,70) 1.130
-07	(31,24) 1.230
-08	(33,78) 1.330
-09	(36,32) 1.430

LEAD STYLE	TSS/TST/HTSS/HTST RIGHT ANGLE TAIL LENGTH (B)
-04	(3,30) .130
-05	(5,84) .230

HTSS/HTST Lead Style -01

-D
= Double Row Through-hole (lead style -01, -02 & -03 only or BODY HEIGHT must be specified)

-DV
= Double Row Surface Mount (lead style -01 only) (HTSS, HTST only)

-D-RA
= Double Row Right Angle (lead style -04 & -05 only) (ZSS, ZST not available)

- "XXXX"
= Body Height (ZSS, ZST & -D only)

LEAD STYLE	MAX. BODY HEIGHT
-01	.540 (13,72)
-02	.640 (16,26)
-03	.740 (18,80)
-04	.840 (21,34)
-05	.940 (23,88)
-06	1.040 (26,42)
-07	1.140 (28,96)
-08	1.240 (31,50)
-09	1.340 (34,04)

For board stacking height add .085" (2,16mm) when mated with SSW series.
Example: ZST-1XX-01-X-X-465 mated with SSW = (13,97mm) .550" board space

05, 07, 08, 10, 12, 13, 15, 17, 20, 25, 32, 36
(Call Samtec for other sizes.)

TYPE STRIP	X	Y
HTSS TSS ZSS	(2,54) .100 X No. of Positions + (1,27) .050	(2,54) .100 X No. of Positions + (3,81) .150
HTST TST ZST	(2,54) .100 X No. of Positions + (5,08) .200	(2,54) .100 X No. of Positions + (7,62) .300

TSS, TST ZSS, ZST

Specify -SS for cost-effective heavy Gold where it counts!

-L
= 10µ" (0,25µm) Gold on post, Matte Tin on tail

-G
= 10µ" (0,25µm) Gold on post, Gold flash on balance (not available on -DV)

-T
= Matte Tin

-SS
= 30µ" (0,76µm) Gold stripe on contact area, Gold flash to tip, Matte Tin on tail (TSS & HTSS only) (Straight -01, -02, -03, Right Angle -04 & Surface Mount -01 only)

Due to technical progress, all designs, specifications and components are subject to change without notice.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Samtec](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [009176003701906](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#)