


SURFACE MOUNT ALUMINUM ELECTROLYTIC CAPACITORS

RC Chip type, Wide Temperature Range Series



- Wide operating temperature range of -55 ~ +105°C
- Designed for surface mounting on high density PC board
- Applicable to automatic insertion machine using carrier tape
- Complied to the RoHS directive



Item	Characteristics							
Operating temperature range	-55 ~ +105°C							
Leakage current max.	I = 0.01CV or 3μA whichever is greater (after 2 minutes)							
Capacitance tolerance	±20% at 120Hz, 20°C							
Dissipation factor max. (at 120Hz, 20°C)	WV	6.3	10	16	25	35	50	
	tanδ	0.27	0.23	0.19	0.15	0.13	0.11	
Low temperature characteristics (Impedance ratio at 120Hz)	WV	6.3	10	16	25	35	50	
	Z-25°C/Z+20°C	3	3	2	2	2	2	
	Z-40°C/Z+20°C	8	5	4	3	3	3	
Load life (after application of the rated voltage for 1000 hours at 105°C)	Leakage current	Less than specified value						
	Capacitance change	Within ±25% of initial value						
	tanδ	Less than 200% of specified value						
Shelf life (at 105°C)	After 1000 hours no load test, leakage current, capacitance and tanδ are same as load life value. The measurement shall be performed at 20°C by the KS C 6035 clause 5.4.							
Resistance to soldering heat	The following specifications shall be satisfied when the capacitors are restored to 20°C after exposing them at 250°C for 10 seconds.							
	Leakage current	Less than specified value						
	Capacitance change	Within ±10% of initial value						
	tanδ	Less than specified value						

● DRAWING (See page 55)

Unit : mm

-Series code of RC is "F"

● DIMENSIONS & MAXIMUM PERMISSIBLE RIPPLE CURRENT

μF \ WV	6.3	10	16	25	35	50
0.1						4×5.3 2
0.22						4×5.3 3
0.33						4×5.3 4
0.47						4×5.3 5
1.0						4×5.3 7
2.2						4×5.3 11
3.3						4×5.3 13
4.7				4×5.3 13	4×5.3 14	5×5.3 18
10			4×5.3 17	5×5.3 23	5×5.3 24	6.3×5.3 31
22	4×5.3 22	5×5.3 27	5×5.3 30	6.3×5.3 39	6.3×5.3 42	6.3×5.8 45
33	5×5.3 31	5×5.3 33	6.3×5.3 43	6.3×5.3 48	6.3×5.8 52	6.3×7.7 60
47	5×5.3 36	6.3×5.3 46	6.3×5.3 51	6.3×5.8 59	6.3×5.8 63	6.3×7.7 63
100	6.3×5.3 50	6.3×5.8 64	6.3×5.8 64	6.3×7.7 91	8×10 296	10×10 295
220	6.3×7.7 86	6.3×7.7 105	6.3×7.7 105	8×10 340	10×10 435	
330	6.3×7.7 105	8×10 305	8×10 340	10×10 470		
470	8×10 330	10×10 340	10×10 470			
1000	10×10 475					

↑ ↑ Ripple current (mA rms) at 105°C, 120Hz
Case size ØD×L (mm)

● FREQUENCY COEFFICIENT OF PERMISSIBLE RIPPLE CURRENT

Frequency	50Hz	120Hz	300Hz	1kHz	10kHz ≤
Coefficient	0.70	1.00	1.17	1.36	1.50

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Samwha manufacturer](#):

Other Similar products are found below :

[6TL2JRB474K](#) [BK2D106M1012MBB](#) [BK2D226M12016PL](#) [BK2D685M1012MBB](#) [BK2E336M12025BB](#) [BK2G105M1012MBB](#)
[BK2G155M1012MBB](#) [BK2G335M10016BB](#) [BK2V226M12025BB](#) [CA1E337M10010VR](#) [CA1V227M10010VR](#) [CK0J107M6L006VR](#)
[CQ1608C0G221J500NRB](#) [CS1005X7R104K500NR](#) [CS1608X7R105K250NRB](#) [CS1608X7R221K500NRB](#) [CS1608X7R225K100NRB](#)
[CS2012X5R225K250NRE](#) [CS2012X5R225K500NRE](#) [CS2012X5R226M250NRE](#) [CS2012X5R475K500NRE](#) [CS2012X7R105K500NRE](#)
[CS2012X7R106K100NRE](#) [CS2012X7R224K500NRE](#) [CS2012X7R225K250NRE](#) [CS2012X7R475K160NRE](#) [CS2012X7R475K250NRE](#)
[CS2012X7R475K350NRE](#) [CS3216X5R106K500NRI](#) [CS3216X5R226K160NRI](#) [CS3216X7R106K250NRI](#) [CS3216X7R106K350NRI](#)
[CS3216X7R225K101NRI](#) [CS3216X7R226K160NRI](#) [CS3216X7R475K500NRI](#) [CS3225X7R106K500NRL](#) [CS3225X7R226K250NRL](#)
[CS3225X7R476K100NRL](#) [CS3225X7S476K160NRL](#) [DB5U107W22045HA](#) [DB5U207M30045HA](#) [DB5U307W35050HA](#)
[DB5U407W35060HA](#) [GL2W338M76110SB](#) [GL2W478M76150SB](#) [GT1H109M35060SB](#) [GT1J229M35120SB](#) [GT1J339M51100SB](#)
[GT1J478M35060SB](#) [GT2A109M35100SB](#)