



**N-channel Enhanced mode TO-252/SOT223 MOSFET****Features**

- High ruggedness
- Low  $R_{DS(ON)}$  (Typ 7Ω)@ $V_{GS}=10V$
- Low Gate Charge (Typ 7nC)
- Improved dv/dt Capability
- 100% Avalanche Tested
- Application: Charger, Adaptor, LED

**1. Gate 2. Drain 3. Source** **$BV_{DSS} : 600V$**  **$I_D : 1A$**  **$R_{DS(ON)} : 7\Omega$** **General Description**

This power MOSFET is produced with advanced technology of SAMWIN.

This technology enable the power MOSFET to have better characteristics, including fast switching time, low on resistance, low gate charge and especially excellent avalanche characteristics.

**Order Codes**

Item	Sales Type	Marking	Package	Packaging
1	SW D 1N60DC	SW1N60DC	TO-252	REEL
2	SW SA 1N60DC	SW1N60DC	SOT223	REEL

**Absolute maximum ratings**

Symbol	Parameter	Value		Unit
		TO-252	SOT223	
$V_{DSS}$	Drain to source voltage	600		V
$I_D$	Continuous drain current (@ $T_C=25^\circ C$ )	1*		A
	Continuous drain current (@ $T_C=100^\circ C$ )	0.63*		A
$I_{DM}$	Drain current pulsed	(note 1)	4	A
$V_{GS}$	Gate to source voltage		$\pm 30$	V
$E_{AS}$	Single pulsed avalanche energy	(note 2)	50	mJ
$E_{AR}$	Repetitive avalanche energy	(note 1)	5	mJ
$dv/dt$	Peak diode recovery $dv/dt$	(note 3)	5	V/ns
$P_D$	Total power dissipation (@ $T_C=25^\circ C$ )	125	6.7	W
	Derating factor above 25°C	1.0	0.05	W/°C
$T_{STG}, T_J$	Operating junction temperature & storage temperature	-55 ~ + 150		°C

\*. Drain current is limited by junction temperature.

**Thermal characteristics**

Symbol	Parameter	Value		Unit
		TO-252	SO-T223	
$R_{thjc}$	Thermal resistance, Junction to case	1.0	18.6	°C/W
$R_{thja}$	Thermal resistance, Junction to ambient	100	74.5	°C/W

## Electrical characteristic ( $T_J = 25^\circ\text{C}$ unless otherwise specified )

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
<b>Off characteristics</b>						
$\text{BV}_{\text{DSS}}$	Drain to source breakdown voltage	$V_{\text{GS}}=0\text{V}, I_D=250\mu\text{A}$	600			V
$\Delta \text{BV}_{\text{DSS}} / \Delta T_J$	Breakdown voltage temperature coefficient	$I_D=250\mu\text{A}$ , referenced to $25^\circ\text{C}$		0.5		$^\circ\text{C}$
$I_{\text{DSS}}$	Drain to source leakage current	$V_{\text{DS}}=600\text{V}, V_{\text{GS}}=0\text{V}$			1	$\mu\text{A}$
		$V_{\text{DS}}=480\text{V}, T_J=125^\circ\text{C}$			50	$\mu\text{A}$
$I_{\text{GSS}}$	Gate to source leakage current, forward	$V_{\text{GS}}=30\text{V}, V_{\text{DS}}=0\text{V}$			100	nA
	Gate to source leakage current, reverse	$V_{\text{GS}}=-30\text{V}, V_{\text{DS}}=0\text{V}$			-100	nA
<b>On characteristics</b>						
$V_{\text{GS(TH)}}$	Gate threshold voltage	$V_{\text{DS}}=V_{\text{GS}}, I_D=250\mu\text{A}$	2.5		4.5	V
$R_{\text{DS(ON)}}$	Drain to source on state resistance	$V_{\text{GS}}=10\text{V}, I_D = 0.5\text{A}, T_J=25^\circ\text{C}$		7	8.5	$\Omega$
		$V_{\text{GS}}=10\text{V}, I_D = 0.5\text{A}, T_J=125^\circ\text{C}$		14		$\Omega$
$G_{\text{fs}}$	Forward transconductance	$V_{\text{DS}} = 30 \text{ V}, I_D = 0.5\text{A}$		0.9		S
<b>Dynamic characteristics</b>						
$C_{\text{iss}}$	Input capacitance	$V_{\text{GS}}=0\text{V}, V_{\text{DS}}=25\text{V}, f=1\text{MHz}$		198		pF
$C_{\text{oss}}$	Output capacitance			29		
$C_{\text{rss}}$	Reverse transfer capacitance			4		
$t_{\text{d(on)}}$	Turn on delay time	$V_{\text{DS}}=300\text{V}, I_D=1\text{A}, R_G=25\Omega, V_{\text{GS}}=10\text{V}$ (note 4,5)		8		ns
$t_r$	Rising time			22		
$t_{\text{d(off)}}$	Turn off delay time			19		
$t_f$	Fall time			25		
$Q_g$	Total gate charge			7		nC
$Q_{\text{gs}}$	Gate-source charge	$V_{\text{DS}}=480\text{V}, V_{\text{GS}}=10\text{V}, I_D=1\text{A}$ (note 4,5)		1.6		
$Q_{\text{gd}}$	Gate-drain charge			3.5		
$R_g$	Gate resistance	$V_{\text{DS}}=0\text{V}, \text{Scan F mode}$		3.2		$\Omega$


## Source to drain diode ratings characteristics

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$I_s$	Continuous source current	Integral reverse p-n Junction diode in the MOSFET			1	A
$I_{\text{SM}}$	Pulsed source current				4	A
$V_{\text{SD}}$	Diode forward voltage drop.	$I_s=1\text{A}, V_{\text{GS}}=0\text{V}$			1.4	V
$t_{\text{rr}}$	Reverse recovery time	$I_s=1\text{A}, V_{\text{GS}}=0\text{V}, \frac{dI_F}{dt}=100\text{A/us}$		244		ns
$Q_{\text{rr}}$	Reverse recovery charge			468		nC


### ※ Notes

- Repetitive rating : pulse width limited by junction temperature.
- $L = 100\text{mH}, I_{\text{AS}} = 1\text{A}, V_{\text{DD}} = 50\text{V}, R_G = 25\Omega, \text{Starting } T_J = 25^\circ\text{C}$
- $I_{\text{SD}} \leq 1\text{A}, \frac{dI}{dt} = 100\text{A/us}, V_{\text{DD}} \leq \text{BV}_{\text{DSS}}$ , Starting  $T_J = 25^\circ\text{C}$
- Pulse Test : Pulse Width  $\leq 300\text{us}$ , duty cycle  $\leq 2\%$ .
- Essentially independent of operating temperature.


**Fig. 1. On-state characteristics**




**Fig. 2. Transfer characteristics**




**Fig. 3. On-resistance variation vs. drain current and gate voltage**



**Fig. 4. On state current vs. diode forward voltage**



**Fig. 5. Breakdown Voltage Variation vs. Junction Temperature**



**Fig. 6. On resistance variation vs. junction temperature**




Fig. 7. Gate charge characteristics




Fig. 8. Capacitance Characteristics




Fig. 9. Maximum safe operating area(TO-252)




Fig. 10. Maximum safe operating area(SOT223)




Fig. 11. Transient thermal response curve(TO-252)




Fig. 12. Transient thermal response curve(SOT223)




Fig. 13. Gate charge test circuit & waveform




Fig. 14. Switching time test circuit & waveform




Fig. 15. Unclamped Inductive switching test circuit & waveform





Fig. 16. Peak diode recovery dv/dt test circuit & waveform



### DISCLAIMER

- \* All the data&curve in this document was tested in SEMIPOWER TESTING & APPLICATION CENTER.
- \* This product has passed the PCT,TC,HTRB,HTGB,HAST,PC and Solderdunk reliability testing.
- \* Qualification standards can also be found on the Web site (<http://www.semipower.com.cn>)
- \* Suggestions for improvement are appreciated, Please send your suggestions to [samwin@samwinsemi.com](mailto:samwin@samwinsemi.com)

# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for MOSFET category:***

***Click to view products by Sam&wing manufacturer:***

Other Similar products are found below :

[IRFD120](#) [JANTX2N5237](#) [2SK2267\(Q\)](#) [BUK455-60A/B](#) [TK100A10N1,S4X\(S](#) [MIC4420CM-TR](#) [VN1206L](#) [NDP4060](#) [SI4482DY](#)  
[IRS2092STRPBF-EL](#) [IPS70R2K0CEAKMA1](#) [TK31J60W5,S1VQ\(O](#) [TK31J60W,S1VQ\(O](#) [TK16J60W,S1VQ\(O](#) [2SK2614\(TE16L1,Q\)](#)  
[DMN1017UCP3-7](#) [EFC2J004NUZTDG](#) [P85W28HP2F-7071](#) [NTE2384](#) [DMC2700UDMQ-7](#) [DMN2080UCB4-7](#) [DMN61D9UWQ-13](#)  
[US6M2GTR](#) [DMN31D5UDJ-7](#) [DMP22D4UFO-7B](#) [IPS60R3K4CEAKMA1](#) [DMN1006UCA6-7](#) [DMN16M9UCA6-7](#) [STF5N65M6](#)  
[IRF40H233XTMA1](#) [STU5N65M6](#) [DMN6022SSD-13](#) [DMN13M9UCA6-7](#) [DMTH10H4M6SPS-13](#) [IPS60R360PFD7SAKMA1](#)  
[DMN2990UFB-7B](#) [SSM3K35CT,L3F](#) [IPLK60R1K0PFD7ATMA1](#) [2N7002W-G](#) [MCAC30N06Y-TP](#) [IPWS65R035CFD7AXKSA1](#)  
[MCQ7328-TP](#) [SSM3J143TU,LXHF](#) [DMN12M3UCA6-7](#) [PJMF280N65E1\\_T0\\_00201](#) [PJMF380N65E1\\_T0\\_00201](#)  
[PJMF280N60E1\\_T0\\_00201](#) [PJMF600N65E1\\_T0\\_00201](#) [PJMF900N65E1\\_T0\\_00201](#) [PJMF900N60E1\\_T0\\_00201](#)