


### Features

- High ruggedness
- Low  $R_{DS(ON)}$  (Typ 12mΩ)@ $V_{GS}=4.5V$   
(Typ 9.5mΩ)@ $V_{GS}=10V$
- Low Gate Charge (Typ 18nC)
- Improved dv/dt Capability
- 100% Avalanche Tested
- Application:Synchronous Rectification,  
Li Battery Protect Board, Inverter



4. Gate 5,6,7,8.Drain 1,2,3.Source

### General Description

This power MOSFET is produced with advanced technology of SAMWIN. This technology enable the power MOSFET to have better characteristics, including fast switching time, low on resistance, low gate charge and especially excellent avalanche characteristics.

### Order Codes

Item	Sales Type	Marking	Package	Packaging
1	SW K 083R06VSM	083R06VSM	SOP8	REEL

### Absolute maximum ratings


Symbol	Parameter	Value	Unit
$V_{DSS}$	Drain to source voltage	60	V
$I_D$	Continuous drain current (@ $T_a=25^\circ C$ )	10*	A
	Continuous drain current (@ $T_a=70^\circ C$ )	9*	A
$I_{DM}$	Drain current pulsed (note 1)	40	A
$V_{GS}$	Gate to source voltage	$\pm 20$	V
$E_{AS}$	Single pulsed avalanche energy (note 2)	95	mJ
$E_{AR}$	Repetitive avalanche energy (note 1)	9	mJ
dv/dt	Peak diode recovery dv/dt (note 3)	5	V/ns
$P_D$	Total power dissipation (@ $T_a=25^\circ C$ )	2.4	W
	Derating factor above 25°C	0.02	W/ $^\circ C$
$T_{STG}, T_J$	Operating junction temperature & storage temperature	-55 ~ + 150	$^\circ C$

\*. Drain current is limited by junction temperature.

### Thermal characteristics

Symbol	Parameter	Value	Unit
$R_{thja}$	Thermal resistance, Junction to ambient	52.4	$^\circ C/W$

Note:  $R_{thja}$  is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins.  $R_{thjc}$  is guaranteed by design while  $R_{thca}$  is determined by the user's board design.



SOP-8  $R_{thja}$  : 52.4 $^\circ C/W$  on a 1 in<sup>2</sup> pad of 2oz copper.

$BV_{DSS}$ : 60V $I_D$ : 10A $R_{DS(ON)}$ : 12mΩ@ $V_{GS}=4.5V$ 9.5mΩ@ $V_{GS}=10V$



Electrical characteristic (  $T_J = 25^\circ\text{C}$  unless otherwise specified )

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
<b>Off characteristics</b>						
$\text{BV}_{\text{DSS}}$	Drain to source breakdown voltage	$V_{\text{GS}}=0\text{V}$ , $I_D=250\mu\text{A}$	60			V
$\Delta \text{BV}_{\text{DSS}} / \Delta T_J$	Breakdown voltage temperature coefficient	$I_D=250\mu\text{A}$ , referenced to $25^\circ\text{C}$		0.03		$\text{V}/^\circ\text{C}$
$I_{\text{DSS}}$	Drain to source leakage current	$V_{\text{DS}}=60\text{V}$ , $V_{\text{GS}}=0\text{V}$		1		$\mu\text{A}$
		$V_{\text{DS}}=48\text{V}$ , $T_J=125^\circ\text{C}$		50		$\mu\text{A}$
$I_{\text{GSS}}$	Gate to source leakage current, forward	$V_{\text{GS}}=20\text{V}$ , $V_{\text{DS}}=0\text{V}$		100		nA
	Gate to source leakage current, reverse	$V_{\text{GS}}=-20\text{V}$ , $V_{\text{DS}}=0\text{V}$		-100		nA
<b>On characteristics</b>						
$V_{\text{GS(TH)}}$	Gate threshold voltage	$V_{\text{DS}}=V_{\text{GS}}$ , $I_D=250\mu\text{A}$	1.4		2	V
$R_{\text{DS(ON)}}$	Drain to source on state resistance	$V_{\text{GS}}=4.5\text{V}$ , $I_D=10\text{A}$ , $T_J=25^\circ\text{C}$		12	14.5	$\text{m}\Omega$
		$V_{\text{GS}}=10\text{V}$ , $I_D=10\text{A}$ , $T_J=25^\circ\text{C}$		9.5	11.5	$\text{m}\Omega$
		$V_{\text{GS}}=10\text{V}$ , $I_D=10\text{A}$ , $T_J=125^\circ\text{C}$		14		$\text{m}\Omega$
$G_{\text{fs}}$	Forward transconductance	$V_{\text{DS}}=5\text{V}$ , $I_D=10\text{A}$		32		S
<b>Dynamic characteristics</b>						
$C_{\text{iss}}$	Input capacitance	$V_{\text{GS}}=0\text{V}$ , $V_{\text{DS}}=30\text{V}$ , $f=1\text{MHz}$		1068		pF
$C_{\text{oss}}$	Output capacitance			354		
$C_{\text{rss}}$	Reverse transfer capacitance			13		
$t_{\text{d(on)}}$	Turn on delay time	$V_{\text{DS}}=30\text{V}$ , $I_D=10\text{A}$ , $R_G=4.7\Omega$ , $V_{\text{GS}}=10\text{V}$ (note 4,5)		5		ns
$t_r$	Rising time			34		
$t_{\text{d(off)}}$	Turn off delay time			24		
$t_f$	Fall time			8		
$Q_g$	Total gate charge	$V_{\text{DS}}=48\text{V}$ , $V_{\text{GS}}=10\text{V}$ , $I_D=10\text{A}$ , $I_G=3\text{mA}$ (note 4,5)		18		nC
$Q_{\text{gs}}$	Gate-source charge			2.2		
$Q_{\text{gd}}$	Gate-drain charge			4		
$R_g$	Gate resistance	$V_{\text{DS}}=0\text{V}$ , Scan F mode		1.8		$\Omega$


## Source to drain diode ratings characteristics

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$I_s$	Continuous source current	Integral reverse p-n Junction diode in the MOSFET			10	A
$I_{\text{SM}}$	Pulsed source current				40	A
$V_{\text{SD}}$	Diode forward voltage drop.	$I_s=10\text{A}$ , $V_{\text{GS}}=0\text{V}$			1.4	V
$t_{\text{rr}}$	Reverse recovery time	$I_s=10\text{A}$ , $V_{\text{GS}}=0\text{V}$ , $dI_F/dt=100\text{A}/\mu\text{s}$		29		ns
$Q_{\text{rr}}$	Reverse recovery charge			14		nC


## ※ Notes

- Repetitive rating : pulse width limited by junction temperature.
- $L = 0.5\text{mH}$ ,  $I_{\text{AS}} = 19.5\text{A}$ ,  $V_{\text{DD}} = 40\text{V}$ ,  $R_G = 25\Omega$ , Starting  $T_J = 25^\circ\text{C}$
- $I_{\text{SP}} \leq 10\text{A}$ ,  $di/dt = 100\text{A}/\mu\text{s}$ ,  $V_{\text{DD}} \leq \text{BV}_{\text{DSS}}$ , Starting  $T_J = 25^\circ\text{C}$
- Pulse Test : Pulse Width  $\leq 300\mu\text{s}$ , duty cycle  $\leq 2\%$ .
- Essentially independent of operating temperature.


**Fig. 1. On-state characteristics**




**Fig. 2. Transfer Characteristics**




**Fig. 3. On-resistance variation vs. drain current and gate voltage**




**Fig. 4. On-state current vs. diode forward voltage**




**Fig 5. Breakdown voltage variation vs. junction temperature**




**Fig. 6. On-resistance variation vs. junction temperature**




**Fig. 7. Gate charge characteristics**



**Fig. 8. Capacitance Characteristics**



**Fig. 9. Maximum safe operating area**



**Fig. 10. Transient thermal response curve**




Fig. 11. Gate charge test circuit & waveform




Fig. 12. Switching time test circuit & waveform





Fig. 13. Unclamped Inductive switching test circuit & waveform






Fig. 14. Peak diode recovery dv/dt test circuit & waveform



## DISCLAIMER

- \* All the data & curve in this document was tested in SEMIPOWER TESTING & APPLICATION CENTER.
- \* This product has passed the PCT, TC, HTRB, HTGB, HAST, PC and Solderdunk reliability testing.
- \* Qualification standards can also be found on the Web site (<http://www.semipower.com.cn>)
- \* Suggestions for improvement are appreciated, Please send your suggestions to [samwin@samwinsemi.com](mailto:samwin@samwinsemi.com)

# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for MOSFET category:***

***Click to view products by Sam&wing manufacturer:***

Other Similar products are found below :

[IRFD120](#) [JANTX2N5237](#) [2SK2267\(Q\)](#) [BUK455-60A/B](#) [TK100A10N1,S4X\(S](#) [MIC4420CM-TR](#) [VN1206L](#) [NDP4060](#) [SI4482DY](#)  
[IRS2092STRPBF-EL](#) [IPS70R2K0CEAKMA1](#) [TK31J60W5,S1VQ\(O](#) [TK31J60W,S1VQ\(O](#) [TK16J60W,S1VQ\(O](#) [2SK2614\(TE16L1,Q\)](#)  
[DMN1017UCP3-7](#) [EFC2J004NUZTDG](#) [P85W28HP2F-7071](#) [NTE2384](#) [DMC2700UDMQ-7](#) [DMN2080UCB4-7](#) [DMN61D9UWQ-13](#)  
[US6M2GTR](#) [DMN31D5UDJ-7](#) [DMP22D4UFO-7B](#) [IPS60R3K4CEAKMA1](#) [DMN1006UCA6-7](#) [DMN16M9UCA6-7](#) [STF5N65M6](#)  
[IRF40H233XTMA1](#) [STU5N65M6](#) [DMN6022SSD-13](#) [DMN13M9UCA6-7](#) [DMTH10H4M6SPS-13](#) [IPS60R360PFD7SAKMA1](#)  
[DMN2990UFB-7B](#) [SSM3K35CT,L3F](#) [IPLK60R1K0PFD7ATMA1](#) [2N7002W-G](#) [MCAC30N06Y-TP](#) [IPWS65R035CFD7AXKSA1](#)  
[MCQ7328-TP](#) [SSM3J143TU,LXHF](#) [DMN12M3UCA6-7](#) [PJMF280N65E1\\_T0\\_00201](#) [PJMF380N65E1\\_T0\\_00201](#)  
[PJMF280N60E1\\_T0\\_00201](#) [PJMF600N65E1\\_T0\\_00201](#) [PJMF900N65E1\\_T0\\_00201](#) [PJMF900N60E1\\_T0\\_00201](#)