


# Power Cord with Locking System for Inlet Filters IL13, IL13P, IL19



- Locking system for standardized IEC C14/C20 inlet filter
- No accidental disconnection
- Rated current up to 10 A (C13 plug), up to 15 A (C13P plug), and up to 20 A (C19 plug)
- Fits any Schaffner IEC C14/C20 inlet filter
- Retrofit for any IEC C14/C20 inlet
- Various power line plugs for international usage



## Approvals & Compliances



The locking system has a tensile force of typical 200N. It is recommended to use it with flange mount filters. For details refer to our Application Note "Using IEC Lock Power Cords with IEC Inlets and Filters"

Schaffner power cords with IEC lock guard against accidental disconnection of all electrical appliances with an IEC inlet. No exchange or modification of the IEC inlet or IEC inlet filter system is needed. Easy retrofit for all electronic equipments and devices.

## Features and Benefits

- Power cord with locking system for IEC inlets
- Protection class I (IL13, IL13P)
- Suitable for use with any C14 IEC inlet (IL13, IL13P) and C20 IEC inlet (IL19)
- Fits the complete Schaffner IEC inlet filter program with C14 IEC inlet and C20 IEC inlet (IL19)
- Max. pin temperature 70°C
- New DUAL locking cord

## Typical Applications

- Data centers
- Industrial equipment
- Medical devices
- In-vitro diagnostic devices
- Broadcasting stations
- Mobile applications

## Technical Specifications IL13 / IL13P

Maximum continuous operating voltage	250 VAC, 50/60 Hz
Rated currents	10 A for C13 plug, 15 A for C13P plug
High potential test voltage	P-> PE 2000 VAC (1 min 50 Hz) P-> N 2000 VAC (1 min 50 Hz)
Protection category	IP 20 according IEC 60529
Temperature range (operation and storage)	-25°C to +70°C
Connector (load side)	IEC C13 according to IEC/EN 60320-2-2 with IEC Lock UL 498, CSA C22.2 no. 42 (for cold conditions) pin temp. 70°C, up to 15 A, Protection Class I
Connector (line side) and cables	Please refer to table on page 2 and 3
Flammability corresponding to	Plugs: UL 94 V-2 or better; Cable: IEC 60332-1 Cat. F2

## Technical Specifications IL19

Maximum continuous operating voltage	250 VAC, 50/60 Hz
Rated currents	16 A (IEC), 20 A (UL)
Operating frequency	50 to 400 Hz
High potential test voltage	P-> PE 2000 VAC (1 min 50 Hz) P-> N 2000 VAC (1 min 50 Hz)
Protection category	IP 20 according IEC 60529
Temperature range (operation and storage)	-25°C to +70°C
Connector (load side)	IEC C19 according to IEC/EN 60320-2-2 with IEC lock, UL 498, CSA C22.2 no. 42 (for cold conditions) pin temp. 70°C, up to 20 A, Protection Class I
Connector (line side) and cables	please refer to table on page 4
Flammability corresponding to	Plugs: UL 94 V-2 or better; Cable: IEC 60332-1 Cat. F2

### Cable Selection Table IL13

<b>IL13-C14-H05-3100-X*</b>	IEC cable assembly with locking system for IEC C14 inlet, EU version
<b>IL13-C14-SVT-3100-X*</b>	IEC cable assembly with locking system for IEC C14 inlet, US version
<b>IL13-CH1-H05-3100-X*</b>	IEC cable assembly with locking system for IEC C14 inlet, CH version
<b>IL13-EU1-H05-3100-X*</b>	IEC cable assembly with locking system for IEC C14 inlet, EU version
<b>IL13-JP1-HVCTF-3125-X*</b>	IEC cable assembly with locking system for IEC C14 inlet, JP version
<b>IL13-SE-H05-3100-X*</b>	IEC cable assembly with locking system for IEC C14 inlet, stripped ends
<b>IL13-UK1-H05-3100-X*</b>	IEC cable assembly with locking system for IEC C14 inlet, UK version
<b>IL13-US1-SVT-3100-X*</b>	IEC cable assembly with locking system for IEC C14 inlet, US version
<b>IL13-US2-SJT-3100-X*</b>	IEC cable assembly with locking system for IEC C14 inlet, US version, hospital grade

To compile a complete part number, please replace the X\* with the required length (please refer to table below for available length per cable type):  
 - X\* options = 200, 300, 400, 500 or 1000 cm; 183, 275 or 366 cm (6, 9 or 12 feet)

### Available Combinations IL13

To compile a complete part number exchange the letters (IL13-yyy-zzz-aaaa-bbb-c) with the data from the table below.

Load side IL13		Line side plug		Cable type		Cable core		Rating	Cable length*		Cable color		Cert.
IL13		yyy		zzz		aaaa			bbb		c		
IL13	IEC C13 Female plug, straight, lock	C14 AU1 CH1 EU1 EU2 IT1 IL1 KC1 SA1 SE UK1 UK2	IEC C14, male, straight	H05VV-F	H05	3x1.00mm <sup>2</sup>	3100	250VAC 10A	6 feet	183	Black Blue Orange Red White	- B O R W	CB KC KEMA SAA
			Australian plug 3 pins						200 cm	200			
			SEV1011, straight						9 feet	275			
			CEE 7/VI, right angled						300 cm	300			
			CEE 7/VI, straight						12 feet	366			
			Italian Plug						400 cm	400			
			Israel Plug						500 cm	500			
			Korean Plug						1000 cm	1000			
			South African Plug										
			Stripped Ends										
			BS1363, right angled fused 5A										
			BS1363, right angled fused 10A										
			IL13						IEC C13 Female plug, straight, lock	C14 JP1 SE			
Japanese Plug JIS C8303 insulated sleeves	200 cm	200											
Stripped Ends	300 cm	300											
	400 cm	400											
	500 cm	500											
IL13	IEC C13 Female plug, straight, lock	C14 SE US1 US2	IEC C14, male, straight	SJT SVT	SJT SVT	AWG 18 AWG 16 AWG 14	3100 3130 3160	125VAC 10A 13A 15A	6 feet	183	Black Blue Orange Red White	- B O R W	UL cUL
			Stripped Ends						200 cm	200			
			NEMA5-15, straight						9 feet	275			
			NEMA5-15, straight, hospital grade						300 cm	300			
									12 feet	366			
									400 cm	400			
	500 cm	500											
	1000 cm	1000											
IL13	IEC C13 Female plug, straight, lock	C14 CN1 SE	IEC C14, male, straight Chinese plug Stripped Ends	RVV	RVV	3x1.00mm <sup>2</sup>	3100	250VAC 10A	200 cm	200	Black Blue Orange Red White	- B O R W	CCC
IL13	IEC C13 Female plug, straight, lock	C14 IN1 SE	IEC C14, male, straight Indian plug 3 Pin Stripped Ends	BIS 694 1000V	BIS694	3x1.00mm <sup>2</sup>	3100	250VAC 10A	200 cm	200	Black Blue Orange Red White	- B O R W	CB

\*feet values are calculated to the matching length in cm

### Cable Selection Table IL13P

<b>IL13P-C14-H05-3100-X*</b>	IEC cable assembly with locking system + for IEC C14 inlet, EU version
<b>IL13P-CH1-H05-3100-X*</b>	IEC cable assembly with locking system + for IEC C14 inlet, CH version
<b>IL13P-EU1-H05-3100-X*</b>	IEC cable assembly with locking system + for IEC C14 inlet, EU version
<b>IL13P-JP1-HVCTF-3125-X*</b>	IEC cable assembly with locking system + for IEC C14 inlet, JP version
<b>IL13P-SE-H05-3100-X*</b>	IEC cable assembly with locking system + for IEC C14 inlet, stripped ends
<b>IL13P-UK1-H05-3100-X*</b>	IEC cable assembly with locking system + for IEC C14 inlet, UK version
<b>IL13P-US1-SJT-3160-X*</b>	IEC cable assembly with locking system + for IEC C14 inlet, US version
<b>IL13P-S-C14-UC-3100-X*</b>	IEC SLIMLINE cable assembly with locking system + for IEC C14 inlet

To compile a complete part number, please replace the X\* with the required length (please refer to table below for available length per cable type):  
 - X\* options = 200, 300, 400, 500 or 1000 cm; 183, 275 or 366 cm (6, 9 or 12 feet)

### Available Combinations IL13P

To compile a complete part number exchange the letters (IL13P-yyy-zzz-aaa-bbb-c) with the data from the table below.

Load side IL13P		Line side plug	Cable type	Cable core	Rating	Cable length*		Cable color	Cert.																													
IL13P		yyy	zzz	aaaa		bbb	c																															
IL13P	IEC C13 + Female plug, straight, lock	IEC C14, male, straight	C14	H05VV-F	H05	3x1.00mm <sup>2</sup>	3100	250VAC	10A	6 feet	183	Black	-	CB																								
		Australian plug 3 pins	AU1												200 cm	200	Blue	B																				
		SEV1011, straight	CH1																9 feet	275	Orange	O																
		CEE 7/VII, right angled	EU1																				300 cm	300	Red	R												
		CEE 7/VII, straight	EU2																								12 feet	366	White	W								
		Italian Plug	IT1																												400 cm	400	KEMA	SAA				
		Israel Plug	IL1																																500 cm	500		
		Korean Plug	KC1																																		1000 cm	1000
		South African Plug	SA1																																			
		Stripped Ends	SE																																			
		BS1363, right angled fused 5A	UK1																																			
		BS1363, right angled fused 10A	UK2																																			
IL13P	IEC C13 + Female plug, straight, lock	IEC C14, male, straight	C14	HVCTF	HVCTF	3x1.25mm <sup>2</sup>	3125	125VAC	12A	100 cm	100	Black	-	PSE																								
		Japanese Plug JIS C8303 insulated sleeves	C14												3x2.00mm <sup>2</sup>	3200	15A	200 cm																				
		Stripped Ends	JP1																300 cm	300	Orange	O																
			SE																				400 cm	400	Red	R												
		500 cm	500	White	W																																	
IL13P	IEC C13 + Female plug, straight, lock					IEC C14, male, straight	C14	SJT	SJT	AWG 18	3100	125VAC	10A	6 feet	183	Black	-	UL																				
						Stripped Ends	SE												SJT	SVT	AWG 16	3130					13A	9 feet	275	Blue	B							
						NEMA5-15, straight	US1																AWG 14	3160	15A	300 cm						300	Orange	O				
		NEMA5-15, straight, hospital grade	US2	400 cm	400	Red	R																															
																																			500 cm	500	White	W
IL13P	IEC C13 + Female plug, straight, lock	IEC C14, male, straight	C14					RVV	RVV	3x1.00mm <sup>2</sup>	3100	250VAC	10A	200 cm	200	Black	-	CCC																				
		Chinese plug	CN1																200 cm	200	Blue	B																
		Stripped Ends	SE	Orange	O																																	
						Red	R																															
IL13P	IEC C13 + Female plug, straight, lock	IEC C14, male, straight	C14					BIS 694	BIS694	3x1.00mm <sup>2</sup>	3100	250VAC	10A	200 cm	200	Black	-	CB																				
		Indian plug 3 Pin	IN1																200 cm	200	Blue	B																
		Stripped Ends	SE	Orange	O																																	
						Red	R																															
		White	W																																			
IL13P-S	IEC C13 + DUAL Locking Female plug, straight, lock							IEC C14 dual locking, male, straight	C14	H05VV-F	UC	3x1.00mm <sup>2</sup>	3100	250VAC	10A	50 cm	50	Black	-	ENEC																		
								100 cm	100							Blue	B																					
						150 cm	150	Red	R																													
				200 cm	200	White	W																															
				250 cm	250																																	
		300 cm	300																																			

\*feet values are calculated to the matching length in cm

### New DUAL Locking Version IL13P-S



Locking functionality on both ends of the cord

### Cable Selection Table IL19

<b>IL19-C20-H05-3150-X*</b>	IEC cable assembly with locking system for IEC C20 inlet, EU version
<b>IL19-C20-SJT-3160-X*</b>	IEC cable assembly with locking system for IEC C20 inlet, US version
<b>IL19-EU1-H05-3150-X*</b>	IEC cable assembly with locking system for IEC C20 inlet, EU version
<b>IL19-SE-H05-3150-X*</b>	IEC cable assembly with locking system for IEC C20 inlet, stripped ends
<b>IL19-UK1-H05-3150-X*</b>	IEC cable assembly with locking system for IEC C20 inlet, UK version
<b>IL19-US1-SJT-3160-X*</b>	IEC cable assembly with locking system for IEC C20 inlet, US version

To compile a complete part number, please replace the X\* with the required length (please refer to table below for available length per cable type):

- X\* options = 200, 300, 400, 500 or 1000 cm; 183, 275 or 366 cm (6, 9 or 12 feet)

### Available Combinations IL19

To compile a complete part number exchange the letters (IL19-yyy-zzz-aaaa-bbb-c) with the data from the table below.

Load side IL19		Line side plug	Cable type		Cable core		Rating*	Cable length**		Cable color		Cert.		
IL19		yyy	zzz		aaaa		bbb	c						
IL19	IEC C19 Female plug, straight, lock	IEC C20, male, straight	C20	H05VV-F	H05	3x1.50mm <sup>2</sup>	3150	16A	6 feet	183	Black Blue Orange Red White	- B O R W	CB KEMA SAA	
		Australian plug 3 pins	AU1					15A	200 cm	200				
		SEV1011, straight	CH1					16A	9 feet	275				
		CEE 7/VII, right angled or straight	EU1					16A	300 cm	300				
		Italian Plug	IT1					16A	12 feet	366				
		South Africa plug	SA1					16A	400 cm	400				
		Stripped Ends	SE					16A	500 cm	500				
		BS1363, right angled fused 13A	UK1					13A	1000 cm	1000				
IL19	IEC C19 Female plug, straight, lock	IEC C20, male, straight	C20	HVCTF	HVCTF	3x2.00mm <sup>2</sup>	3200	15A	100 cm	100	Black Blue Orange Red White	- B O R W	PSE	
		Japanese Plug JIS C8303 insulated sleeves	JP1						200 cm	200				
		Stripped Ends	SE						300 cm	300				
									400 cm	400				
									500 cm	500				
IL19	IEC C19 Female plug, straight, lock	IEC C20, male, straight	C20	SJT	SJT	AWG14	3160	125V	6 feet	183	Black Blue Orange Red White	- B O R W	UL cUL	
		Stripped Ends	SE						200 cm	200				
		NEMAS-15, straight	US1						9 feet	275				
		Nema 5-20P	US4						15A	300 cm				300
									20A	12 feet				366
										400 cm				400
			500 cm	500										
			1000 cm	1000										
IL19	IEC C19 Female plug, straight, lock	Chinese plug	CN1	RVVF	RVVF	3x1.50mm <sup>2</sup>	3150	16A	200 cm	200	black	-	CCC	

\* if not separately mentioned 250VAC is rated voltage

\*\* feet values are calculated to the matching length in cm

## Headquarters, Global Innovation and Development

### Switzerland

#### Schaffner Group

Industrie Nord  
Nordstrasse 11e  
4542  
Luterbach  
+41 32 681 66 26  
[info@schaffner.com](mailto:info@schaffner.com)

## Sales and Application Centers

### China

#### Schaffner EMC Ltd. Shanghai

T20-3 C No 565 Chuangye Road Pudong  
district  
201201  
Shanghai  
+86 2138139500  
[cschina@schaffner.com](mailto:cschina@schaffner.com)

### Finland

#### Schaffner Oy

Sauvonrinne 19 H  
8500  
Lohja  
+358 50 468 7284  
[finlandsales@schaffner.com](mailto:finlandsales@schaffner.com)

### France

#### Schaffner EMC S.A.S.

16-20 Rue Louis Rameau  
95875  
Bezons  
+33 1 34 34 30 60  
[francesales@schaffner.com](mailto:francesales@schaffner.com)

### Germany

#### Schaffner Deutschland GmbH

Schoemperlenstrasse 12B  
76185  
Karlsruhe  
+49 721 56910  
[germanysales@schaffner.com](mailto:germanysales@schaffner.com)

### India

#### Schaffner India Pvt. Ltd

Regus World Trade Centre  
WTC 22nd Floor Unit No 2238 Brigade  
Gateway Campus 26/1 Dr. Rajkumar Road  
Malleshwaram (W)  
560055  
Bangalore  
+91 8067935355  
[indiasales@schaffner.com](mailto:indiasales@schaffner.com)

### Italy

#### Schaffner EMC S.r.l.

Via Ticino, 30  
20900  
Monza (MB)  
+39 039 21 41 070  
[italysales@schaffner.com](mailto:italysales@schaffner.com)

### Japan

#### Schaffner EMC K.K.

ISM Sangenjaya 7F  
1-32-12 Kamiyama Setagaya-ku  
154-0011  
Tokyo  
+81 3 5712 3650  
[japansales@schaffner.com](mailto:japansales@schaffner.com)

### Singapore

#### Schaffner EMC Pte Ltd.

Blk 3015A Ubi Road 1 #05-09 Kampong Ubi  
Industrial Estate  
408705  
Singapore  
+65 63773283  
[singaporesales@schaffner.com](mailto:singaporesales@schaffner.com)

### Spain

#### Schaffner EMC España

Calle Caléndula 93 Miniparc III Edificio E El  
Soto de Moraleja Alcobendas  
28109  
Madrid  
+34 917 912 900  
[spainsales@schaffner.com](mailto:spainsales@schaffner.com)

### Sweden

#### Schaffner EMC AB

Östermalmstrorg 1  
114 42  
Stockholm  
+46 8 5050 2425  
[swedensales@schaffner.com](mailto:swedensales@schaffner.com)

### Switzerland

#### Schaffner EMV AG

Industrie Nord  
Nordstrasse 11e  
4542  
Luterbach  
+41 32 681 66 26  
[switzerlandsales@schaffner.com](mailto:switzerlandsales@schaffner.com)

### Taiwan

#### Schaffner EMV Ltd.

U-Town  
20 Floor-2 No 97 Section 1 XinTai 5th Road  
XiZhi District  
22175  
New Taipei City  
+886 226975500  
[taiwansales@schaffner.com](mailto:taiwansales@schaffner.com)

### Thailand

#### Schaffner EMC Co. Ltd.

Sathorn Square Tower  
Room 3780 37FL 98 North-Sathorn Rd Silom  
Bangrak  
10500  
Bangkok  
+66 621056397  
[thailandsales@schaffner.com](mailto:thailandsales@schaffner.com)

### United Kingdom

#### Schaffner Ltd.

Suite 1 Oakmede Place  
Terrace Road  
RG42 4JF  
Binfield  
+44 118 9770070  
[uksales@schaffner.com](mailto:uksales@schaffner.com)

### United States

#### Schaffner EMC Inc.

52 Mayfield Avenue  
Edison, New Jersey  
+1 732 225 9533  
[usasales@schaffner.com](mailto:usasales@schaffner.com)

To find your local partner within  
Schaffner's global network [schaffner.com](http://schaffner.com)

© 2022 Schaffner Group

The content of this document has been carefully checked and understood. However, neither Schaffner nor its subsidiaries assume any liability whatsoever for any errors or inaccuracies of this document and the consequences thereof. Published specifications are subject to change without notice. Product suitability for any area of application must ultimately be determined by the customer. In all cases, products must never be operated outside their published specifications. Schaffner does not guarantee the availability of all published products. This disclaimer shall be governed by substantive Swiss law and resulting disputes shall be settled by the courts at the place of business of Schaffner Holding AG. Latest publications and a complete disclaimer can be downloaded from the Schaffner website. All trademarks recognized.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [AC Power Leads](#) category:*

*Click to view products by [Schaffner](#) manufacturer:*

Other Similar products are found below :

[YP-61+YC12](#) [YP21A+YC13](#) [6601](#) [FTP-629Y603](#) [1700001947](#) [IL13-EU1-H05-3100-300-S](#) [2217913-1](#) [P28976-M45](#) [BB-3271V86](#) [P29844-M5](#) [P29844-M10](#) [P28818-M6](#) [387005324](#) [387005325](#) [59903000000](#) [387007040](#) [IL13P-EU1-H05-3100-300](#) [PCAK2](#) [EM9169](#) [32004](#) [32002](#) [W-98979](#) [W-98980](#) [W-98983](#) [W-98987](#) [W-99183](#) [AM TO TYPE-C-0.3M](#) [HC-3C1.5MM-Z-P](#) [HC-CE1.2MM-W-K](#) [AK-RD-07A](#) [LPS275](#) [18049236](#) [LA0055](#) [HC-3C1.5MM-W-P](#) [NUFPWC-03PMMS-LC500](#) [NUF-MSAP-08BMMM-RJ](#) [BEST 053](#) [W-99469](#) [W2243](#) [W-99945](#) [W-99764](#) [W-98642](#) [W-98643](#) [W-99440](#) [W-97783](#) [W-99175](#) [W-97760](#) [W-99243](#) [M02411](#) [W-98692](#)