

Spring plunger

FSTIm M5-IG M5-IG A 20 VG-IN

Part no.:10.01.02.01483

<https://www.schmalz.com/10.01.02.01483>

Homepage > Vacuum Technology for Automation > Vacuum Components > Mounting Elements > Spring plunger > Spring Plungers FSTIm >


FSTIm M5-IG M5-IG A 20 VG-IN

Spring plunger with internal damping spring and height compensation



Suction cup connection: M5-F
 Vacuum connection: M5-F
 Shape: n.d.
 Spring stroke Z: 20 mm
 Shape: rotation lock/insulating

Design Data



Attribute	Value
dn	2 mm
G1	M5-IG
G2	M5-F
G3	M10x1-M
H	79.4 mm
H2	29 mm
LG1	4.5 mm
LG2	4.5 mm
LG3	41 mm
SW1	14 mm
SW2	8 mm
Z (Stroke)	20 mm

Spring plunger

FSTIm M5-IG M5-IG A 20 VG-IN

Part no.:10.01.02.01483

<https://www.schmalz.com/10.01.02.01483>




Technical Data

Attribute	Value
Spring rate	0.052 N/mm
Spring pretension	0.5 N
Spring force, center	1.02 N
Vertical load	15 N
Horizontal load	10 N
Weight	23.5 g
Operating temperature	0 ... 80 °C

Note: Spring force: Referred to 50 % of operating stroke Vertical load: Maximum static loading
Horizontal load: The specification of the horizontal load refers to the lower edge of the plunger with extended spring. It is a maximum static stress and it impairs the spring compression and extension in horizontal position.

Accessories



VSL 6-4 PU SO

Part no.10.07.09.00141

Hose for vacuum and compressed-air systems

External diameter D: 6 mm

Internal diameter d: 4 mm

Length (max): 50 m

Material: PU

Installation radius (min): 15 mm

Colour: blue

Pressure range (operating pressure):

-0.84 ... 6.00 bar

Ambient temperature: -25 ... 60 °C

SO: Hose in soft design

Spring plunger

FSTIm M5-IG M5-IG A 20 VG-IN

Part no.:10.01.02.01483

<https://www.schmalz.com/10.01.02.01483>



ST M5-AG 4 MS-V

Part no.10.08.03.00311


Hose sleeve

Thread G1: M5-M

Internal hose diameter: 4 mm

Material: Brass

Surface: nickel plated



HTR-STA 47 1N D10/16 FL

Part no.10.08.03.00085

Holder for flexible mounting of suction cups/spring plungers on sections


Length L: 47 mm

Cross-beam connection: Sliding block

Suction cup or spring plunger conn.:

Contour D10 and D16

Shape: flat



HTR-ST5 30x30 D10/16 WI

Part no.10.08.03.00088

Holder for flexible mounting of suction cups/spring plungers on square tubes

Cross-beam connection: 30x30

Suction cup or spring plunger conn.:

Contour D10 and D16

Shape: angled

Spring plunger

FSTIm M5-IG M5-IG A 20 VG-IN

Part no.:10.01.02.01483

<https://www.schmalz.com/10.01.02.01483>



HTR-ST5 40x40 D10/16 WI

Part no.10.08.03.00089

Holder for flexible mounting of suction cups/spring plungers on square tubes

Cross-beam connection: 40x40

Suction cup or spring plunger conn.:

Contour D10 and D16

Shape: angled

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Bench Top Tools](#) category:

Click to view products by [SCHMALZ](#) manufacturer:

Other Similar products are found below :

[0027](#) [6104-201-2102](#) [6104-201-2502](#) [6-1372442-6](#) [62500-1584](#) [63801-7252](#) [63801-7269](#) [69002-5525](#) [691667-1](#) [768539-1](#) [854130-1](#)
[854946-2](#) [856203-1](#) [904449-1](#) [9-22280-9](#) [986096-2](#) [992438-3](#) [1-21000-3](#) [1-21000-4](#) [1-21000-1](#) [1-25022-4](#) [1302263353](#) [1424264-1](#)
[1424267-1](#) [1428211-1](#) [1-455755-6](#) [1752324-1](#) [1752744-1](#) [18023-9](#) [189763-1](#) [1901726-1](#) [1954222-1](#) [2079747-1](#) [21001-2](#) [2119083-1](#)
[2119085-1](#) [2119371-1](#) [2161362-2](#) [2161930-1](#) [2217088-2](#) [2217339-1](#) [2217347-1](#) [22281-9](#) [22374-7](#) [240825-4](#) [992342-2](#) [2030790-2](#) [2063796-1](#) [2063799-2](#) [2119092-1](#)