



Main

| | |
|------------------------------|-------------------------------------|
| Product range | 8501K |
| Product type | Relay |
| Relay Type | General purpose |
| Mounting type | Socket |
| Contact composition | 3PDT |
| [Uc] control circuit voltage | 120 V AC |
| Pilot light | Indicator light relay energised LED |
| Manual operator | Without test button |

Complementary

| | |
|---------------------------|---|
| Horsepower rating | 0.33 Hp 120 V AC 0.5 hp 240 V AC |
| Breaking capacity | 3 A 120 V AC inductive control circuit UL 508 1.5 A 240 V AC inductive control circuit UL 508 10 A 28 V DC resistive control circuit UL 508 10 A 120 V AC resistive control circuit UL 508 6.66 A 240 V AC resistive control circuit UL 508 |
| Maximum switching voltage | 300 V AC 30 V DC |
| Contact material | Silver tin oxide |
| Operating time | 12 ms - pick-up 12 ms - drop-out |
| Shape of pins | Tubular |
| For use with | 8501NR61 8501NR62 |

Environment

| | |
|---|---|
| Ambient temperature range - operational | -40...113 °F (-40...45 °C) |
| Product certifications | CSA UL Listed CE UL Recognized |
| Height | 2.66 in (67.56 mm) |
| Width | 1.39 in (35.31 mm) |
| Depth | 1.39 in (35.31 mm) |

Ordering and shipping details

| | |
|---------------------|--------------------|
| Category | 21141-8501 KP |
| Discount Schedule | CP2 |
| GTIN | 00785901480525 |
| Package weight(Lbs) | 3.36 oz (95.254 g) |
| Returnability | No |
| Country of origin | CN |

Packing Units

| | |
|------------------|--------------------|
| Package 1 Height | 1.70 in (4.318 cm) |
| Package 1 width | 1.70 in (4.318 cm) |
| Package 1 Length | 2.90 in (7.366 cm) |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [General Purpose Relays](#) category:

Click to view products by [Schneider](#) manufacturer:

Other Similar products are found below :

[PCN-105D3MH,000](#) [59641F200](#) [LY1SAC110120](#) [5X827E](#) [5X837F](#) [5X840F](#) [5X842F](#) [5X848E](#) [LY2N-AC120](#) [LY2S-AC220/240](#) [LY2-US-AC120](#) [LY3-US-AC120](#) [LY4F-UA-DC12](#) [LY4F-UA-DC24](#) [LY4F-US-AC120](#) [LY4F-US-AC240](#) [LY4F-US-DC24](#) [LY4F-VD-AC110](#) [LYQ20DC12](#) [M115C60](#) [M115N010](#) [M115N0150](#) [6031007G](#) [603-12D](#) [61211T0B4](#) [61212T400](#) [61222Q400](#) [61243B600](#) [61243C500](#) [61243Q400](#) [61311BOA2](#) [61311BOA6](#) [61311BOA8](#) [61311C0A2](#) [61311COA1](#) [61311COA6](#) [61311F0A2](#) [61311QOA1](#) [61311QOA4](#) [61311T0D6](#) [61311TOA6](#) [61311TOA7](#) [61311TOB3](#) [61311TOB4](#) [61311U0A6](#) [61312Q600](#) [61312T400](#) [61312T600](#) [61313U200](#) [61313U400](#)