## Product data sheet Characteristics

# 9001KM38 30MM LIGHT MODULE RESISTOR 120V

Product availability: Stock - Normally stocked in distribution facility



| Main                      |                                 |
|---------------------------|---------------------------------|
| Range of product          | Harmony 9001SK<br>Harmony 9001K |
| Product or component type | Light block                     |
| Device short name         | 9001K                           |
| Bulb base                 | BA 9s                           |
| Light block supply        | Direct via integral resistance  |

#### Complementary

| Product weight            | 0.11 lb(US) (0.05 kg) |
|---------------------------|-----------------------|
| Light source              | Incandescent          |
| [Us] rated supply voltage | 120 V AC/DC           |

#### Environment

| Protective treatment                  | TC   |  |
|---------------------------------------|--|--|
| Ambient air temperature for storage   | -40158 °F (-4070 °C)   |  |
| Ambient air temperature for operation | -13158 °F (-2570 °C)   |  |
| IP degree of protection               | IP20 conforming to IEC 60529   |  |
| Standards                             | UL 508 EN/IEC 60947-1 CSA C22.2 No 14 JIS C 4520 JIS C 852 EN/IEC 60947-5-1 EN/IEC 60947-5-4 |  |
| Product certifications                | UL 508<br>NEMA   |  |
| Electrical shock protection class     | Class II conforming to IEC 61140   |  |
| Vibration resistance                  | 7 gn (f = 2500 Hz) conforming to IEC 60068-2-6   |  |
| Shock resistance                      | 50 gn conforming to IEC 60068-2-27   |  |

#### Ordering and shipping details

| Category              | 21435 - 9001 KM LIGHT MODULES |  |
|-----------------------|-------------------------------|--|
| Discount Schedule     | CS1                           |  |
| GTIN                  | 00785901726623                |  |
| Nbr. of units in pkg. | 1                             |  |
| Package weight(Lbs)   | 0.1400000000000001            |  |
| Returnability         | Υ                             |  |
| Country of origin     | MX                            |  |

### Offer Sustainability

| RoHS (date code: YYWW)    | Compliant - since 0921 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity               |
|---------------------------|--|
| REACh                     | Reference not containing SVHC above the threshold  |
| California proposition 65 | WARNING: This product can expose you to chemicals including:   |
| Substance 1               | Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. |
| More information          | For more information go to www.p65warnings.ca.gov  |


#### Contractual warranty

| Warranty period | 18 months |
|-----------------|-----------|
|                 |           |

# Product data sheet Dimensions Drawings

# 9001KM38

#### **Dimensions**



e panel thickness: 1 to 6 mm / 0.04 to 0.24 in.

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Switch Fixings category:

Click to view products by Schneider manufacturer:

Other Similar products are found below:

893102000 00-5150 LZZ1A 0098.9234 M2PA-5011 630155 635401 6PA113 6PA147-E6 6PA148-E6 6PA32 6PA9 700109 700303A56

700C1GRY 700C2GRN 704-6001 704.960.4 704.960.9 704.965.2 704.965.6 704.966.0 7089-3 710082-B11 71M1048 757200264

764300000 MHU35 MHU37 807039-1 825.003.011 825.005.011 825.053.011 825.055.011 826.000.071 827.020.011 827.400.021

835.900.023 MML52C10C MML52E10C MML92HGH MML93K 84211M02CNNS 84212M02CNNS 84217A8.0LNOS 842.500.011

843.000.011 843187-000 843487-000 84-901