## Product data sheet Characteristics

# 9007CB33S1 SNAP SWITCH - 600 V - 10 AMP - CB + OPTIONS



Product availability: Stock - Normally stocked in distribution facility



Main	
Range of product	9007
Series name	Heavy duty
Product or component type	Snap limit switch
Device short name	9007AO/CO
Body type	Fixed

C	_   _		4.	
Com	one	me	TIT!	arv
00111	$\sim$		,,,,,,,	<b>ч</b> . у

Mounting mode	-
Operator profile	Plunger head
Material	Metal
Body material	Cast zinc
Operator material	Cast zinc
Fixing mode	By the body
Movement of operating head	Linear
Type of operator	Metal spring return roller lever plunger LH bracket + 0.47" roller
Switch actuation	By 30° cam
Type of approach	2 directions traverse approach
Electrical connection	12 cables 6 binder head screw terminals (AWG 22AWG 14)
Number of poles	2
Contacts type and composition	2(NC-NO), switch function: DPDT-DB
Contact form	Form ZZ
Contact operation	Snap action
Number of steps	1
Contacts material	Silver contacts
Positive opening	Without
Terminals description ISO n°1	(1-2)NC (3-4)NO (5-6)NC (7-8)NO
Minimum force for tripping	0.5 lbf
Maximum force for tripping	0.5 lbf
[le] rated operational current	0.1 A at 250 V DC 0.75 A at 480 V AC, B600 conforming to NEMA rating designation 1.5 A at 240 V AC, B600 conforming to NEMA rating designation 3 A at 120 V AC, B600 conforming to NEMA rating designation 0.2 A at 125 V DC 0.6 A at 600 V AC, B600 conforming to NEMA rating designation
[Ithe] conventional enclosed thermal current	10 A
[Ui] rated insulation voltage	600 V - for contact block (degree of pollution: 3) conforming to UL 508 600 V - for contact block conforming to CSA C22.2 No 14
Width	0.95 in
Height	2.5 in

Depth	2.54 in	
Product weight	1.5 lb(US)	

#### Environment

NEMA degree of protection	NEMA 1 conforming to Nema type 250
IP degree of protection	IP20 conforming to IEC 60529
Ambient air temperature for operation	-20185 °F
Ambient air temperature for storage	-20185 °F

## Ordering and shipping details

Category	21492 - 9007 C SNAP SWITCHES
Discount Schedule	DS1
GTIN	00785901047247
Nbr. of units in pkg.	1
Package weight(Lbs)	0.200000000000001
Returnability	Υ
Country of origin	MX

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1150 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations
California proposition 65	WARNING: This product can expose you to chemicals including:
Substance 1	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Substance 2	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
More information	For more information go to www.p65warnings.ca.gov

### Contractual warranty

Warranty period	18 months

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Limit Switches category:

Click to view products by Schneider manufacturer:

Other Similar products are found below:

5ML1-E1 5ML31 LZG1 LZL1-6C 622EN114-R 622EN18-6 622EN224-6B 622EN230 622EN237-R 622EN69-3 622EN85-RB MA-10019
6PA109 7LS51 83547001 83725002 83830001 83840701 83841001 83881140 8AS42 8LS10 8LS125-4PG 8LS152-4PGN20 914CE163A 914CE3-3L1 915PA10 91MCE16-P2O 924CE16-Y3 924CE1-S6 924CE1-T25A 924CE1-T3 924CE1-T9A 924CE2-T9 924CE31-Y20X5 924CE31-Y3L1 GL-10054 GLAB26J2B GLDB03C-6 GLDC05C GLZ324 H3141CAKAA RDI-G-L5B DD-10000 DT-2R3-A7
14CE16-3N28 14CE18-N15 151ML3-E1 E3102BAAAA BFL1-AW1-S