9050JCK14V14

Plug-In Timer - On Delay - 1.2-120 seconds - 24VAC/DC



Product availability: Non-Stock - Not normally stocked in distribution facility



Main	
Product range	9050JCK
Product type	Timer
Timing mode	On-delay
Timing range	1.2120 s
Supply voltage	24 V AC/DC

Comp	lemen	tarv
COILIP	10111011	·u·y

o complementary		
Power consumption	2 VA	
Line Rated Current	10 A	
Switch function	DPDT	
Contact composition	2 NO + 2 NC	
Contact material	Silver nickel	
Maximum switching voltage	240 V AC	
Mounting type	Socket	
Number of pins	8	
Shape of pins	Tubular	
For use with	8501NR51	
	8501NR52	

Environment

Environment	
Certifications	CE RoHS UL listed UL recognized
Ambient temperature range - operational	-18150 °F
Height	2.4 in (61 mm)
Width	1.69 in (43 mm)
Depth	4.09 in (104 mm)

Ordering and shipping details

Category	21651 - 9050 JCK(NOT JCK60, 70) G P TIMERS	
Discount Schedule	CP2	
GTIN	00785901056362	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.3300000000000002	
Returnability	N	
Country of origin	US	

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0627 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available
California proposition 65	WARNING: This product can expose you to chemicals including:
Substance 1	Nickel compounds, which is known to the State of California to cause cancer, and
Substance 2	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
More information	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months
-----------------	-----------

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Time Delay & Timing Relays category:

Click to view products by Schneider manufacturer:

Other Similar products are found below:

5NO30 614-11B-0A2 614-11B-0A3 614-11B-OA4 614-11B-OA6 614-11B-OA6 614-11C-OA1 614-11C-OA2 614-11C-OA5 614-11Q-OA3 614-11T-OA3 614-11T-OA6 614-11T-OA7 614-12B-4A1 614-12C-400 614-12Q-400 614-12T-600 614-22T-4A1 614-43B-400 614-43C-100 614-43F-200 614-43Q-0A2 614-43Q-100 614-43Q-600 614-43T-0A9 614-43T-600 614-43U-400 614-43U-4A1 614-43U-6A2 615-21T-200 655-11T-100 655-11U-500 655-12T-300 655-22T-400 655-22T-600 CUA-41-30001 CUA-41-30030 CUA-41-70180 CUA-41-71038 CUA-42-30005 CUA-42-30010 CUA-42-30120 CUA-42-70120 CUA-99-72502 CUC-41-30030 CUF-42-30010 CUH-41-31006 7012AFX 7012GD