



Overview

Lead time	Usually in Stock
-----------	------------------

Main

Kw Rating	450 W
Rated power in VA	850 VA
Nb of power socket outlets	6 NEMA 5-15R 3 NEMA 5-15R surge
Main Output Voltage	120 V
Main Input Voltage	120 V
Plug standard	NEMA 5-15P
Cable length	5 ft (1.52 m)
Number of cables	1

General

Provided equipment	User Manual USB cable
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Color	Black
Depth	4.13 in (10.5 cm)
Height	5.47 in (13.9 cm)
Mounting preference	No preference
Net Weight	9.04 lb(US) (4.1 kg)
Mounting Mode	Not rack-mountable
Two post mountable	0
USB compatible	No
Width	12.87 in (32.7 cm)

Input

Input Frequency	50/60 Hz +/- 3 Hz auto-sensing
Efficiency at full load	92...139 V

Output

Max Configurable Power (Watts)	450 W
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains
Topology	Standby
Waveform Type	Stepped approximation to a sine wave
Maximum configurable power in VA	850 VA
Transfer Time	6ms typical : 10ms maximum

Conformance

Product Certifications	California (CEC) Battery Charger cTUVus
Standards	CSA C22.2 No 107.3 FCC Part 15 class B UL 1778
Equipment protection policy	Lifetime : \$75000

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	10...90 %
Storage altitude	0...50000 ft (0.00...15240.00 m)
Acoustic level	45 dBA

Batteries & Runtime

Battery Type	Lead-Acid battery
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	8 h
Battery Charge Power (Watts)	13 W rated
Battery power in VAH	102 VAh capacity 104 VAh runtime
Battery life	2...5 year(s)
Battery graph comments	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several variables including battery age, battery charge level, environmental conditions and characteristics of the connected load.
Extendable Run Time	0

Communications & Management

Control panel	LED status display with On Line : On Battery : Replace Battery and Building Wiring Fault
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	354 J
---------------------	-------

Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
GTIN	00731304325260
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No

Packing Units

Package 1 Height	7.72 in (19.6 cm)
Package 1 width	16.38 in (41.6 cm)
Package 1 Length	6.61 in (16.8 cm)
SCC14	10731304325267
Number of Units in Package 2	2
Package 2 Weight	21.61 lb(US) (9.80 kg)
Package 2 Height	16.89 in (429.01 mm)
Package 2 width	13.74 in (349.00 mm)
Package 2 Length	8.64 in (219.46 mm)
Number of Units in Package 3	80
Package 3 Weight	912.71 lb(US) (414 kg)
Package 3 Height	1.57 in (4 cm)
Package 3 width	47.24 in (120 cm)
Package 3 Length	47.24 in (120 cm)
Pallet unit layers	16
Pallet layers	5

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	3 years repair or replace
----------	---------------------------

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [UPS - Uninterruptible Power Supplies](#) category:

Click to view products by [Schneider](#) manufacturer:

Other Similar products are found below :

[SMART-1400-RM](#) [UPS1500ITSIT](#) [UPS25512](#) [UPS1024746](#) [UPS23916EBM](#) [UPSITSNMP](#) [TRIO-UPS-2G/1AC/24DC/5](#) [TRIO-UPS-2G/1AC/24DC/10](#) [QUINT4-UPS/24DC/24DC/20/EI](#) [QUINT4-UPS/24DC/24DC/5/USB](#) [SLNSPSPMBRK](#) [MINI-BAT/12DC/2.6AH](#) [1274119](#)
[TSPC 240-124UPS](#) [SDU-24-BAT](#) [AKKUTEC2440](#) [DR-UPS40](#) [DUPS40](#) [UPS003LSM](#) [1081430](#) [1082548](#) [1094596](#) [2320212](#) [2320225](#)
[2320238](#) [2320241](#) [2320254](#) [2320267](#) [2320270](#) [2320377](#) [2320380](#) [2320393](#) [2320461](#) [2320526](#) [2866213](#) [2866226](#) [2866239](#) [2866242](#)
[2866349](#) [2866352](#) [2866365](#) [2866417](#) [2866569](#) [2866572](#) [2866598](#) [2866611](#) [2866666](#) [2868703](#) [2905907](#) [2905908](#)