

Product data sheet

Specifications



APC Back-UPS CS 350VA, 120V, 6 NEMA outlets (4 surge)

BK350

Overview

Lead time Usually in Stock

Main

Kw Rating	210 W
Rated power in VA	350 VA
Nb of power socket outlets	3 NEMA 5-15R 3 NEMA 5-15R surge
Main Output Voltage	120 V
Main Input Voltage	120 V
Plug standard	NEMA 5-15P
Cable length	6 ft (1.83 m)
Number of cables	1

General

Provided equipment CD with software
Cord management straps
User Manual
USB cable

Number of power module free slots 0

Number of power module filled slots 0

Redundant No

Physical

Color	Beige
Depth	11.18 in (28.4 cm)
Height	6.50 in (16.5 cm)
Mounting Location	Front
Mounting preference	No preference
Net Weight	12.52 lb(US) (5.68 kg)
Mounting Mode	Not rack-mountable
Two post mountable	0

USB compatible	Yes
Width	3.58 in (9.1 cm)

Input

Input Frequency	50/60 Hz +/- 3 Hz auto-sensing
Efficiency at full load	98...140 V

Output

Max Configurable Power (Watts)	210 W
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains
Topology	Standby
Waveform Type	Stepped approximation to a sine wave
Maximum output current	10 A
Maximum configurable power in VA	350 VA
Transfer Time	8ms typical : 12ms maximum

Conformance

Product Certifications	California (CEC) Battery Charger ENERGY STAR V2.0 (USA) TÜV
Standards	FCC part 68
Equipment protection policy	Lifetime : \$100000

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0.00...15240.00 m)
Acoustic level	45 dBA
Heat dissipation	20 Btu/h

Batteries & Runtime

Battery Type	Lead-Acid battery
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	8 h
RBC Quantity	1
Battery Voltage	12 V
Battery Capacity	7.0 Ah
Battery Charge Power (Watts)	10 W rated
Battery power in VAH	86 VAh capacity 84 VAh runtime

Battery life	4...6 year(s)
Battery graph comments	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several variables including battery age, battery charge level, environmental conditions and characteristics of the connected load.
Extendable Run Time	0

Communications & Management

Control panel	LED status display with On Line : On Battery : Replace Battery and Overload indicators
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	1020 J
Filtering	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : mee
Data line protection	Analog phone line for phone/fax/modem/DSL (RJ11 connector)
Let Through Voltage Rating	300 V


Ordering and shipping details

Package weight(Lbs)	14.02 lb(US) (6.36 kg)
---------------------	------------------------

Packing Units

Package 1 Height	10.35 in (26.3 cm)
Package 1 width	6.89 in (17.5 cm)
Package 1 Length	14.06 in (35.7 cm)
SCC14	10731304016295
Number of Units in Package 2	2
Package 2 Weight	29 lb(US) (13.15 kg)
Number of Units in Package 3	36

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Energy Star	ENERGY STAR UPS V2.0 (USA) 
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	3 years repair or replace
----------	---------------------------

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [UPS - Uninterruptible Power Supplies](#) category:

Click to view products by [Schneider](#) manufacturer:

Other Similar products are found below :

[SMART-1400-RM](#) [UPS1500ITSIT](#) [UPS12438](#) [UPS12434](#) [UPS25512](#) [UPS1024746](#) [UPS23916EBM](#) [UPSITSNMP](#) [TRIO-UPS-2G/1AC/24DC/5](#) [TRIO-UPS-2G/1AC/24DC/10](#) [QUINT4-UPS/24DC/24DC/20/EI](#) [QUINT4-UPS/24DC/24DC/5/USB](#) [QUINT4-UPS/24DC/24DC/20/US](#) [SLNSPSPMBRK](#) [MINI-BAT/12DC/2.6AH](#) [TSPC 240-124UPS](#) [AKKUTEC2440](#) [DR-UPS40](#) [UPS003LSM](#)
[1081430](#) [1082548](#) [1094596](#) [2320212](#) [2320225](#) [2320238](#) [2320241](#) [2320254](#) [2320267](#) [2320270](#) [2320377](#) [2320380](#) [2320393](#) [2320461](#)
[2866213](#) [2866226](#) [2866239](#) [2866242](#) [2866349](#) [2866352](#) [2866365](#) [2866417](#) [2866569](#) [2866572](#) [2866598](#) [2866611](#) [2866666](#) [2868703](#)
[2905907](#) [2905908](#) [2905909](#)