Product data sheet Characteristics

DL1CJUS0245

LED bulb with BA9s base - amber - 24 V AC/DC



Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Range compatibility	Harmony XB4
Accessory / separate part type	LED bulb
Accessory / separate part category	Lighting accessory
Accessory / separate part destination	Illuminated push-button
[Us] rated supply voltage	24 V AC/DC
Signalling colour	Amber
Sale per indivisible quantity	1

Complementary

Bulb base	BA 9s
-----------	-------

Ordering and shipping details

ordorning and ornpping dotaile		
Category	22466 - PUSHBUTTON, ACCESSORIES	
Discount Schedule	CS2	
GTIN	00785901070092	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.01	
Returnability	N	
Country of origin	US	

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 0627 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	
California proposition 65	WARNING: This product can expose you to chemicals including:	
Substance 1	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.	
More information	For more information go to www.p65warnings.ca.gov	

Contractual warranty

Contracted warranty		
Warranty period	18 months	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Lamps category:

Click to view products by Schneider manufacturer:

Other Similar products are found below:

5AB 6180 8111 8623 912 120PS 1224 DE603 DW50 IFL-LX2162-16T C9A C9A 3015 303 19 PR13 268 GT-NE6H1225T

CM5004WW 32-2211T 323 509K 5314N1 5314N2 WWT1-EW10/GRN 4925H1 DW07 10C7DC-120V 1141 MS25231-313 E73 CM2

7683EBP 8553 XE135B WWT2-EW34BLA 6S6/30V 7367 1301910036 7A1H 8630FBBB 85 106 105 BGF717-UV1 1974D 1495 373

400 502