



Main

Range	TeSys
Device short name	GV4AE
Product or Component Type	Auxiliary contact
Device Application	Signalling
Range compatibility	TeSys GV4 TeSys BV4
Auxiliary contact composition	1 NO/NC
[Ue] rated operational voltage	<= 690 V
[Ith] conventional free air thermal current	5 A IEC 60947-5-1 5 A CSA C22.2 No 14 5 A UL 508
Mounting Mode	Internal mounting

Complementary

[Ui] rated insulation voltage	690 V IEC 60947-1
[Ie] rated operational current	5 A <= 690 V AC-12 IEC 60947-5-1 5 A <= 48 V AC-15 IEC 60947-5-1 4 A 110/127 V AC-15 IEC 60947-5-1 3 A 220/240 V AC-15 IEC 60947-5-1 2.5 A 380...440 V AC-15 IEC 60947-5-1 0.11 A 660/690 V AC-15 IEC 60947-5-1 5 A <= 24 V DC-12 IEC 60947-5-1 2.5 A 48 V DC-12 IEC 60947-5-1 0.6 A 110/127 V DC-12 IEC 60947-5-1 0.3 A 250 V DC-12 IEC 60947-5-1 2.5 A <= 24 V DC-12 IEC 60947-5-1 1.2 A 48 V DC-12 IEC 60947-5-1 0.35 A 110/127 V DC-12 IEC 60947-5-1 0.05 A 250 V DC-12 IEC 60947-5-1 1 A <= 24 V DC-12 IEC 60947-5-1 0.2 A 48 V DC-12 IEC 60947-5-1 0.05 A 110/127 V DC-12 IEC 60947-5-1 0.03 A 250 V DC-12 IEC 60947-5-1
Rated power in VA	120 VA AC-12 24 V IEC 60947-5-1 240 VA AC-12 48 V IEC 60947-5-1 635 VA AC-12 110/127 V IEC 60947-5-1 1200 VA AC-12 230/240 V IEC 60947-5-1 2200 VA AC-12 380/440 V IEC 60947-5-1 3450 VA AC-12 660/690 V IEC 60947-5-1
Rated power in W	DC-12 120 W 24 V IEC 60947-5-1 DC-12 120 W 48 V IEC 60947-5-1 DC-12 66 W 110 V IEC 60947-5-1 DC-12 75 W 250 V IEC 60947-5-1
Associated fuse rating	5 A gG 690 V IEC 60947-5-1
Minimum switching current	2 mA
Minimum switching voltage	17 V
Mechanical durability	40000 cycles
Connections - terminals	Spring terminals 1 0.00...0.00 in ² (0.5...1.5 mm ²) flexible without cable end
Wire stripping length	0.31 in (8 mm)

Environment

Quantity per Set	Set of 1
------------------	----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ordering and shipping details

Category	22366 - MAN STR PROTECTORS-GV1/GV3
Discount Schedule	I11
GTIN	3606485444246
Nbr. of units in pkg.	1
Package weight(Lbs)	0.92 oz (26 g)
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	0.79 in (2 cm)
Package 1 width	3.15 in (8 cm)
Package 1 Length	4.33 in (11 cm)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	9.35 oz (265 g)
Package 2 Height	1.57 in (4 cm)
Package 2 width	6.30 in (16 cm)
Package 2 Length	10.63 in (27 cm)
Unit Type of Package 3	P06
Number of Units in Package 3	1760
Package 3 Weight	134.14 lb(US) (60.844 kg)
Package 3 Height	29.53 in (75 cm)
Package 3 width	23.62 in (60 cm)
Package 3 Length	31.50 in (80 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Circuit Breakers](#) category:

Click to view products by [Schneider](#) manufacturer:

Other Similar products are found below :

[LUGZX66-1-61-20.0-44](#) [M39019/01-201](#) [M39019/01-221](#) [M39019/04-249S](#) [M39019/04-313S](#) [M55629/1-016](#) [M55629/1-018](#) [M55629/1-021](#)
[M55629/1-033](#) [M55629/1-046](#) [M55629/1-048](#) [M55629/1-058](#) [M55629/1-067](#) [M55629/1-070](#) [M55629/1-079](#) [M55629/1-084](#) [M55629/1-085](#)
[M55629/1-101](#) [M55629/1-109](#) [M55629/11-102](#) [M55629/12-045](#) [M55629/12-046](#) [M55629/1-330](#) [M55629/1-366](#) [M55629/1-387](#) [M55629/1-](#)
[401](#) [M55629/2-022](#) [M55629/2-030](#) [M55629/2-072](#) [M55629/2-082](#) [M55629/2-099](#) [M55629/2-101](#) [M55629/2-102](#) [M55629/21-BM-BM](#)
[M55629/21-HM-HM](#) [M55629/21-NS-NS](#) [M55629/22-NR-NR-NR](#) [M55629/22-RS-RS-RS](#) [M55629/2-347](#) [M55629/2-401](#) [M55629/2-413](#)
[M55629/3-030](#) [M55629/3-050](#) [M55629/3-102](#) [M55629/3-103](#) [M55629/3-128](#) [M55629/3-130](#) [M55629/3-238](#) [M55629/3-386](#) [M55629/3-](#)
[LBZB](#)