Product data sheet Characteristics

GVAE113 TeSys GV2 & GV3 - auxiliary contact - 1 NO + 1 NC



Product availability: Stock - Normally stocked in distribution facility



| Main | |
|-------------------------------|--|
| Range | TeSys |
| Device short name | GVAE |
| Product or component type | Auxiliary contact block |
| Product compatibility | GV2RT GV2L GV2LE GV3P GV2P GV3L LS1D323 GV2ME |
| Mounting location | Front side |
| Pole contact composi- tion | 1 NO + 1 NC |
| Connections - terminals | Spring terminals 2 cable 00 in ² (0.751.5 mm ²) - cable stiffness: flexible - without cable end |
| Quantity per set | Set of 10 |

Complementary

| Complementary | |
|---|--|
| [Ui] rated insulation voltage | 300 V - conforming to UL 508 300 V - conforming to CSA C22.2 No 14 250 V - conforming to IEC 60947-1 |
| System Voltage | 24240 V AC 2460 V DC |
| [Ith] conventional free air thermal current | 2.5 A |
| Protection type | GG fuse 10 A GB2CB06 circuit breaker 10 A |
| Mechanical durability | 100000 cycles |
| Minimum switching current | 5 mA |
| Minimum switching voltage | 17 V |
| Rated operational power in VA | 120 VA at 110120 V AC-15 - electrical durability: 100000 cycles 120 VA at 230240 V AC-15 - electrical durability: 100000 cycles 48 VA at 24 V AC-15 - electrical durability: 100000 cycles 60 VA at 48 V AC-15 - electrical durability: 100000 cycles |
| Rated operational power in W | 15 W at 48 V DC-13 - electrical durability: 100000 cycles 24 W at 24 V DC-13 - electrical durability: 100000 cycles 9 W at 60 V DC-13 - electrical durability: 100000 cycles |
| Height | 0.51 in (13 mm) |
| Width | 1.75 in (44.5 mm) |
| Depth | 1.24 in (31.5 mm) |
| Product weight | 0.11 lb(US) (0.05 kg) |
| | |

Environment

| Environmental characteristic | Normal environment | |
|------------------------------|--------------------|--|
|------------------------------|--------------------|--|



Ordering and shipping details

| Category | 22367 - MANUAL STR PROTECTOR - GV2 |
|-----------------------|------------------------------------|
| Discount Schedule | l11 |
| GTIN | 00785901494935 |
| Nbr. of units in pkg. | 10 |
| Package weight(Lbs) | 4.0000000000001E-2 |
| Returnability | Y |
| Country of origin | CZ |
| | |

Offer Sustainability

| Sustainable offer status | Green Premium product |
|----------------------------------|---|
| RoHS (date code: YYWW) | Compliant - since 0701 - Schneider Electric declaration of conformity |
| REACh | Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |
| California proposition 65 | WARNING: This product can expose you to chemicals including: |
| Substance 1 | Lead and lead compounds, which is known to the State of California to cause can- cer and birth defects or other reproductive harm. |
| More information | For more information go to www.p65warnings.ca.gov |

Contractual warranty

Warranty period

18 months

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Contactors - Electromechanical category:

Click to view products by Schneider manufacturer:

Other Similar products are found below :

6-1618400-7 686-117111 686-120111 686-924 686-948 70-901 70-914 MB-3D-6 MC-22A/4-AC120V 8-1616943-9 8-1672124-5 A40-30-10-84 120-905 A701U 120-904 1393132-9 154-905 154-912 154-913 154-915 154-902 154-910 AVR743D B6-40-00-84 B7-40-00-84 1616017-5 1616021-1 MVDILM HP-11D-24 P25-E5019-1 P30C47A12D1-120 P40C47A12D1-120 P40P47D13P1-24-01 CA7-12-10-240 CA7-72-00-24Z 90-162 9-1393132-2 2NC4F0222 A275KXXV2-120VAC ACC338UMM20 AF80-30-11-13 SZ-B1 CGC-9A-120 3GC2H0M22 3NC0T0A22 3NC1Q0A22 3NC2H0A22 3NC2T0122/SE 3TF3400-0BB4 MC-12B-DC24V