## Product data sheet Characteristics

## GVAE203 TeSys GV2 & GV3 - auxiliary contact block - 2 NO



Product availability: Non-Stock - Not normally stocked in distribution facility



Main	
Range	TeSys
Device short name	GVAE
Product or component type	Auxiliary contact block
Product compatibility	GV2RT GV2P GV2ME GV3L LS1D323 GV2L GV3P GV2LE
Mounting location	Front side
Pole contact composi- tion	2 NO
Connections - terminals	Spring terminals 2 cable 00 in <sup>2</sup> (0.751.5 mm <sup>2</sup> ) - cable stiffness: flexible - without cable end
Quantity per set	Set of 10

#### Complementary

Complementary	
[Ui] rated insulation voltage	300 V - conforming to UL 508 300 V - conforming to CSA C22.2 No 14 250 V - conforming to IEC 60947-1
System Voltage	24240 V AC 2460 V DC
[Ith] conventional free air thermal current	2.5 A
Protection type	GG fuse 10 A GB2CB06 circuit breaker 10 A
Mechanical durability	100000 cycles
Minimum switching current	5 mA
Minimum switching voltage	17 V
Rated operational power in VA	120 VA at 110120 V AC-15 - electrical durability: 100000 cycles 120 VA at 230240 V AC-15 - electrical durability: 100000 cycles 48 VA at 24 V AC-15 - electrical durability: 100000 cycles 60 VA at 48 V AC-15 - electrical durability: 100000 cycles
Rated operational power in W	15 W at 48 V DC-13 - electrical durability: 100000 cycles 24 W at 24 V DC-13 - electrical durability: 100000 cycles 9 W at 60 V DC-13 - electrical durability: 100000 cycles
Height	0.51 in (13 mm)
Width	1.75 in (44.5 mm)
Depth	1.24 in (31.5 mm)
Product weight	0.11 lb(US) (0.05 kg)

#### Environment

Environmental characteristic	Normal environment	
------------------------------	--------------------	--



### Ordering and shipping details

Category	22367 - MANUAL STR PROTECTOR - GV2
Discount Schedule	111
GTIN	00785901494928
Nbr. of units in pkg.	10
Package weight(Lbs)	0.46000000000002
Returnability	Ν
Country of origin	CZ

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0701 - Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations
California proposition 65	WARNING: This product can expose you to chemicals including:
Substance 1	Lead and lead compounds, which is known to the State of California to cause can- cer and birth defects or other reproductive harm.
More information	For more information go to www.p65warnings.ca.gov

#### Contractual warranty

Warranty period

18 months

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Contactors - Electromechanical category:

Click to view products by Schneider manufacturer:

Other Similar products are found below :

6-1618400-7 686-117111 686-120111 686-924 686-948 70-901 70-914 MB-3D-6 MC-22A/4-AC120V 8-1616943-9 8-1672124-5 A40-30-10-84 120-905 A701U 120-904 1393132-9 154-905 154-912 154-913 154-915 154-902 154-910 AVR743D B6-40-00-84 B7-40-00-84 1616017-5 1616021-1 MVDILM HP-11D-24 P25-E5019-1 P30C47A12D1-120 P40C47A12D1-120 P40P47D13P1-24-01 CA7-12-10-240 CA7-72-00-24Z 90-162 9-1393132-2 2NC4F0222 A275KXXV2-120VAC ACC338UMM20 AF80-30-11-13 SZ-B1 CGC-9A-120 3GC2H0M22 3NC0T0A22 3NC1Q0A22 3NC2H0A22 3NC2T0122/SE 3TF3400-0BB4 MC-12B-DC24V