

Product availability: Stock - Normally stocked in distribution facility



Main	
Range	TeSys
Device short name	GVAE
Product or component type	Auxiliary contact block
Product compatibility	LS1D32 GV3P GV2P GV2RT GV2L GV2ME GV3L GV2LE
Mounting location	Front side
Pole contact composition	2 NO
Connections - terminals	Screw clamp terminals 1 cable 00 in² (0.752.5 mm²) - cable stiffness: flexible - without cable end Screw clamp terminals 2 cable 00 in² (0.752.5 mm²) - cable stiffness: flexible - without cable end Screw clamp terminals 1 cable 00 in² (0.751.5 mm²) - cable stiffness: flexible - with cable end Screw clamp terminals 1 cable 00 in² (12.5 mm²) - cable stiffness: solid Screw clamp terminals 2 cable 00 in² (12.5 mm²) - cable stiffness: solid
Quantity per set	Set of 10

#### Complementary

[Ui] rated insulation voltage	300 V - conforming to UL 508 300 V - conforming to CSA C22.2 No 14 250 V - conforming to IEC 60947-1	
System Voltage	24240 V AC 2460 V DC	
[lth] conventional free air thermal current	2.5 A	
Protection type	GG fuse 10 A GB2CB06 circuit breaker 10 A	
Mechanical durability	100000 cycles	
Minimum switching current	5 mA	
Minimum switching voltage	17 V	
Rated operational power in VA	120 VA at 110120 V AC-15 - electrical durability: 100000 cycles 120 VA at 230240 V AC-15 - electrical durability: 100000 cycles 48 VA at 24 V AC-15 - electrical durability: 100000 cycles 60 VA at 48 V AC-15 - electrical durability: 100000 cycles	
Rated operational power in W	15 W at 48 V DC-13 - electrical durability: 100000 cycles 24 W at 24 V DC-13 - electrical durability: 100000 cycles 9 W at 60 V DC-13 - electrical durability: 100000 cycles	
Tightening torque	1.4 N.m - on screw clamp terminals	
Height	0.43 in (11 mm)	
Width	1.77 in (45 mm)	
Depth	1.14 in (29 mm)	
Product weight	0.04 lb(US) (0.02 kg)	

#### **Environment**

Environmental characteristic	Normal environment

## Ordering and shipping details

Category	22367 - MANUAL STR PROTECTOR - GV2	
Discount Schedule	l11	
GTIN	00785901343462	
Nbr. of units in pkg.	1	
Package weight(Lbs)	5.00000000000003E-2	
Returnability	Υ	
Country of origin	CZ	

## Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 0701 - Schneider Electric declaration of conformity Schneder Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	
California proposition 65	WARNING: This product can expose you to chemicals including:	
Substance 1	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.	
More information	For more information go to www.p65warnings.ca.gov	

### Contractual warranty

Warranty period	18 months	

GVAE20



# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Motor Drives category:

Click to view products by Schneider manufacturer:

Other Similar products are found below:

GMA02 R7DBP02L 1300920283 ST10-S GMA11 GMA20 R88DUA03LAAC100V30W R88DUA12HA R88DUP03LAAC100V30W VX5A1400 VFD002EL11A MFMCB0030GET MFECA0030EAM 1302263150 1300920078 R88D-GT04H R88D-GN04H-ML2 R7D-BP01H R88D-KN04L-ECT 70354063 79294435 27358015 15275008 ST5-Q-EN 1SFA896103R1100 1SFA896103R7000 1SFA896112R1100 R88D-GP08H GNCF8-11 KLC35BE ST10-Q-RN 1302263161 SV2D10-Q-AE VX5A1300 2SIE 71-2A R88A-CA1C005SF-E R88A-CR1B005NF-E SEH 56-2C SEH 71-4B SEHR90-4L U-PKZ0(400V50HZ) LUCC12BL LUCC12FU LU9BN11L LULC08 GV2P01 UDS1UR6M50CANCZ183 LC1D09M7 103H7126-1740 103H7823-1741