Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Range of product	Harmony Series K
Product or component type	Cam switch operating head
Component name	KAX
Product compatibility	Front mounting bodies 12 and 20 A by Ø 22 mm hole
Cam switch head type	With bezel Ø 28.5 mm, metal
Type of operator	Key Ronis 455
Rotary handle padlock-ing	Without
Presentation of legend	With mat black legend
Switching angle	45 °

Complementary

Mechanical durability	1000000 cycles	
CAD overall width	1.14 in (29 mm)	
CAD overall height	1.14 in (29 mm)	
CAD overall depth	0.83 in (21 mm)	
Product weight	0.14 lb(US) (0.065 kg)	

Environment

Protective treatment	TC	
Ambient air temperature for operation	-13131 °F (-2555 °C)	
Ambient air temperature for storage	-40158 °F (-4070 °C)	
Shock resistance	30 gn conforming to IEC 68-2-27	
Vibration resistance	5 gn, 10150 Hz conforming to IEC 68-2-6	
IP degree of protection	IP65 conforming to IEC 529 IP65 conforming to NF C 20-010	

Ordering and shipping details

Category	21446 - 9003 K CAM SWITCHES
Discount Schedule	CS1
GTIN	00785901837688
Nbr. of units in pkg.	1
Package weight(Lbs)	0.140000000000001
Returnability	N
Country of origin	CZ

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including:
Substance 1	Nickel compounds, which is known to the State of California to cause cancer, and
Substance 2	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
More information	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	40 continu
Warranty period	18 months

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Keylock Switches category:

Click to view products by Schneider manufacturer:

Other Similar products are found below:

89496-09 58J1007 58J8A45-01B05N 719-0201-000 719-0202-000 719-0702-000 719-5504-000 84800-04 GKNC33L GKNC3L

PVA2OAH5 HA1K-2C2VA-2 14-136.025K 14-235.022K AS6H-2K2A AS6M-2K1B AS6Q-2K2A AS6Q-3K2A 1571487-1 KEY-AS6

KH3C-20C 8928K493 2SWK131AL102 AS6M-2K1A AS6Q-2K1PB 51-401.036D 51-414.036D HW1K-31BF20 HW1K-3HF20 Y1112
2027CLFT 51-155.025D 51-195.025D 51-404.036D 51-405.036D 1-1437597-8 58J8A36-01B04N 58M1422 86945-05 719-0204-000 719
0205-000 719-0801-000 719-0804-000 719-0805-000 88422-18 58J8A90-01C02N 58J9P36-01B09N 58J8A36-01C03N GKRA3K1A2-F03
C GKBB14L6 14-236.025K1020