Product data sheet Characteristics

LE1D09V7

TeSys LE - enclosed DOL starter - 9 A - 400 V AC coil





Main

| Range | TeSys | |
|---------------------------|--|--|
| Product name | TeSys LE | |
| Device short name | LE1D | |
| Product or component type | Enclosed DOL starter | |
| Device application | Standard | |
| Utilisation category | AC-3 | |
| Device composition | Thermal overload relay ordered separately Contactor | |
| Control type | Push-button start green I Push-button stop/reset red O | |

Complementary

| [le] rated operational current | 9 A AC-3 | |
|--|--|--|
| Motor power kW | 4 KW at 380/400 V AC 50/60 Hz 4 KW at 415 V AC 50/60 Hz 4 KW at 440 V AC 50/60 Hz 2.2 KW at 220/230 V AC 50/60 Hz 5.5 KW at 500 V AC 50/60 Hz 5.5 KW at 660/690 V AC 50/60 Hz | |
| [Ithe] conventional enclosed thermal current | 9 A | |
| [Uc] control circuit voltage | 400 V AC 50/60 Hz | |
| Cable entry number | 2 ISO20 top 2 ISO20 bottom 2 Pg 13 bottom 2 Pg 16 bottom | |
| Width | 88 Mm | |
| Height | 166 Mm | |
| Depth | 128.5 Mm | |
| Product weight | 0.92 Kg | |

Environment

| Material | Polycarbonate |
|---------------------------------------|------------------------------|
| IP degree of protection | IP65 conforming to IEC 60529 |
| IK degree of protection | IK07 conforming to IEC 60529 |
| Standards | IEC 60947-4-1 |
| Ambient air temperature for operation | -540 °C |
| Environmental characteristic | Standard environment |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|----------|
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 874 G |
| Package 1 Height | 19.5 Cm |
| Package 1 width | 20 Cm |
| Package 1 Length | 25.5 Cm |
| Unit Type of Package 2 | P06 |
| Number of Units in Package 2 | 30 |
| Package 2 Weight | 39.22 Kg |
| Package 2 Height | 80 Cm |
| Package 2 width | 80 Cm |
| Package 2 Length | 60 Cm |
| - | |

Offer Sustainability

| Sustainable offer status | Green Premium product | |
|----------------------------|---|--|
| REACh Regulation | REACh Declaration | |
| REACh free of SVHC | Yes | |
| EU RoHS Directive | Compliant EEU RoHS Declaration | |
| Toxic heavy metal free | Yes | |
| Mercury free | Yes | |
| RoHS exemption information | ₫Yes | |
| China RoHS Regulation | China RoHS Declaration | |
| Environmental Disclosure | Product Environmental Profile | |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins | |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov | |

Contractual warranty

| Warranty | 18 months | |
|-----------|-----------|--|
| vvarianty | 18 months | |

Product Life Status: Commercialised

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Motor Drives category:

Click to view products by Schneider manufacturer:

Other Similar products are found below:

GMA02 R7DBP02L 1300920283 ST10-Plus ST10-S GMA11 GMA20 R88DUA03LAAC100V30W R88DUA12HA

R88DUP03LAAC100V30W VX5A1400 VFD002EL11A MFMCB0030GET MFECA0050EAM 1302263150 1300920078 SR24 R88D
GT04H R88D-GN04H-ML2 R7D-BP01H R88D-KN04L-ECT 70354063 79294435 27358015 15275008 ST5-Q-EN 1SFA896103R1100

1SFA896103R7000 1SFA896112R1100 R88D-GP08H GNCF8-11 KLC35BE ST10-Q-RN 1302263161 VX5A1300 2SIE 71-2A 2SIE 71X
4C DV0P4140-FTDI R88A-CA1C005SF-E R88A-CR1B005NF-E SEH 56-2C SEH 71-4B SEHR90-4L U-PKZ0(400V50HZ) LUCC12BL

LUCC12FU LU9BN11L LULC08 ODE-3-140022-3F1B UDS1UR6M50CANCZ183