# LE1D18M7

# TeSys LE - enclosed DOL starter - 18 A - 220 V AC coil





Main	
Range	TeSys
Product name	TeSys LE
Device short name	LE1D
Product or component type	Enclosed DOL starter
Device application	Standard
Utilisation category	AC-3
Device composition	Thermal overload relay ordered separately Contactor

Push-button start green I Push-button stop/reset red O

#### Complementary

[le] rated operational current	18 A AC-3	
Motor power kW	10 KW at 500 V AC 50/60 Hz 10 KW at 660/690 V AC 50/60 Hz 4 KW at 220/230 V AC 50/60 Hz	
	9 KW at 415 V AC 50/60 Hz	
	9 KW at 440 V AC 50/60 Hz	
	7.5 kW at 380/400 V AC 50/60 Hz	
[Ithe] conventional enclosed thermal current	18 A	
[Uc] control circuit voltage	220 V AC 50/60 Hz	
Cable entry number	2 ISO20 top	
	2 ISO20 bottom	
	2 Pg 16 bottom	
	2 ISO25 top	
	2 Pg 21 bottom	
	2 ISO25 bottom	
Width	3.98 in (101 mm)	
Height	7.91 in (201 mm)	
Maximum Depth	6.04 in (153.5 mm)	
Net Weight	2.24 lb(US) (1.015 kg)	

Control type

#### Environment

Material	Polycarbonate
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 60529
Standards	IEC 60947-4-1
Ambient air temperature for operation	-540 °C
Environmental characteristic	Standard environment

#### Ordering and shipping details

22313 - CTRS,D-LINE,ENCL (METAL)	
l11	
03389110578188	
1	
2.57 lb(US) (1.17 kg)	
No	
FR	
	111 03389110578188 1 2.57 lb(US) (1.17 kg) No

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	6.54 in (16.6 cm)
Package 1 width	7.87 in (20 cm)
Package 1 Length	9.92 in (25.2 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	1
Package 2 Weight	2.56 lb(US) (1.161 kg)
Package 2 Height	7.68 in (19.5 cm)
Package 2 width	6.30 in (16 cm)
Package 2 Length	9.76 in (24.8 cm)
Unit Type of Package 3	P06
Number of Units in Package 3	22
Package 3 Weight	85.16 lb(US) (38.63 kg)
Package 3 Height	31.50 in (80 cm)
Package 3 width	31.50 in (80 cm)
Package 3 Length	23.62 in (60 cm)

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

## Contractual warranty

Warranty	18 months

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Schneider manufacturer:

Other Similar products are found below:

ATV312H037M2 LU9M1 7D 7S 7XA1 FNQR2 8501RS44V24 8501RSD14P14V51 8501XO20V03Y414 9001KR9RH13 9001KXRK
9001SKR9P35RH25 9001SKT35L31 9003K2C003GA 9007AA1 9007BA1 9007C54D 9007C62A2 9007CA11 9007FA3 9007HA4
9007HA6 9007KA1 9007KB11 9007MS01S0206 9012GAR4 9012GAW2 9012GBW1 9012GDW5E3 9012GFW1 9012GNG1 9012GNG3
9012GNG6 9013FHG39J69 9013FSG52J33M4 9013GHG2J30 9050JCK2F30V14 GZ1E02 ABL8MEM24003 ABL8RPS24030
ATS01N206QN RSL1PRJU 9001KA35 9001KA3G 9001KA4 9001KR16H13 9001KR1GH5 9001KR1U 9001KXSDC 9007C52A2