



### Main

Range	PratiKa
Product or component type	Wander plug
Device short name	PratiKa plug
Plug, socket category	Low voltage
Poles description	3P + E
Network type	AC
Outlet standard	Industrial

### Complementary

Plug, socket, control station shape	Straight	
[In] rated current	16 A	
[Ue] rated operational voltage	380415 V	
Network frequency	50/60 Hz	
Ground lug clockwise position	6 h	
Plug, socket material	Housing: self-extinguishing engineering polymer	
Contacts material	Sleeves: brass	
Connections - terminals	Fast connection	
Cable cross section	12.5 Mm²	
Cable outer diameter	815 Mm	
Cable entry	Cable gland Fair lead	
Thread type	Pg 16	
Net weight	0.18 Kg	
Height	139 Mm	
Width	65 Mm	
Depth	65 Mm	
Colour	Grey (RAL 7035)	
Voltage colour	Red	

## **Environment**

Standards	IEC 60309-1 IEC 60309-2	
IP degree of protection	IP44 conforming to IEC 60529	
IK degree of protection	IK08 conforming to EN 62262	
Fire resistance	850 °C conforming to IEC 60695-2-11	
Relative humidity	50 % at 40 °C 70 % at 30 °C 90 % at 20 °C	

Operating altitude	2000 m		
Ambient air temperature for operation	35 °C ( 86400 s ) -2540 °C		

Off	er	Sι	ıst	ai	na	bi	lity

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	<sup>™</sup> China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

# Contractual warranty

Warrantv	18 months

Product Life Status:	Commercialised	
----------------------	----------------	--



# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for AC Power Entry Modules category:

Click to view products by Schneider manufacturer:

Other Similar products are found below:

0098.0050 6-1609987-9 6167.0002 7-6609955-2 FN389-4-22 FN9233ER-12-06 FN9233S1-10-06 FN9233S1-8-06 FN9233S1B-8-06 FN9233S1R-10-06 FN9233S1R-12-06 FN9233SB-10-06 FN9233SB-10-06 FN9233SR-10-06 FN9233SR-3-06 FN9244B-15-06HI FN9244EB-3-06 FN9244EB-8-06 FN9244ER-15-06 FN9244ER-8-06 FN9244ES1-8-06 FN9244ESB-8-06 FN9244EU-6-06 FN9244R-12-06 FN9244R-3-07 FN9244R-8-06 FN9244S1-10-06 FN9244S1-12-06 FN9244S1B-6-06 FN9244S1B-6-06 FN9244S1B-3-06 FN92