## Product data sheet Characteristics

# RL00402 REACTOR DRIVE LINE 3PH 1Hp 208/230V Open

Comple	emen	tary
--------	------	------

Line Rated Current	4 A
AWG gauge	AWG 22AWG 14
Depth	4.1 in (104.14 mm)
Electrical Connection	Screw clamp terminal
Height	2.8 in (71.12 mm)
Permissible voltage	600 V AC
Net Weight	4 lb(US) (1.81 kg)
Protection Type	Current protection Overvoltage protection Harmonic distortion
Width	4.4 in (111.76 mm)

#### Environment

NEMA degree of protection	No enclosure rating (open device)
Product Certifications	CE UL listed file E180243 CSA LR29753

#### Ordering and shipping details

Category	22062-LINE REACTORS/FILTERS (RL,KLC)	
Discount Schedule	CP4C	
GTIN	00785901884378	
Package weight(Lbs)	4.00 lb(US) (1.814 kg)	
Returnability	Yes	
Country of origin	US	

#### Contractual warranty

	•
Warranty	18 months

### **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Control Switches category:

Click to view products by Schneider manufacturer:

Other Similar products are found below:

80887-99 80932-99 86855-00 88814-30 1424293-1 HW4S-2TC10 89721-12 89804-08 SSN RL01801 ASD2L20N-LVO 50051857-17 50099156-001-05 51.155R-15200 50058920-26 CP-FA51 CP-FA49 ACCU-SC/L-3000 PP9M PP87G PP86GA PP74G PP73M PP71G PP70G PP6G PP62G PP58BL PP56G PP86GB PP77GA PP76G PP4M PP47G PP46G PP41M PP40G PP32G RD-20 PP23M PP14M PP12G RD-40 PORTAPRO PNB-2005 3057.0012 CV-075 CV-140SB CV-150 CV-150S