Product data sheet Characteristics

RL02501 REACTOR LINE 1PH 3HP 208v OPEN

Complementar	
	v

Line Rated Current	25 A
AWG gauge	AWG 22AWG 5
Depth	5.8 in (147.32 mm)
Electrical Connection	Screw clamp terminal
Height	3.5 in (88.90 mm)
Permissible voltage	600 V AC
Net Weight	11 lb(US) (4.99 kg)
Protection Type	Current protection Overvoltage protection Harmonic distortion
Width	7.2 in (182.88 mm)

Environment

NEMA degree of protection	No enclosure rating (open device)
Product Certifications	CSA LR29753 CE UL listed file E180243

Ordering and shipping details

Category	18065-SPARE PARTS DISCOUNT CP4C	
Discount Schedule	CP4C	
GTIN	00785901712213	
Package weight(Lbs)	11.00 lb(US) (4.990 kg)	
Returnability	Yes	
Country of origin	US	

Contractual warranty

Contractual warranty	
Warranty	18 months

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Control Switches category:

Click to view products by Schneider manufacturer:

Other Similar products are found below:

80887-99 80932-99 86855-00 88814-30 1424293-1 HW4S-2TC10 89721-12 89804-08 SSN RL01801 ASD2L20N-LVO 50051857-17 50099156-001-05 51.155R-15200 50058920-26 CP-FA51 CP-FA49 ACCU-SC/L-3000 PP9M PP87G PP86GA PP74G PP73M PP73G PP71G PP70G PP6G PP62G PP58BL PP56G PP86GB PP77GA PP76G PP4M PP47G PP46G PP41M PP40G PP32G RD-20 PP23M PP14M PP12G RD-40 PORTAPRO POM-2708 PNB-2005 3057.0012 CV-075 CV-140SB