Product data sheet Characteristics

SGC8025 MAGNET SWITCH - 15 VA max - 250 Vdc / 1 A max - 1 NO

Product availability: Non-Stock - Not normally stocked in distribution facility

Main	
Product or component type	Coded magnetic system
Contacts type and composition	1 NO
Material	Plastic
Electrical connection	Pre-cabled
System Voltage	250 V DC

Com		

Protection type	Overload and short-circuit protection
Breaking capacity	15 VA

Environment

Ambient air temperature for operation	-13158 °F (-2570 °C)
Ambient air temperature for storage	-40185 °F (-4085 °C)

Ordering and shipping details

Category	22487 - SENSORS, PROXIMITY, U S	
Discount Schedule	DS2	
GTIN	00785901173380	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.2800000000000003	
Returnability	N	
Country of origin	US	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including:	
Substance 1	Diisononyl phthalate (DINP), which is known to the State of California to caus cancer, and	
Substance 2	Di-isodecyl phthalate (DIDP), which is known to the State of California to caus birth defects or other reproductive harm.	
More information	For more information go to www.p65warnings.ca.gov	

Contractual warranty

Contractual warranty		
Warranty period	18 months	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Proximity Sensors category:

Click to view products by Schneider manufacturer:

Other Similar products are found below:

01.001.5653.1 70.340.1028.0 70.360.2428.0 70.364.4828.0 70.810.1053.0 72.360.1628.0 73.363.6428.0 8027AL20NL2CPXX FYCC8E1-2 9221350022 922AA2W-A9P-L PLS2 GL-12F-C2.5X10(LOT3) 972AB2XM-A3N-L 972AB3XM-A3P-L PS3251 980659-1 QT-12 E2E2-X5M41-M4 E2E-X14MD1-G E2E-X2D1-G E2EX2ME2N E2EX3D1SM1N E2E-X4MD1-G E2E-X5E1-5M-N E2E-X5Y2-N E2E-X7D1-M1J-T-0.3M-N E2FMX1R5D12M E2K-F10MC1 5M EH-302 EI3010TBOP EI5515NPAP MS605AU EP175-32000 IFRM04N35B1/L IFRM04P1513/S35L IFRM06P1703/S35L IFRM08P1501/S35L IFRM12N17G3/L IFRM12P17G3/L IFRM12P3502/L IFRM12P37G1/S14L ILFK12E9189/I02 ILFK12E9193/I02 IMM2582C OISN-013 25.161.3253.0 25.332.0653.1 25.352.0653.0 25.352.0753.0