Product data sheet Characteristics

SM860A1200

Hyde Park, microsonic thru beam transmitter

Main	
Range of Product	Hyde Park
Sensor Type	Ultrasonic sensor
Series name	Standard format
Device short name	SM860
Sensor design	Cylindrical Ø 12 mm plain
Material	Stainless steel
[Us] rated supply voltage	1224 V DC
[Sd] sensing range	1.00 ft (0.305 m)
IP degree of protection	IP67

Complementary

[Sn] nominal sensing distance	1.00 ft (0.305 m)
Type of sensing window	Fixed
Condition of use	Thru beam

Environment

Product Certifications	CE
------------------------	----

Ordering and shipping details

22490 - SENSORS-ULTRASONIC (XX5,6)	22490 - SENSORS-ULTRASONIC (XX5,6)		
DS2			
03389119111973			
1			
0.12 lb(US) (0.05 kg)			
No			
US			
	DS2 03389119111973 1 0.12 lb(US) (0.05 kg) No		

Offer Sustainability

phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
☑REACh Declaration
Not applicable, out of EU RoHS legal scope

Contractual warranty

\	40		
Warrantv	18 months		

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Proximity Sensors category:

Click to view products by Schneider manufacturer:

Other Similar products are found below:

01.001.5653.1 70.340.1028.0 70.360.2428.0 70.364.4828.0 70.810.1053.0 72.360.1628.0 73.363.6428.0 8027AL20NL2CPXX FYCC8E1-2 9221350022 922AA2W-A9P-L PLS2 GL-12F-C2.5X10(LOT3) 972AB2XM-A3N-L 972AB3XM-A3P-L PS3251 980659-1 QT-12 E2E2-X5M41-M4 E2E-X14MD1-G E2E-X2D1-G E2EX2ME2N E2EX3D1SM1N E2E-X4MD1-G E2E-X5E1-5M-N E2E-X5Y2-N E2E-X7D1-M1J-T-0.3M-N E2FMX1R5D12M E2K-F10MC1 5M EH-302 EI3010TBOP EI5515NPAP MS605AU EP175-32000 IFRM04N35B1/L IFRM04P1513/S35L IFRM06P1703/S35L IFRM08P1501/S35L IFRM12N17G3/L IFRM12P17G3/L IFRM12P3502/L IFRM12P37G1/S14L ILFK12E9189/I02 ILFK12E9193/I02 IMM2582C OISN-013 25.161.3253.0 25.332.0653.1 25.352.0653.0 25.352.0753.0