

Product data sheet

Specifications



cartridge M200 - 2 Analog inputs / 1 Analog output

TMCR2AM3

Main

Range of product	Easy Modicon M200
Product or component type	Analogue I/O cartridge
Product compatibility	Easy Modicon M200
Analogue input number	2

Complementary

Analogue input type	current 4...20 mA current 0...20 mA voltage 0...10 V voltage 0...5 V
Analogue input resolution	16 bits
Analogue output number	1
Analogue output type	Current: 4...20 mA Voltage: 0...10 V Current: 0...20 mA Voltage: 0...5 V
Analogue output resolution	16 bits
LSB value	2 µA 0...5 V voltage 4...20 mA current 2 µA 0...10 V voltage 0...20 mA current 1 mV 0...20 mA current 0...5 V voltage 1 mV 4...20 mA current 0...10 V voltage
Load type	Resistive
Load impedance ohmic	<= 500 Ohm >= 2 kOhm
Conversion time	2 ms
Sampling duration	1 ms
Stabilisation time	40 ms
Absolute accuracy error	+/- 1 % of full scale at 55 °C
Cross talk	80 dB
Type of cable	Twisted shielded pairs cable
Electrical connection	7 x 1.5 mm ² screw terminal block with pitch 3.5 mm adjustment for inputs and outputs
Maximum cable distance between devices	Twisted shielded pairs cable: <30 m for input/output
Insulation	Between output and internal logic
Local signalling	1 LED (green) for PWR

Height	41 mm
Depth	15 mm
Width	35 mm
Net weight	0.024 kg
Permissible continuous overload	40 mA, analogue input type: current 30 V, analogue input type: voltage
Input impedance	<= 250 Ohm current >= 1 MOhm voltage

Environment

Marking	CE
---------	----

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5 cm
Package 1 Width	6.3 cm
Package 1 Length	8.9 cm
Package 1 Weight	46 g
Unit Type of Package 2	S02
Number of Units in Package 2	32
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	1830 g
Unit Type of Package 3	P12
Number of Units in Package 3	1536
Package 3 Height	95 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	96840 g

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Recommended replacement(s)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [PLC Controllers](#) category:

Click to view products by [Schneider](#) manufacturer:

Other Similar products are found below :

[3G2A5PS223E](#) [CJ1M-CPU13](#) [CS1W-CN227](#) [CP1H-Y20DT-D](#) [AFP0RDA4](#) [FC6A-C16R1AE](#) [TM200CE24T](#) [TM200C24R](#) [TMCR2AQ2V](#)
[TM200C40T](#) [TM200C40R](#) [TM200CE32R](#) [EASY-BOX-E4-AC1](#) [TMCR2AM3](#) [TM200CE24R](#) [TM200C16T](#) [TM200C24T](#) [6GK1901-1BB30-0AA0](#) [6ES7193-6BP00-0DA1](#) [6ES7155-6AR00-0AN0](#) [6ES7193-6BP40-0DA1](#) [6ES7972-0BB12-0XA0](#) [6ES7193-6BP40-0BA1](#) [6ES7193-6PA00-0AA0](#) [6ES7972-0BB52-0XA0](#) [6ES7135-6GB00-0BA1](#) [6ES7134-6FF00-0AA1](#) [6ES7132-6BD20-0BA0](#) [6ES7131-6BF01-2BA0](#)
[6ES7522-1BL10-0AA0](#) [6ES7134-6JF00-0CA1](#) [6ES7193-6BP20-0BF0](#) [6ES7521-1BL10-0AA0](#) [6ES7226-6RA32-0XB0](#) [6ES7132-6HD01-0BB1](#) [6ES7193-6BP20-0BB1](#) [6ES7590-1AE80-0AA0](#) [6ES7226-6DA32-0XB0](#) [6ES7392-1AJ00-0AA0](#) [6ES7972-0BA12-0XA0](#) [6ES7522-1BL01-0AB0](#) [6ES7226-6BA32-0XB0](#) [CPM2C10CDT1MD](#) [AFP0RC14RS](#) [2906916](#) [2906920](#) [2906921](#) [CJ2M-MD211](#) [CS1W-OA201](#)
[CJ2M-MD212](#)